

Proposal for **Corona Fire Department**

Prepared by **South Coast Fire Equipment, Inc**

11/13/2025



PERFORM. LIKE NO OTHER.™

CONTENTS

GENERAL DESIGN AND CONSTRUCTION..... 15

QUALITY AND WORKMANSHIP 15

DELIVERY 16

MANUAL AND SERVICE INFORMATION 16

SAFETY VIDEO 16

PERFORMANCE TESTS 16

SERVICE AND WARRANTY SUPPORT..... 16

LIABILITY..... 17

INSURANCE PROVIDED BY BIDDER..... 17

 Commercial General Liability Insurance..... 17

 Commercial Automobile Liability Insurance..... 18

 Umbrella/Excess Liability Insurance..... 18

INSURANCE PROVIDED BY MANUFACTURER 18

 Product Liability Insurance 18

 Umbrella/Excess Liability Insurance..... 19

SINGLE SOURCE MANUFACTURER 19

NFPA 2024 STANDARDS..... 19

NFPA COMPLIANCY 20

PUMP TEST 20

GENERATOR TEST 20

BREATHING AIR TEST 20

VEHICLE INSPECTION PROGRAM CERTIFICATION..... 20

INSPECTION TRIP(S) 20

BID BOND NOT REQUESTED 21

PERFORMANCE BOND NOT REQUESTED 21

APPROVAL DRAWING..... 22

ELECTRICAL WIRING DIAGRAMS 22

ENFORCER CHASSIS 23

WHEELBASE..... 23

GVW RATING 23

FRAME 23

FRONT AXLE..... 23

FRONT SUSPENSION 23

SHOCK ABSORBERS 23

FRONT OIL SEALS..... 23

FRONT TIRES 23

REAR AXLE 23

TOP SPEED OF VEHICLE..... 24

REAR SUSPENSION..... 24

REAR OIL SEALS 24

REAR TIRES..... 24

TIRE BALANCE 24

TIRE PRESSURE MANAGEMENT 24

CHROME LUG NUT COVERS..... 24

FRONT HUB COVERS 24

MUD FLAPS 24

WHEEL CHOCKS 25

 Wheel Chock Brackets..... 25

ELECTRONIC STABILITY CONTROL 25

ANTI-LOCK BRAKE SYSTEM 25

AUTOMATIC TRACTION CONTROL..... 25

BRAKES 25

BRAKE SYSTEM AIR COMPRESSOR..... 26

BRAKE SYSTEM 26

BRAKE SYSTEM AIR DRYER 26

BRAKE LINES..... 26

AIR INLET/OUTLET 27

ALL WHEEL LOCK-UP 27

COLOR CODE RESERVOIRS 27

REMOTE AIR TANK DRAIN 27

ENGINE 27

HIGH IDLE 28

CLUTCH FAN 28

FLOOR MOUNT, ACCELERATOR PEDAL..... 28

ENGINE AIR INTAKE..... 28

EXHAUST SYSTEM.....	28
RADIATOR	28
COOLANT LINES	29
RADIATOR SKID PLATE	29
FUEL TANK	29
DIESEL EXHAUST FLUID TANK.....	30
FUEL PRIMING PUMP	30
FUEL SHUTOFF	30
FUEL COOLER.....	30
FUEL/WATER SEPARATOR	30
TRANSMISSION.....	30
TRANSMISSION SHIFTER.....	31
TRANSMISSION COOLER.....	31
DOWNSHIFT MODE (w/engine brake).....	31
TRANSMISSION FLUID.....	32
DRIVELINE	32
STEERING.....	32
STEERING WHEEL	32
LOGO AND CUSTOMER DESIGNATION ON DASH.....	32
BUMPER.....	32
Gravel Pan.....	33
CENTER HOSE TRAY	33
Center Hose Tray Cover	33
TOW EYES	33
FRONT BUMPER NOTCH	33
CAB	33
CAB ROOF DRIP RAIL.....	34
FENDER LINERS	35
PANORAMIC WINDSHIELD	35
WINDSHIELD WIPERS.....	35
ENGINE TUNNEL	35
INSULATION PACKAGE	35
INTERIOR CREW CAB REAR WALL ADJUSTABLE SEATING (PATENT PENDING).....	35

CAB REAR WALL EXTERIOR COVERING 36

CAB LIFT 36

 Cab Lift Interlock..... 36

GRILLE 36

SCUFFPLATE..... 36

SIDE OF CAB MOLDING 36

MIRRORS 36

DOORS..... 37

 Door Panels..... 37

ELECTRIC OPERATED CAB DOOR WINDOWS 37

ELECTRIC CAB DOOR LOCKS..... 38

KEY PAD FOR ELECTRIC DOOR LOCKS 38

CAB STEPS 38

CAB EXTERIOR HANDRAILS 38

STEP LIGHTS..... 38

FENDER CROWNS 38

ADDITIONAL HANDRAIL..... 38

CREW CAB WINDOWS..... 39

CAB ROOF COVERING 39

GLOVE BOX 39

CAB DASH..... 39

MOUNTING PLATE ON ENGINE TUNNEL 39

CAB INTERIOR..... 39

CAB INTERIOR UPHOLSTERY..... 40

CAB INTERIOR PAINT 40

CAB FLOOR 40

DEFROST/AIR CONDITIONING SYSTEM 40

 Cab Defroster 40

 Cab/Crew Auxiliary Heater..... 41

 Air Conditioning 41

 Climate Control..... 41

 Gravity Drain Tubes..... 42

BRUSH GUARD..... 42

120 VOLT AIR CONDITIONING.....	42
INTERIOR CAB INSULATION	42
SUN VISORS.....	42
GRAB HANDLES	42
ENGINE COMPARTMENT LIGHTS.....	42
ACCESS TO ENGINE DIPSTICKS	43
MAP BOX WITH CUP HOLDERS	43
SEATING CAPACITY.....	43
DRIVER SEAT	43
OFFICER SEAT	43
FORWARD FACING DRIVER SIDE OUTBOARD SEAT.....	44
FORWARD FACING CENTER SEAT.....	44
FORWARD FACING PASSENGER SIDE OUTBOARD SEAT	44
STORAGE CABINET	44
SEAT UPHOLSTERY.....	44
AIR BOTTLE HOLDERS	45
SEAT EMBROIDERY	45
FOOT REST ANGLE.....	45
SEAT BELTS	45
HELMET STORAGE PROVIDED BY FIRE DEPARTMENT	45
CAB DOME LIGHTS	46
CAB SPOTLIGHT	46
Spotlight Controller	46
Spotlight Controller Locations	46
PORTABLE HAND LIGHTS PROVIDED BY DEALER.....	46
CAB INSTRUMENTATION.....	46
Gauges.....	46
Indicator Lamps	48
Alarms	49
Indicator Lamp and Alarm Prove-Out.....	49
Control Switches.....	49
Custom Switch Panels.....	50
Diagnostic Panel.....	50

Cab LCD Display 51

AIR RESTRICTION INDICATOR..... 51

"DO NOT MOVE APPARATUS" INDICATOR 51

DO NOT MOVE TRUCK MESSAGES..... 51

SWITCH PANELS 52

WIPER CONTROL..... 52

CAB USB 52

SPARE CIRCUIT 53

SPARE CIRCUIT 53

SPARE CIRCUIT 53

SPARE CIRCUIT 54

SPARE CIRCUIT 54

STEREO RADIO 54

INFORMATION CENTER..... 55

 General Screen Design..... 55

 Home/Transit Screen..... 56

 On Scene Screen 56

 Virtual Buttons 56

 Page Screen..... 56

VEHICLE DATA RECORDER 58

 Seat Belt Monitoring System..... 59

VEHICLE CAMERA SYSTEM 59

 Camera Switcher 60

ELECTRICAL POWER CONTROL SYSTEM 60

 Solid-State Control System..... 60

 Circuit Protection and Control Diagram..... 61

 On-Board Electrical System Diagnostics..... 61

 TCU Module with WiFi 62

 Indicator Light and Alarm Prove-Out System 62

 Voltage Monitor System..... 62

 Dedicated Radio Equipment Connection Points..... 62

 EMI/RFI Protection 62

ELECTRICAL SYSTEM PROGNOSTICS 63

ELECTRICAL 63

BATTERY SYSTEM 64

ISOLATED BATTERY 64

BATTERY SYSTEM 64

MASTER BATTERY SWITCH 64

BATTERY COMPARTMENTS 64

JUMPER STUDS 65

INVERTER / BATTERY CHARGER 65

BATTERY CHARGE DISPLAY 65

AUTO EJECT FOR SHORELINE 66

BATTERY SAVER 66

ALTERNATOR 66

ELECTRONIC LOAD MANAGER 66

SEQUENCER 67

HEADLIGHTS 68

FRONT DIRECTIONALS 68

INTERMEDIATE LIGHT 68

CAB CLEARANCE LIGHTS 68

FRONT CAB SIDE DIRECTIONAL/MARKER LIGHTS 68

REAR CLEARANCE/MARKER/ID LIGHTING 68

REAR FMVSS LIGHTING 69

LICENSE PLATE BRACKET 69

LIGHTING BEZEL 70

ADDITIONAL BRAKE/TAIL LIGHT 70

BACK-UP ALARM 70

WARNING LIGHT FLASH PATTERN 70

CAB PERIMETER SCENE LIGHTS 70

PUMP HOUSE PERIMETER LIGHTS 70

BODY PERIMETER SCENE LIGHTS 70

ADDITIONAL PERIMETER LIGHTS 71

ENHANCED SOFTWARE FOR PERIMETER LIGHTS 71

STEP LIGHTS 71

SIDE SCENE LIGHTS 71

SCENE LIGHTS..... 71

SIDE SCENE LIGHTS..... 71

12 VOLT LIGHTING 72

12 VOLT LIGHTING - BODY 72

HOSE BED LIGHTS..... 72

WALKING SURFACE LIGHT 72

MASTER SWITCH FOR BODY COMPARTMENT LIGHTS 72

WATER TANK..... 72

SLEEVE PLUMBING THROUGH TANK 73

HOSE BED 74

HOSE BED DIVIDER 74

HOSE BED COVER..... 74

RUNNING BOARDS 75

TAILBOARD..... 75

REAR WALL, SMOOTH ALUMINUM/BODY MATERIAL 75

REAR TOW EYES 75

REAR TOW BAR 75

RUNNING BOARD HOSE RESTRAINT..... 76

HOSE TRAY 76

COMPARTMENTATION 76

UNDERBODY SUPPORT SYSTEM..... 76

AGGRESSIVE WALKING SURFACE 77

LOUVERS..... 77

TESTING OF BODY DESIGN 77

LEFT SIDE COMPARTMENTATION 78

RIGHT SIDE COMPARTMENTATION 78

SIDE COMPARTMENT ROLLUP DOOR(S) 79

REAR COMPARTMENTATION..... 79

REAR COMPARTMENT DOORS 80

DOOR GUARD 80

ELECTRIC DOOR LOCKS..... 80

ELECTRIC DOOR LOCKS..... 80

COMPARTMENT LIGHTING 80

HATCH COMPARTMENT 81

HATCH COMPARTMENT 81

COMPARTMENT LIGHTING 81

CARGO/DUNNAGE AREA LIGHTING 82

MOUNTING TRACKS 82

ADJUSTABLE SHELVES..... 82

SLIDE-OUT FLOOR MOUNTED TRAY..... 82

DRAWER ASSEMBLY 83

PARTITION, TRANSVERSE REAR COMPARTMENT..... 83

COMPARTMENT DUST FILTERS..... 83

RUB RAIL 83

BODY FENDER CROWNS 83

BODY FENDER LINER..... 84

HARD SUCTION HOSE..... 84

HANDRAILS 84

HANDRAILS 84

HANDRAIL..... 84

ADDITIONAL HANDRAIL..... 84

EXTINGUISHER/AIR BOTTLE/ STORAGE (Triangular) 84

AIR BOTTLE COMPARTMENT STRAP..... 84

AIR BOTTLE STORAGE (Triple)..... 85

 Air Bottle Compartment Strap 85

EXTINGUISHER STORAGE 85

EXTENSION LADDER 85

ROOF LADDER 85

LADDER STORAGE 85

FOLDING LADDER..... 85

FOLDING LADDER STORAGE 86

PIKE POLE 8 FT 86

PIKE POLE STORAGE 86

6' PIKE POLE..... 86

PIKE POLE STORAGE 86

TRASH HOOK STORAGE 86

PIKE POLE STORAGE	86
I-ZONE BRACKETS	86
PUMP COMPARTMENT	86
PUMP MOUNTING	87
LEFT SIDE PUMP CONTROL PANEL	87
IDENTIFICATION TAGS	87
MIDSHIP FIRE PUMP	88
MECHANICAL SEAL ON PUMP	89
PUMP TRANSMISSION	89
PUMPING MODE	89
AIR PUMP SHIFT	89
TRANSMISSION LOCK-UP	90
AUXILIARY COOLING SYSTEM	90
INTAKE RELIEF VALVE - PUMP	90
PRESSURE CONTROLLER	90
PRIMING PUMP	92
PUMP DRAIN	92
RECIRCULATING LINE WITH CHECK VALVE	92
THERMAL RELIEF VALVE	92
PUMP MANUALS	92
PLUMBING, STAINLESS STEEL AND HOSE	92
FOAM SYSTEM PLUMBING	93
MAIN PUMP INLETS	93
SHORT SUCTION TUBE(S)	93
MAIN PUMP INLET CAP PROVIDED BY FIRE DEPARTMENT	93
VALVES	93
INLET CONTROL	93
LEFT SIDE INLET	93
ANODE, INLET	93
INLET BLEEDER VALVE	93
TANK TO PUMP	94
TANK REFILL	94
DISCHARGE OUTLET CONTROLS	94

LEFT SIDE DISCHARGE OUTLETS.....	94
LEFT SIDE OUTLET ELBOWS.....	94
RIGHT SIDE DISCHARGE OUTLETS	95
RIGHT SIDE OUTLET ELBOWS.....	95
LARGE DIAMETER DISCHARGE OUTLET.....	95
LARGE DIAMETER OUTLET ELBOWS.....	95
FRONT DISCHARGE OUTLET.....	95
REAR DISCHARGE OUTLET	95
REAR OUTLET ELBOWS.....	95
DISCHARGE CAPS/ INLET PLUGS	96
OUTLET BLEEDER VALVE	96
ADAPTER	96
DELUGE RISER	96
MONITOR.....	97
CROSSLAY HOSE BEDS, 1.50"	97
DEADLAY HOSE BEDS.....	97
CROSSLAY/DEADLAY HOSE RESTRAINT	97
CROSSLAY COVER.....	98
CROSSLAY 8.00" LOWER THAN STANDARD.....	98
BOOSTER HOSE REEL	98
PRESSURE GAUGE.....	98
FOAM CONCENTRATE PROPORTIONING SYSTEM	98
FOAM TANK	99
FOAM TANK DRAIN.....	99
PUMP PANEL CONFIGURATION	99
PUMP AND GAUGE PANEL.....	99
PUMP ACCESS	99
Right Side Panel.....	99
Panel Fastener	99
PUMP COMPARTMENT LIGHT.....	100
PUMP PANEL GAUGES AND CONTROLS.....	100
THROTTLE READY GREEN INDICATOR LIGHT.....	100
OK TO PUMP INDICATOR LIGHT.....	100

FUEL GAUGE	100
AIR HORN BUTTON.....	100
PUMP HOUSE - FRONT PANEL	100
VACUUM AND PRESSURE GAUGES.....	100
PRESSURE GAUGES	101
WATER LEVEL GAUGE	101
ADDITIONAL WATER LEVEL GAUGE(S)	101
CLASS "A" FOAM LEVEL GAUGE	101
LIGHT SHIELD.....	102
ADDITIONAL LIGHT SHIELD	102
AIR HORN SYSTEM.....	102
Air Horn Location.....	102
Air Horn Control.....	103
ELECTRONIC SIREN	103
SPEAKER	103
AUXILIARY MECHANICAL SIREN	103
MECHANICAL SIREN CONTROL.....	103
FRONT ZONE UPPER WARNING LIGHTS	104
LIGHTS, FRONT ZONE LOWER	105
DAYTIME RUNNING LIGHTS (HEADLIGHTS).....	105
HEADLIGHT FLASHER	105
SIDE ZONE LOWER LIGHTING	105
REAR ZONE LOWER LIGHTING.....	106
REAR WARNING LIGHTS	106
WARNING LIGHTS (Rear and Side upper zones).....	106
TRAFFIC DIRECTING LIGHT	106
LOOSE EQUIPMENT.....	107
NFPA LOOSE EQUIPMENT	107
NFPA Required Loose Equipment Provided by Fire Department.....	107
NFPA Loose Equipment That Should be Considered	107
SOFT SUCTION HOSE	108
DRY CHEMICAL EXTINGUISHER PROVIDED BY FIRE DEPARTMENT	108
WATER EXTINGUISHER PROVIDED BY FIRE DEPARTMENT	108

FLATHEAD AXE PROVIDED BY FIRE DEPARTMENT 108

PICKHEAD AXE PROVIDED BY FIRE DEPARTMENT 108

PAINT PROCESS 108

 Environmental Impact 109

CAB PAINT 110

BODY PAINT 110

PAINT CHASSIS FRAME ASSEMBLY..... 110

AXLE HUB PAINT 110

COMPARTMENT INTERIOR PAINT 110

REFLECTIVE BAND 111

REAR CHEVRON STRIPING..... 111

"Z" JOG IN REFLECTIVE STRIPE..... 111

REFLECTIVE OUTLINE STRIPE 111

INVERTED "V" CHEVRON STRIPING ON CAB AND CREW CAB DOORS 111

FIRE APPARATUS PARTS MANUAL..... 111

 Service Parts Internet Site 112

CHASSIS SERVICE MANUALS..... 112

CHASSIS OPERATION MANUAL..... 112

ONE (1) YEAR MATERIAL AND WORKMANSHIP 112

ENGINE WARRANTY 112

STEERING GEAR WARRANTY..... 112

FIFTY (50) YEAR STRUCTURAL INTEGRITY..... 113

FRONT AXLE WARRANTY 113

SINGLE REAR AXLE FIVE (5) YEAR MATERIAL AND WORKMANSHIP WARRANTY 113

ABS BRAKE SYSTEM THREE (3) YEAR MATERIAL AND WORKMANSHIP WARRANTY 113

TEN (10) YEAR STRUCTURAL INTEGRITY 113

TEN (10) YEAR PRO-RATED PAINT AND CORROSION..... 113

FIVE (5) YEAR MATERIAL AND WORKMANSHIP 113

CAMERA SYSTEM WARRANTY 113

COMPARTMENT LIGHT WARRANTY..... 113

TRANSMISSION WARRANTY 113

TRANSMISSION COOLER WARRANTY..... 113

WATER TANK WARRANTY 113

TEN (10) YEAR STRUCTURAL INTEGRITY	114
ROLLUP DOOR MATERIAL AND WORKMANSHIP WARRANTY	114
PUMP WARRANTY	114
TEN (10) YEAR PUMP PLUMBING WARRANTY	114
TEN (10) YEAR PRO-RATED PAINT AND CORROSION.....	114
VEHICLE STABILITY CERTIFICATION.....	114
ENGINE INSTALLATION CERTIFICATION	114
POWER STEERING CERTIFICATION	114
CAB INTEGRITY CERTIFICATION.....	114
Side Impact.....	115
Frontal Impact.....	115
Additional Frontal Impact	115
Roof Crush	115
Additional Roof Crush.....	115
CAB DOOR DURABILITY CERTIFICATION	115
WINDSHIELD WIPER DURABILITY CERTIFICATION	115
ELECTRIC WINDOW DURABILITY CERTIFICATION	115
SEAT BELT ANCHOR STRENGTH.....	115
SEAT MOUNTING STRENGTH.....	116
PERFORMANCE CERTIFICATIONS.....	116
Cab Air Conditioning.....	116
Cab Defroster	116
Cab Auxiliary Heater.....	116
AMP DRAW REPORT.....	116

South Coast Fire Equipment is pleased to submit a proposal to Corona Fire Department for a **Pierce® triple combination pumper** per your request for quotation. The following paragraphs will describe in detail the apparatus, construction methods, and equipment proposed. This proposal will indicate size, type, model and make of components parts and equipment, providing proof of compliance with each and every item (except where noted) in the departments advertised specifications.

PIERCE MANUFACTURING was founded in 1913. Since then, we have been building bodies with one philosophy, "BUILD THE FINEST". Our skilled craftsmen take pride in their work, which is reflected, in the final product. We have been building fire apparatus since the early "forties" giving Pierce Manufacturing over 75 years of experience in the fire apparatus market. Pierce Manufacturing has built and put into service more than 62,500 apparatus, including more than 33,900 on Pierce custom chassis designed and built specifically for fire and emergency applications. Our Appleton, Wisconsin facility has over 870,000 total square feet of floor space situated on approximately 105 acres of land. Our Bradenton, Florida facility has 300,000 square feet of floor space situated on approximately 38 acres of land.

Our beliefs in high ethical standards are carried through in all of our commitments and to everyone with whom we do business. Honesty, Integrity, Accountability and Citizenship are global tenets by which we all live and work. Consequently, we neither engage in, nor have we ever been convicted of price fixing, bid rigging, or collusion in any domestic or international fire apparatus market.

Pierce has only one brand of fire apparatus "Pierce", ensuring you are receiving top of the line product that meets your specification.

In accordance with the current edition of applicable NFPA standards, this proposal will specify whether the fire department, manufacturer, or apparatus dealership will provide required loose equipment.

Images and illustrative material in this proposal are as accurate as known at the time of publication but are subject to change without notice. Images and illustrative material are for reference only and may include optional equipment and accessories and may not include all standard equipment.

GENERAL DESIGN AND CONSTRUCTION

To control quality, ensure compatibility, and provide a single source for service and warranty, the custom cab, chassis, pump module and body will be entirely designed, assembled/welded and painted in Pierce owned manufacturing facilities. This includes, but not limited to the cab weldment, the pumphouse module assembly, the chassis assembly, the body and the electrical system.

QUALITY AND WORKMANSHIP

Pierce has set the pace for quality and workmanship in the fire apparatus field. Our tradition of building the highest quality units with craftsmen second to none has been the rule right from the beginning and we demonstrate that ongoing commitment by: Ensuring all steel welding follows American Welding Society D1.1-2004 recommendations for structural steel welding. All aluminum welding follows American Welding society and ANSI D1.2-2003 requirements for structural welding of aluminum. All sheet metal welding follows American welding Society B2.1-2000 requirements for structural welding of sheet metal. Our flux core arc welding uses alloy rods, type 7000 and is performed to American Welding Society standards A5.20-E70T1. Furthermore, all employees classified as welders are tested

and certified to meet the American welding Society codes upon hire and every three (3) years thereafter. Pierce also employs an American Welding Society certified welding inspector in plant during working hours to monitor weld quality.

Pierce Manufacturing operates a Quality Management System under the requirements of ISO 9001. These standards sponsored by the International Organization for Standardization (ISO) specify the quality systems that are established by the manufacturer for design, manufacture, installation and service. A copy of the certificate of compliance is included with this proposal.

In addition to the Quality Management system, we also employ a Quality Achievement Supplier program to ensure the vendors and suppliers that we utilize meet the high standards we demand. That is just part of our overall "Quality at the Source" program at Pierce.

To demonstrate the quality of our products and services, a list of at least fifteen (15) fire departments/municipalities that have purchased vehicles for a second time is provided.

DELIVERY

The apparatus will be delivered under its own power to ensure proper break-in of all components while the apparatus is still under warranty. A qualified delivery representative shall deliver the apparatus and remain for a sufficient length of time to instruct personnel in proper operation, care and maintenance of the equipment delivered.

MANUAL AND SERVICE INFORMATION

At time of delivery, complete operation and maintenance manuals covering the apparatus will be provided. A permanent plate will be mounted in the driver's compartment specifying the quantity and type of fluids required including engine oil, engine coolant, transmission, pump transmission lubrication, pump primer and drive axle.

SAFETY VIDEO

At the time of delivery Pierce will also provide one (1) 39-minute, professionally produced apparatus safety video, in DVD format. A link to the video is also available on the Pierce Training website. This video will address key safety considerations for personnel to follow when they are driving, operating, and maintaining the apparatus, including the following: vehicle pre-trip inspection, chassis operation, pump operation, aerial operation, and safety during maintenance.

PERFORMANCE TESTS

A road test will be conducted with the apparatus fully loaded and a continuous run of no less than ten (10) miles. During that time the apparatus will show no loss of power, nor will it overheat. The transmission drive shaft or shafts and the axles will run quietly and be free of abnormal vibration or noise. The apparatus when fully loaded will not have less than 25 percent nor more than 50 percent on the front axle, and not less than 50 percent nor more than 75 percent on the rear axle. The apparatus will meet the current edition of applicable NFPA standards acceleration and braking requirements.

SERVICE AND WARRANTY SUPPORT

Pierce dealership support will be provided by ReNewell Fleet Services by operating in conjunction with a Pierce authorized service center. The service center will have factory-trained mechanics on staff

versed in Pierce fire apparatus. The service facility will be located within twenty five (25) miles of the fire department.

In addition to the dealership, Pierce has service facilities located in both, Weyauwega, Wisconsin and Bradenton, Florida. Pierce also maintains a dedicated parts facility of over 100,000 square feet in Appleton, Wisconsin. The parts facility stocks in excess of \$5,000,000 in parts dedicated to service and replacement parts. The parts facility employs a staff dedicated solely for the distribution and shipment of service and replacement parts.

Service parts for the apparatus being proposed can be found via Pierceparts.com which, is an interactive online tool that delivers information regarding your specific apparatus as well as the opportunity to register for training classes.

As a Pierce customer you have the ability to view the complete bill of materials for your specific apparatus, including assembly drawings, piece part drawings, and beneficial parts notations. You will also have the ability to search the complete Pierce item master through a parts search function which offers all Pierce SKU's and descriptions offered on all Pierce apparatus. Published component catalogs, which include proprietary systems along with an extensive operator's manual library is available for easy reference.

Pierce Manufacturing maintains a dedicated service and warranty staff of over 35 personnel, dedicated to customer support, which also maintains a 24 hour 7 day a week toll free hot line, four (4) on staff EVTs, and offers hands-on repair and maintenance training classes multiple times a year.

LIABILITY

The successful bidder will defend any and all suits and assume all liability for the use of any patented process including any device or article forming a part of the apparatus or any appliance furnished under the contract.

INSURANCE PROVIDED BY BIDDER

Commercial General Liability Insurance

The successful bidder will, during the performance of the contract and for three (3) years following acceptance of the product, keep in force at least the following minimum limits of commercial general liability insurance:

Each Occurrence:	\$1,000,000
Products/Completed Operations Aggregate:	\$1,000,000
Personal and Advertising Injury:	\$1,000,000
General Aggregate:	\$2,000,000

Coverage will be written on a Commercial General Liability form. The policy will be written on an occurrence form and will include Contractual Liability coverage for bodily injury and property damage subject to the terms and conditions of the policy. The policy will include Owner as an additional insured when required by written contract.

Commercial Automobile Liability Insurance

The successful bidder will, during the performance of the contract, keep in force at least the following minimum limits of commercial automobile liability insurance and coverage will be written on a Commercial Automobile liability form:

Each Accident Combined Single Limit:	\$1,000,000
--------------------------------------	-------------

Umbrella/Excess Liability Insurance

The successful bidder will, during the performance of the contract and for three (3) years following acceptance of the product, keep in force at least the following minimum limits of umbrella liability insurance:

Aggregate:	\$3,000,000
Each Occurrence:	\$3,000,000

The umbrella policy will be written on an occurrence basis and at a minimum provide excess to the bidder's General Liability and Automobile Liability policies.

The required limits can be provided by one (1) or more policies provided all other insurance requirements are met.

Coverage will be provided by a carrier(s) rated A- or better by A.M. Best.

All policies will provide a 30-day notice of cancellation to the named insured. The Certificate of Insurance will provide the following cancellation clause: Should any of the above described polices be cancelled before the expiration date thereof, notice will be delivered in accordance with the policy provisions.

Bidder agrees to furnish owner with a current Certificate of Insurance with the coverages listed above along with the bid. The certificate will show the purchaser as certificate holder.

INSURANCE PROVIDED BY MANUFACTURER

Product Liability Insurance

The manufacturer will, during the performance of the contract and for three (3) years following acceptance of the product, keep in force at least the following minimum limits of Product Liability insurance:

Each Occurrence:	\$1,000,000
Products/Completed Operations Aggregate:	\$1,000,000

Coverage will be written on a Commercial General Liability form. The policy will be written on an occurrence form. The manufacturer's policy will include the owner as additional insured when required by written contract between the Owner and a Pierce authorized dealer.

Umbrella/Excess Liability Insurance

The manufacturer will, during the performance of the contract and for three (3) years following acceptance of the product, keep in force at least the following minimum limits of umbrella liability insurance:

Each Occurrence:	\$25,000,000
Aggregate:	\$25,000,000

The umbrella policy will be written on an occurrence basis and provide excess to the manufacturer's General Liability/Products policies.

The required limits can be provided by one (1) or more policies provided all other insurance requirements are met.

Coverage will be provided by a carrier(s) rated A- or better by A.M. Best.

All policies will provide a 30-day notice of cancellation to the named insured. The Certificate of Insurance will provide the following cancellation clause: Should any of the above described policies be cancelled before the expiration date thereof, notice will be delivered in accordance with the policy provisions.

Manufacturer agrees to furnish owner with a current Certificate of Insurance with the coverages listed above along with the bid. The certificate will show the purchaser as the certificate holder.

SINGLE SOURCE MANUFACTURER

Pierce Manufacturing, Inc. provides an integrated approach to the design and manufacture of our products that delivers superior apparatus and a dedicated support team. From our facilities, the chassis, cab weldment, cab, pumphouse (including the sheet metal enclosure, valve controls, piping and operators panel) and body will be entirely designed, tested, and hand assembled to the customer's exact specifications. The electrical system either hardwired or multiplexed, will be both designed and integrated by Pierce Manufacturing. The warranties relative to these major components (excluding component warranties such as engine, transmission, axles, pump, etc.) will be provided by Pierce as a single source manufacturer. Pierce's single source solution adds value by providing a fully engineered product that offers durability, reliability, maintainability, performance, and a high level of quality.

Your apparatus will be manufactured in Appleton, Wisconsin.

NFPA 2024 STANDARDS

This unit will comply with the NFPA standards effective January 1, 2024, except for fire department directed exceptions. These exceptions will be set forth in the Statement of Exceptions.

Certification of slip resistance of all stepping, standing and walking surfaces will be supplied with delivery of the apparatus.

All horizontal surfaces designated as a standing or walking surface that are greater than 48.00" above the ground must be defined by a 1.00" wide line along its outside perimeter. Perimeter markings and designated access paths to destination points will be identified on the customer approval print and are

shown as approximate. Actual location(s) will be determined based on materials used and actual conditions at final build. Access paths may pass through hose storage areas and opening or removal of covers or restraints may be required. Access paths may require the operation of devices and equipment such as the aerial device or ladder rack.

A plate that is highly visible to the driver while seated will be provided. This plate will show the overall height, length, and gross vehicle weight rating.

The manufacturer will have programs in place for training, proficiency testing and performance for any staff involved with certifications.

An official of the company will designate, in writing, who is qualified to witness and certify test results.

NFPA COMPLIANCY

Apparatus proposed by the bidder will meet the applicable requirements of the National Fire Protection Association (NFPA) as stated in current edition at time of contract execution. Fire department's specifications that differ from NFPA specifications will be indicated in the proposal as "non-NFPA".

PUMP TEST

Underwriters Laboratory (UL) will test, approved, and certify the pump. The test results and the pump manufacturer's certification of hydrostatic test; the engine manufacturer's certified brake horsepower curve; and the pump manufacturer's record of pump construction details will be forwarded to the Fire Department.

GENERATOR TEST

If the unit has a generator, Underwriters Laboratory (UL) will test, approved, and certify the generator. The test results will be provided to the Fire Department at the time of delivery.

BREATHING AIR TEST

If the unit has breathing air, Pierce Manufacturing will draw an air sample from the air system and have the sample certified that the air quality meets the requirements of NFPA 1989, *Standard on Breathing Air Quality for Fire and Emergency Services Respiratory Protection*.

VEHICLE INSPECTION PROGRAM CERTIFICATION

To assure the vehicle is built to current NFPA 1900 standards, the apparatus, in its entirety, will be third-party, independent, audit-certified through Underwriters Laboratory (UL) that it is built and complies to all applicable standards in the current edition. The certification includes: all design, production, operational, and performance testing of not only the apparatus, but those components that are installed on the apparatus.

A placard will be affixed in the driver's side area stating the third party agency, the date, the standard and the certificate number of the whole vehicle audit.

INSPECTION TRIP(S)

The bidder will provide three (3) factory inspection trip(s) for four customer representative(s). The inspection trip(s) will be scheduled at times mutually agreed upon between the manufacturer's

representative and the customer. All costs such as travel, lodging and meals will be the responsibility of the bidder.

BID BOND NOT REQUESTED

A bid bond will not be included. If requested, the following will apply:

All bidders will provide a bid bond as security for the bid in the form of a 5 percent bid bond to accompany their bid. This bid bond will be issued by a Surety Company who is listed on the U.S. Treasury Departments list of acceptable sureties as published in Department Circular 570. The bid bond will be issued by an authorized representative of the Surety Company and will be accompanied by a certified power of attorney dated on or before the date of bid. The bid bond will include language, which assures that the bidder/principal will give a bond or bonds as may be specified in the bidding or contract documents, with good and sufficient surety for the faithful performance of the contract, including the Basic One (1) Year Limited Warranty, and for the prompt payment of labor and material furnished in the prosecution of the contract.

Notwithstanding any document or assertion to the contrary, any surety bond related to the sale of a vehicle will apply only to the Basic One (1) Year Limited Warranty for such vehicle. Any surety bond related to the sale of a vehicle will not apply to any other warranties that are included within this bid (OEM or otherwise) or to the warranties (if any) of any third party of any part, component, attachment or accessory that is incorporated into or attached to the vehicle. In the event of any contradiction or inconsistency between this provision and any other document or assertion, this provision will prevail.

PERFORMANCE BOND NOT REQUESTED

A performance bond will not be included. If requested at a later date, one will be provided to you for an additional cost and the following will apply:

The successful bidder will furnish a Performance and Payment bond (Bond) equal to 100 percent of the total contract amount within 30 days of the notice of award. Such Bond will be in a form acceptable to the Owner and issued by a surety company included within the Department of Treasury's Listing of Approved Sureties (Department Circular 570) with a minimum A.M. Best Financial Strength Rating of A and Size Category of XV. In the event of a bond issued by a surety of a lesser Size Category, a minimum Financial Strength rating of A+ is required.

Bidder and Bidder's surety agree that the Bond issued hereunder, whether expressly stated or not, also includes the surety's guarantee of the vehicle manufacturer's Bumper to Bumper warranty period included within this proposal. Owner agrees that the penal amount of this bond will be simultaneously amended to 25 percent of the total contract amount upon satisfactory acceptance and delivery of the vehicle(s) included herein. Notwithstanding anything contained within this contract to the contrary, the surety's liability for any warranties of any type will not exceed three (3) years from the date of such satisfactory acceptance and delivery, or the actual Bumper to Bumper warranty period, whichever is shorter.

Due to global supply chain constraints, any delivery date contained herein is a good faith estimate as of the date of this order/contract, and merely an approximation based on current information. Delivery updates will be made available, and a final firm delivery date will be provided as soon as possible.

If the Producer Price Index of Components for Manufacturing [www.bls.gov Series ID: WPUID6112] ("PPI") has increased at a compounded annual growth rate of 5.0% or more between the month Pierce accepts the order ("Order Month") and a month 14 months prior to the then predicted Ready For Pickup date ("Evaluation Month"), then pricing may be updated in an amount equal to the increase in PPI over 5.0% for each year or fractional year between the Order Month and the Evaluation Month. The seller will document any such updated price for the customer's approval before proceeding and provide an option to cancel the order.

APPROVAL DRAWING

A drawing of the proposed apparatus will be prepared and provided to the purchaser for approval before construction begins. The Pierce sales representative will also be provided with a copy of the same drawing. The finalized and approved drawing will become part of the contract documents. This drawing will indicate the chassis make and model, location of the lights, siren, horns, compartments, major components, etc.

A "revised" approval drawing of the apparatus will be prepared and submitted by Pierce to the purchaser showing any changes made to the approval drawing.

ELECTRICAL WIRING DIAGRAMS

Three (3) USB flash drives containing "As-Built" electrical wiring diagrams specifically prepared for the chassis and body will be provided. The diagrams will consist of information pertaining to the 12 VDC systems only. Two (2) flash drives will be shipped with the loose equipment with each truck. One (1) flash drive will be included with the job folder at apparatus builders facility for future reference.

Each flash drive will include the following capabilities:

- The capability of viewing each separate diagram.
- The capability of zooming in on any section of each separate diagram.
- The capability of printing each separate diagram.
- The capability of printing each zoomed in area of each separate diagram.

Each flash drive will include the following items:

- Title page, identifying the job number and chassis model.
- Table of contents.
- Truck specific electrical compartment and instrument layouts for the chassis.
- Truck specific electrical compartment layouts for the body.
- Applicable drawings from the appropriate standard wiring diagrams.
- All truck specific wiring diagrams (special drawings).
- Harness drawings for all wiring harnesses used on the chassis.
- Harness drawings for all wiring harnesses used on the body.
- All truck input and output programming sheets (multiplexed trucks only).

There will be no hard copies of these diagrams required for this unit.

ENFORCER CHASSIS

The Pierce Enforcer™ is the custom chassis developed exclusively for the fire service. Chassis provided will be a new, tilt-type custom fire apparatus. The chassis will be manufactured in the apparatus body builder's facility eliminating any split responsibility. The chassis will be designed and manufactured for heavy-duty service, with adequate strength, capacity for the intended load to be sustained, and the type of service required. The chassis will be the manufacturer's first line tilt cab.

WHEELBASE

The wheelbase of the vehicle will be 184.5.

GVW RATING

The gross vehicle weight rating will be 44,000.

FRAME

The chassis frame will be built with two (2) steel channels bolted to five (5) cross members or more, depending on other options of the apparatus. The side rails will have a 13.38" tall web over the front and mid sections of the chassis, with a continuous smooth taper to 10.75" over the rear axle. Each rail will have a section modulus of 25.992 cubic inches and a resisting bending moment (rbm) of 3,119,040 in-lb over the critical regions of the frame assembly, with a section modulus of 18.96 cubic inches with an rbm of 2,275,200 in-lb over the rear axle. The frame rails will be constructed of 120,000 psi yield strength heat-treated 0.38" thick steel with 3.50" wide flanges.

FRONT AXLE

The front axle will be a reverse "I" beam type with inclined king pins. It will be a Hendrickson SteerTek™ axle, with a rated capacity of 20,000 lb.

FRONT SUSPENSION

The front springs will be a Hendrickson, Steertek™ NXT, taper leaf design, with a ground rating of 20,000 lb.

SHOCK ABSORBERS

Hendrickson Steertek shock absorbers will be provided on the front axle.

FRONT OIL SEALS

Oil seals with viewing window will be provided on the front axle.

FRONT TIRES

Front tires will be Michelin radials 385/65R22.5, load range J, all position XZY3 wide base tread, rated for 20,052 lb maximum axle load and 65 mph maximum speed.

The tires will be mounted on Alcoa 22.50" x 12.25" polished aluminum disc type wheels with a ten (10) stud, 11.25" bolt circle.

REAR AXLE

The rear axle will be a Meritor™, Model RS-23-186, with a capacity of 24,000 lb.

TOP SPEED OF VEHICLE

A rear axle ratio will be furnished to allow the vehicle to reach a top speed of 68 mph / 109 kph.

REAR SUSPENSION

The rear suspension will be Standens, semi-elliptical, 3.00" wide x 52.50" long, with a ground rating of 24,000 lb. The spring hangers will be castings.

The two (2) top leaves will wrap the forward spring hanger pin, and the rear of the spring will be a slipper style end that will ride in a rear slipper hanger.

A steel encased rubber bushing will be used in the spring eye. The steel encased rubber bushing will be maintenance free and require no lubrication.

REAR OIL SEALS

Oil seals will be provided on the rear axle(s).

REAR TIRES

Rear tires will be four (4) Michelin 12R22.50 radials, 16 ply "all position" XZE* tread, rated for 27,120 lb maximum axle load and 75 mph maximum speed.

The tires will be mounted on Alcoa 22.50" x 8.25" polished aluminum disc wheels with a ten (10) stud 11.25" bolt circle.

TIRE BALANCE

All tires will be balanced with Counteract balancing beads. The beads will be inserted into the tire and eliminate the need for wheel weights.

TIRE PRESSURE MANAGEMENT

There will be a RealWheels LED AirSecure™ tire alert pressure management system provided, that will monitor each tire's pressure. A sensor will be provided on the valve stem of each tire for a total of six (6) tires.

The sensor will calibrate to the tire pressure when installed on the valve stem for pressures between 10 and 200 psi. The sensor will activate an integral battery operated LED when the pressure of that tire drops 5 to 8 psi.

Removing the cap from the sensor will indicate the functionality of the sensor and battery. If the sensor and battery are in working condition, the LED will immediately start to flash.

CHROME LUG NUT COVERS

Chrome lug nut covers will be supplied on front and rear wheels.

FRONT HUB COVERS

Stainless steel hub covers will be provided on the front axle. An oil level viewing window will be provided.

MUD FLAPS

Mud flaps will be installed behind the front and rear wheels. The mud flaps will be black.

WHEEL CHOCKS

There will be one (1) pair of folding Ziamatic, Model SAC-44-E, aluminum alloy, Quick-Choc wheel blocks, with easy-grip handle provided.

Wheel Chock Brackets

There will be one (1) pair of Zico, Model SQCH-44-H, horizontal mounting wheel chock brackets provided for the Ziamatic, Model SAC-44-E, folding wheel chocks. The brackets will be made of aluminum and consist of a quick release spring loaded rod to hold the wheel chocks in place. The brackets will be mounted below the left side rear compartment.

ELECTRONIC STABILITY CONTROL

A vehicle control system will be provided as an integral part of the ABS brake system from Meritor Wabco.

The system will monitor and update the lateral acceleration of the vehicle and compare it to a critical threshold where a side roll event may occur. If the critical threshold is met, the vehicle control system will automatically reduce engine RPM, engage the engine retarder (if equipped), and selectively apply brakes to the individual wheel ends of the front and rear axles to reduce the possibility of a side roll event.

The system will monitor directional stability through a lateral accelerometer, steer angle sensor and yaw rate sensor. If spinout or drift out is detected, the vehicle control system will selectively apply brakes to the individual wheel ends of the front and rear axles to bring the vehicle back to its intended direction.

ANTI-LOCK BRAKE SYSTEM

The vehicle will be equipped with a Wabco 4S4M, anti-lock braking system. The ABS will provide a four (4) channel anti-lock braking control on both the front and rear wheels. A digitally controlled system that utilizes microprocessor technology will control the anti-lock braking system. Each wheel will be monitored by the system. When any wheel begins to lockup, a signal will be sent to the control unit. This control unit will then reduce the braking of that wheel for a fraction of a second and then reapply the brake. This anti-lock brake system will eliminate the lockup of any wheel thus helping to prevent the apparatus from skidding out of control.

AUTOMATIC TRACTION CONTROL

An anti-slip feature will be included with the ABS. The Automatic Traction Control will be used for traction in poor road and weather conditions. The Automatic Traction Control will act as an electronic differential lock that will not allow a driving wheel to spin, thereby supplying traction at all times. The ABS electronic control unit (ECU) will work with the engine ECU, sharing information concerning wheel slip. Engine ECU will use information to control engine speed, allowing only as much throttle application as required for the available traction, regardless of how much the driver is asking for. An "off road traction" switch will be provided on the instrument panel. Activation of the switch will allow additional tire slip to let the truck climb out and get on top of deep snow or mud.

BRAKES

The service brake system will be full air type by Meritor™.

Front brakes will be Model EX225 Disc Plus, disc type with automatic pad wear adjustment and 17.00" ventilated rotors for improved stopping distance.

The rear brakes will be Meritor™, Disc Plus, Model EX225, disc operated with automatic slack adjusters and a 17.00" ventilated rotor for improved stopping distance.

BRAKE SYSTEM AIR COMPRESSOR

The air compressor will be a Cummins/WABCO with 18.7 cubic feet per minute output.

BRAKE SYSTEM

The brake system will include:

- Brake treadle valve
- Heated automatic moisture ejector on air dryer
- Total air system minimum capacity of 4,272 cubic inches
- Two (2) air pressure gauges with a red warning light and an audible alarm, that activates when air pressure falls below 60 psi
- Spring set parking brake system
- Parking brake operated by a push-pull style control valve
- A parking "brake on" indicator light on instrument panel
- Park brake relay/inversion and anti-compounding valve, in conjunction with a double check valve system, with an automatic spring brake application at 40 psi
- A pressure protection valve to prevent all air operated accessories from drawing air from the air system when the system pressure drops below 80 psi (550 kPa)
- 1/4 turn drain valves on each air tank

The air tank will be primed and painted to meet a minimum 750 hour salt spray test.

The air tanks will be painted selected from another option category for multi colored or sprayed with abrasive resistant material.

To reduce the effects of corrosion, the air tank will be mounted with stainless steel brackets.

BRAKE SYSTEM AIR DRYER

The air dryer will be a Bendix AD-9 air dryer, with spin-on coalescing filter cartridge and 100 watt heater.

BRAKE LINES

Wire braided reinforced rubber brake lines will be provided for the chassis air brake system. This also includes the brake lines between the frame and brake chambers. The brake lines will not be painted.

Coupler fittings for chassis brake lines will be installed forward of the front axle. They will be a separation point for those air lines going to the cab. The air lines going into the cab will be nylon wrapped in loom.

AIR INLET/OUTLET

One (1) air inlet/outlet will be installed with the female coupling located on the passenger side pump panel. This system will tie into the "wet" tank of the brake system and include a check valve in the inlet line and an 85 psi pressure protection valve in the outlet line. The air outlet will be controlled by a needle valve.

A mating male fitting will be provided with the loose equipment.

The air inlet will allow a shoreline air hose to be connected to the vehicle. This will allow station air to be supplied to the brake system of the vehicle to insure constant air pressure.

ALL WHEEL LOCK-UP

An all wheel lock-up system will be installed which will apply air to the front brakes and use the spring brake at the rear.

Front brakes will apply when standard rear parking brake control valve is activated.

COLOR CODE RESERVOIRS

The chassis air reservoirs will be painted for easy identification. Depending on the air tanks installed on the chassis, the following color scheme will be provided (not all tank types may be on a chassis):

Supply tank will be black #101, primary tank will be green #683, secondary tank will be blue #465 and auxiliary tank(s) will be yellow #104.

REMOTE AIR TANK DRAIN

There will be a single remote drain valve provided to drain all air supply reservoirs at the same time. The drain valve will be actuated from the side of the apparatus. The drain valve will be located forward of the driver side rear axle. Automatic valves will be provided to isolate the reservoirs from one another when the drain is closed.

ENGINE

The chassis will be powered by an electronically controlled engine as described below:

Make:	Cummins
Model:	X10
Power:	450 hp at 1800 rpm
Torque:	1650 lb-ft at 1000 rpm
Governed Speed:	1900 rpm
Emissions Level:	EPA 2027
Fuel:	Diesel
Cylinders:	Six (6)
Displacement:	604 cubic inches (9.9L)
Starter:	Delco 39MT™
Fuel Filters:	Spin-on style primary filter with water separator and water-in-fuel sensor. Secondary spin-on style filter.

The engine will include On-board diagnostics (OBD), which provides self diagnostic and reporting. The system will give the owner or repair technician access to state of health information for various vehicle sub systems. The system will monitor vehicle systems, engine and after treatment. The system will illuminate a malfunction indicator light on the dash console if a problem is detected.

The engine will be filled with FA-4 10W30 oil as required by Cummins.

HIGH IDLE

A high idle switch will be provided, inside the cab, on the instrument panel, that will automatically maintain a preset engine rpm. A switch will be installed, at the cab instrument panel, for activation/deactivation.

The high idle will be operational only when the parking brake is on and the truck transmission is in neutral. A green indicator light will be provided, adjacent to the switch. The light will illuminate when the above conditions are met. The light will be labeled "OK to Engage High Idle."

CLUTCH FAN

A fan clutch will be provided. The fan clutch will be automatic when the pump transmission is in "Road" position, and constantly engaged when in "Pump" position.

FLOOR MOUNT, ACCELERATOR PEDAL

There will be a standard automotive style floor mounted accelerator pedal hinged and bolted to the floor of the cab in place of the standard suspended accelerator pedal.

ENGINE AIR INTAKE

The engine air intake will be located above the engine cooling package. It will draw fresh air from the front of the apparatus through the radiator grille.

The ember separator is designed to prevent road dirt and recirculating hot air from entering the engine.

The ember separator will be easily accessible by tilting the cab.

EXHAUST SYSTEM

The exhaust system will be stainless steel from the turbo to the engine's aftertreatment device. The exhaust system will include an aftertreatment device to meet current EPA standards. An insulation wrap will be provided on all exhaust pipe between the turbo and the aftertreatment device to minimize the transfer of heat to the cab.

The exhaust will terminate horizontally ahead of the right side rear wheels and will extend 2.00" past the body rub rail. The exhaust pipes will be aluminized steel.

There will be an aluminized steel exhaust diffuser with a standard straight tip on the end provided to reduce the temperature of the exhaust as it exits. Heat deflector shields will be provided to isolate chassis and body components from the heat of the tailpipe diffuser.

RADIATOR

The radiator and the complete cooling system will meet or exceed the current edition of applicable NFPA and engine manufacturer cooling system standards.

For maximum corrosion resistance and cooling performance, the entire radiator core will be constructed using long life aluminum alloy. The radiator core will consist of aluminum fins, having a serpentine design, brazed to aluminum tubes.

The radiator core will have a minimum front area of 1060 square inches.

Supply tank will be made of heavy duty glass-reinforced nylon and the return tank will be made of aluminum. Both tanks will be crimped onto the core assembly using header tabs and a compression gasket to complete the radiator core assembly. There will be a full steel frame around the inserts to enhance cooling system durability and reliability.

The radiator will be compatible with commercial antifreeze solutions.

The radiator assembly will be isolated from the chassis frame rails with rubber isolators to prevent the development of leaks caused by twisting or straining when the apparatus operates over uneven terrain.

The radiator will include a de-aeration/expansion tank. For visual coolant level inspection, the radiator will have a built-in sight glass. The radiator will be equipped with a 15 psi pressure relief cap.

A drain port will be located at the lowest point of the cooling system and/or the bottom of the radiator to permit complete flushing of the coolant from the system.

Shields or baffles will be provided to prevent recirculation of hot air to the inlet side of the radiator.

COOLANT LINES

Gates® silicone or a combination of silicone and rubber hoses will be used for the radiator and cab heater hoses installed by the chassis manufacturer.

The chassis manufacturer will also use Gates® brand hose on other heater and auxiliary coolant circuits. There will be some areas in which an appropriate Gates product is not available. In those instances a comparable silicone hose from another manufacturer will be used.

Rubber hoses will be used for the overhead defrost/heater system only in the drain tubes of the cab.

Hose clamps will be stainless steel constant torque type to prevent coolant leakage. They will react to temperature changes in the cooling system and expand or contract accordingly while maintaining a constant clamping pressure on the hose.

RADIATOR SKID PLATE

A lower radiator skid plate will be supplied for protection. The skid plate will be constructed of 0.25" steel plate.

FUEL TANK

A 65 gallon fuel tank will be provided and mounted at rear of chassis. The tank will be constructed of 12-gauge, hot rolled steel. It will be equipped with swash partitions and a vent. To eliminate the effects of corrosion, the fuel tank will be mounted with stainless steel straps.

A .75" drain plug will be provided in a low point of the tank for drainage.

A fill inlet will be located on the left hand and right hand sides of the body and be covered with a hinged, spring loaded, stainless steel door that is marked "Ultra Low Sulfur - Diesel Fuel Only."

A .50" diameter vent will be provided running from top of tank to just below fuel fill inlets.

The tank will meet all FHWA 393.67 requirements including a fill capacity of 95 percent of tank volume.

Servicing the fuel tank pick-up tubes and fuel gauge sending unit will be capable of being accomplished by draining fuel and dropping tank.

All fuel lines will be provided as recommended by the engine manufacturer.

DIESEL EXHAUST FLUID TANK

A 4.5 gallon diesel exhaust fluid (DEF) tank will be provided and mounted in the left side body forward of the rear axle.

A 0.50" drain plug will be provided in a low point of the tank for drainage.

A fill inlet will be located on the left side of the body and be covered with a hinged, spring loaded, polished stainless steel door that is marked "Diesel Exhaust Fluid Only".

The tank will meet the engine manufacturers requirement for 10 percent expansion space in the event of tank freezing.

The tank will include an integrated heater unit that utilizes engine coolant to thaw the DEF in the event of freezing.

FUEL PRIMING PUMP

A Cummins automatic electronic fuel priming pump will be integrated as part of the engine.

FUEL SHUTOFF

A shutoff valve will be installed in the fuel line, on both sides of the fuel filter.

FUEL COOLER

An air to fuel cooler will be installed in the engine fuel return line.

FUEL/WATER SEPARATOR

In addition to the standard fuel filters, a Racor 690R1210, 10 micron fuel/water separator with heater will be provided.

TRANSMISSION

An Allison 6th generation, Model EVS 4000PR, electronic, torque converting, automatic transmission with retarder will be provided.

The transmission will be equipped with prognostics to monitor oil life, filter life, and transmission health. A wrench icon on the shift selector's digital display will indicate when service is due.

Two (2) PTO openings will be located on left side and top of converter housing (positions eight (8) o'clock and one (1) o'clock).

A transmission temperature gauge, with amber light and audible alarm, will be installed on the cab instrument panel.

The transmission retarder control will be activated 33 percent by release of the accelerator pedal or 66 percent by slight application of the brake pedal, or 100 percent by heavy application of brake pedal. A second on/off switch is provided to activate and deactivate the auto apply portion.

The transmission will have the 1600 ft. lb. torque (medium) spring setting for retardation force.

The transmission retarder will have a master "on/off" switch on the instrument panel. A red indicator light will be provided to warn that the transmission is being overworked.

The retarder will be wired to the brake lights so they are energized when the retarder is slowing the vehicle down.

The ABS system will automatically disengage the auxiliary braking device when required.

TRANSMISSION SHIFTER

A six (6)-speed push button shift module will be mounted to right of driver on console. Shift position indicator will be indirectly lit for after dark operation.

The transmission ratio will be:

1st	3.51 to 1.00
2nd	1.91 to 1.00
3rd	1.43 to 1.00
4th	1.00 to 1.00
5th	0.75 to 1.00
6th	0.64 to 1.00
R	4.80 to 1.00

TRANSMISSION COOLER

An externally mounted Modine bar plate transmission oil cooler will be provided using engine coolant to control the transmission oil temperature. The internal bar plates will be constructed of stainless steel. The cooler's housing will be constructed of 1020 steel, coated to protect from corrosion. The cooler will be tagged with information including OEM part number, vendor serial number and date / lot code.

An externally mounted Modine bar plate transmission oil cooler will be provided using engine coolant to control the transmission retarder oil temperature. The internal bar plates will be constructed of stainless steel. The cooler's housing will be constructed of 1020 steel, coated to protect from corrosion. The cooler will be tagged with information including OEM part number, vendor serial number and date / lot code.

DOWNSHIFT MODE (W/ENGINE BRAKE)

The transmission will be provided with an aggressive downshift mode.

This will provide earlier transmission downshifts to 2nd gear from 6th gear, resulting in improved engine braking performance.

TRANSMISSION FLUID

The transmission will be provided with TranSynd, or other Allison approved TES-668 heavy duty synthetic transmission fluid.

DRIVELINE

Drivelines will be a heavy-duty metal tube and be equipped with Spicer® 1810 universal joints.

The shafts will be dynamically balanced before installation.

A splined slip joint will be provided in each driveshaft where the driveline design requires it. The slip joint will be coated with Glidecoat® or equivalent.

STEERING

Dual steering gear, with integral heavy-duty power steering, will be provided. For reduced system temperatures, the power steering will incorporate an air to oil cooler and Vickers® V20NF hydraulic pump with integral pressure and flow control. All power steering lines will have wire braded lines with crimped fittings.

A tilt and telescopic steering column will be provided to improve fit for a broader range of driver configurations.

STEERING WHEEL

The steering wheel will be 18.00" in diameter, have tilting and telescoping capabilities, and a 4-spoke design.

LOGO AND CUSTOMER DESIGNATION ON DASH

The dash panel will have an emblem containing the Pierce logo and customer name. The emblem will have three (3) rows of text for the customer's department name. There will be a maximum of eight (8) characters in the first row, 11 characters in the second row and 11 characters in the third row.

The first row of text will be: Corona

The second row of text will be: Fire

The third row of text will be: Department

BUMPER

A one (1) piece, ten (10) gauge, 304-2B type polished stainless steel bumper, minimum of 10.00" high, will be attached to a bolted modular extension frame constructed of 50,000 psi tensile steel "C" channel mounted directly behind it to provide adequate support strength.

The bumper will be extended 16.00" from front face of cab.

Gravel Pan

A gravel pan, constructed of bright aluminum treadplate, will be furnished between the bumper and cab face. The gravel pan will be properly supported from the underside to prevent flexing and vibration of the aluminum treadplate.

CENTER HOSE TRAY

A hose tray, constructed of aluminum, will be placed in the center of the bumper extension.

The tray will have a capacity of 100' of 1.75" double jacket cotton-polyester hose.

Black rubber grating will be provided at the bottom of the tray. Drain holes are also provided.

Center Hose Tray Cover

A bright aluminum treadplate cover will be provided over the center hose tray.

The cover will be "notched" allowing the hose to be pre connected to hose connection.

The cover will be attached with a stainless steel hinge.

A D-ring latch will secure the cover in the closed position and a pneumatic stay arm will hold the cover in the open position. The arm will be located over the center tray.

TOW EYES

Two (2) Chicago style tow eyes will be mounted through the top of the bumper extension. The tow eyes will be designed and positioned to allow up to a 6,000 lb straight horizontal pull in line with the centerline of the vehicle. The tow eyes will not be used for lifting of the apparatus.

The inner and outer edges of the tow eyes will have a .25" radius.

The tow eyes will be chrome plated.

FRONT BUMPER NOTCH

The front bumper will be notched for recessing of the Q2B siren. The notch will be designed so that the bumper is one (1) continuous piece. The notch will be welded in place for strength with a continuous top and bottom flange. All areas will be polished for appearance. The siren will be located on the driver side of the bumper.

CAB

The Enforcer cab will be designed specifically for the fire service and manufactured by the chassis builder.

The cab will be built by the apparatus manufacturer in a facility located on the manufacturer's premises.

For reasons of structural integrity and enhanced occupant protection, the cab will be a heavy duty design, constructed to the following minimal standards.

The cab will have 12 main vertical structural members located in the A-pillar (front cab corner posts), B-pillar (side center posts), C-pillar (rear corner posts), and rear wall areas. The A-pillar will be constructed of solid A356-T5 aluminum castings. The B-pillar and C-pillar will be constructed from

0.13" wall extrusions. The rear wall will be constructed of two (2) 2.00" x 2.00" outer aluminum extrusions and two (2) 2.00" x 1.00" inner aluminum extrusions. All main vertical structural members will run from the floor to 4.625" x 3.864" x 0.090" thick roof extrusions to provide a cage-like structure with the A-pillar and roof extrusions being welded into a 0.25" thick corner casting at each of the front corners of the roof assembly.

The front of the cab will be constructed of a 0.13" firewall plate, covered with a minimum 0.090" front skin thickness, and reinforced with a full width x 0.50" thick cross-cab support located just below the windshield and fully welded to the engine tunnel. The cross-cab support will run the full width of the cab and weld to each A-pillar, the 0.13" firewall plate, and the front skin.

The cab floors will be constructed of 0.125" thick aluminum plate and reinforced at the firewall with an additional 0.375" thick cross-floor support providing a total thickness of 0.50" of structural material at the front floor area. The front floor area will also be supported with two (2) triangular 0.30" wall extrusions that also provides the mounting point for the cab lift. This tubing will run from the floor wireway of the cab to the engine tunnel side plates, creating the structure to support the forces created when lifting the cab.

The cab will be 96.00" wide (outside door skin to outside door skin) to maintain maximum maneuverability.

The centerline of front axle to the rear of the cab will be 70.00" long.

The overall height (from the cab roof to the ground) of approximately 99.00". The overall height listed will be calculated based on a truck configuration with the lowest suspension weight rating, the smallest diameter tires for the suspension, no water weight, no loose equipment weight, and no personnel weight. Larger tires, wheels, and suspension will increase the overall height listed.

The floor to ceiling height inside the crew cab will be 54.50" in the center and outboard positions.

The crew cab floor will measure 46.00" from the rear wall to the back side of the rear facing seat risers.

The medium block engine tunnel, at the rearward highest point (knee level), will measure 61.50" to the rear wall. The big block engine tunnel will measure between 45.00" and 51.50" to the rear wall, depending on the engine.

The crew cab will be a totally enclosed design with the interior area completely open to improve visibility and verbal communication between the occupants.

The cab will be a full tilt cab style.

A 3-point cab mount system with rubber isolators will improve ride quality by isolating chassis vibrations from the cab.

CAB ROOF DRIP RAIL

For enhanced protection from inclement weather, a drip rail will be furnished on the sides of the cab. The drip rail will be painted to match the cab roof, and bonded to the sides of the cab. The drip rail will extend the full length of the cab roof.

FENDER LINERS

Full circular inner fender liners in the wheel wells will be provided.

PANORAMIC WINDSHIELD

A one (1)-piece safety glass windshield will be provided with over 2,775 square inches of clear viewing area. The windshield will be full width and will provide the occupants with a panoramic view. The windshield will consist of three (3) layers: outer light, middle safety laminate, and inner light. The outer light layer will provide superior chip resistance. The middle safety laminate layer will prevent the windshield glass pieces from detaching in the event of breakage. The inner light will provide yet another chip resistant layer. The cab windshield will be bonded to the aluminum windshield frame using a urethane adhesive. A custom frit pattern will be applied on the outside perimeter of the windshield for a finished automotive appearance.

WINDSHIELD WIPERS

Three (3) electric windshield wipers with washer will be provided that meet FMVSS and SAE requirements.

The washer reservoir will be able to be filled without raising the cab.

ENGINE TUNNEL

Engine hood side walls will be constructed of 0.375" aluminum. The top will be constructed of 0.125" aluminum and will be tapered at the top to allow for more driver and passenger elbow room.

The engine hood will be insulated for protection from heat and sound. Perforated foil faced insulation will be over a closed cell foam affixed with pressure sensitive adhesive and further secured with mechanical fasteners. The noise insulation keeps the dBA level within the limits stated in the current edition of applicable NFPA standards.

The engine tunnel will be no higher than 17.00" off the crew cab floor.

INSULATION PACKAGE

All insulation utilized in the cab construction will be provided for extreme climate temperatures. The insulation will be provided in the following areas:

- Engine tunnel
- Cab and crew cab floors
- Cab and crew cab doors
- Cab roof
- Cab and crew cab walls

INTERIOR CREW CAB REAR WALL ADJUSTABLE SEATING (PATENT PENDING)

The interior rear wall of the crew cab will have mounting holes every 2.75" to allow for adjustability of the forward facing crew cab seating along the rear wall. Seats will be adjustable with use of simple hand tools allowing departments flexibility of their seating arrangement should their department needs change.

CAB REAR WALL EXTERIOR COVERING

The exterior surface of the rear wall of the cab will be overlaid with bright aluminum treadplate except for areas that are not typically visible when the cab is lowered.

CAB LIFT

A hydraulic cab lift system will be provided consisting of an electric powered hydraulic pump, dual lift cylinders, and necessary hoses and valves.

Hydraulic pump will have a manual override for backup in the event of electrical failure.

Lift controls will be located in the driver side stepwell. A "cab unlocked" indicator light will be located at the controls that will indicate when the cab is not in the locked position for safe road travel.

The cab will be capable of tilting 43 degrees to accommodate engine maintenance and removal.

The cab will be locked down by a 2-point normally closed spring loaded hook type latch that fully engages after the cab has been lowered. The system will be hydraulically actuated to release the normally closed locks when the cab lift control is in the raised position and cab lift system is under pressure. When the cab is completely lowered and system pressure has been relieved, the spring loaded latch mechanisms will return to the normally closed and locked position.

The hydraulic cylinders will be equipped with a velocity fuse that protects the cab from accidentally descending when the control is located in the tilt position.

For increased safety, a redundant mechanical stay arm will be provided that must be manually put in place on the left side between the chassis and cab frame when the cab is in the raised position. This device will be manually stowed to its original position before the cab can be lowered.

Cab Lift Interlock

The cab lift system will be interlocked to the parking brake. The cab tilt mechanism will be active only when the parking brake is set and the ignition switch is in the on position. If the parking brake is released, the cab tilt mechanism will be disabled.

GRILLE

A bright finished aluminum mesh grille screen, inserted behind a bright finished grille surround, will be provided on the front center of the cab.

SCUFFPLATE

A bright aluminum treadplate scuffplate will be provided on the entire rear vertical surface of the engine tunnel.

SIDE OF CAB MOLDING

Chrome molding will be provided on both sides of cab.

MIRRORS

A Retraco, Model 613423, dual vision, motorized, west coast style mirror, with chrome finish, will be mounted on each side of the front cab door with spring loaded retractable arms. The flat glass and convex glass will be heated and adjustable with remote control within reach of the driver.

DOORS

To enhance entry and egress to the cab, the forward cab door openings will be a minimum of 37.50" wide x 63.37" high. The crew cab doors will be located on the sides of the cab and will be constructed in the same manner as the forward cab doors. The crew cab door openings will be a minimum of 34.30" wide x 63.37" high.

The forward cab and crew cab doors will be constructed of extruded aluminum with a nominal material thickness of 0.093". The exterior door skins will be constructed from 0.090" aluminum.

A customized, vertical, pull-down type door handle will be provided on the exterior of each cab door. The finish of the door handle will be chrome/black. The exterior handle will be designed specifically for the fire service to prevent accidental activation, and will provide 4.00" wide x 2.00" deep hand clearance for ease of use with heavy gloved hands.

Each door will also be provided with an interior flush, open style paddle handle that will be readily operable from fore and aft positions, and be designed to prevent accidental activation. The interior handles will provide 4.00" wide x 1.25" deep hand clearance for ease of use with heavy gloved hands.

The cab doors will be provided with both interior (rotary knob) and exterior (keyed) locks exceeding FMVSS standards. The keys will be Model 751. The locks will be capable of activating when the doors are open or closed. The doors will remain locked if locks are activated when the doors are opened, then closed.

A full length, heavy duty, stainless steel, piano-type hinge with a 0.38" pin and 11 gauge leaf will be provided on all cab doors. There will be double automotive-type rubber seals around the perimeter of the door framing and door edges to ensure a weather-tight fit.

A chrome handle will be provided on the inside of each cab door for ease of entry.

A red webbed grab handle will be installed on the crew cab door stop strap. The grab handles will be securely mounted.

The bottom cab step at each cab door location will be located below the cab doors and will be exposed to the exterior of the cab.

Door Panels

The inner cab door panels will be constructed out of brushed stainless steel.

ELECTRIC OPERATED CAB DOOR WINDOWS

All four (4) cab doors will be equipped with electric operated windows with one (1) flush mounted automotive style switch on each door. The driver's door will have four (4) switches, one (1) to control each door window.

Each switch will allow intermittent or auto down operation for ease of use. Auto down operation will be actuated by holding the window down switch for approximately 1 second.

ELECTRIC CAB DOOR LOCKS

The front driver and officer doors will have a door lock master switch that will control all front and rear crew cab door locks. Each rear crew cab door will have its own lock control.

There will be one (1) concealed switch located in an easily accessible chassis specific location that will unlock all the doors.

KEY PAD FOR ELECTRIC DOOR LOCKS

For improved convenience, the cab door locks will include a Trimark keypad entry system to provide complete keyless entry to the cab. There will be two (2) keypads provided, located one (1) each side of the cab behind the front cab doors. The keypads will include visual and audio feedback to confirm activation and acknowledge correct entry code. For enhanced night time use, the keypads will be lighted. For increased security, the system will allow over 3,000 possible code combinations.

CAB STEPS

The forward cab and crew cab access steps will be a full size two (2) step design to provide largest possible stepping surfaces for safe ingress and egress. The bottom steps will be designed with a grip pattern punched into bright aluminum treadplate material to provide support, slip resistance, and drainage. The bottom steps will be a bolt-in design to minimize repair costs should they need to be replaced. The forward cab steps will be a minimum 25.00" wide, and the crew cab steps will be 21.65" wide with a 10.00" minimum depth. The inside cab steps will not exceed 16.50" in height.

The vertical surfaces of the step well will be aluminum treadplate.

CAB EXTERIOR HANDRAILS

A 1.25" diameter slip-resistant, knurled aluminum handrail will be provided adjacent to each cab and crew cab door opening to assist during cab ingress and egress.

STEP LIGHTS

There will be eight (8) TecNiq Model E03W000-1, 2.90" wide x .90" high x .70" deep LED step lights with stainless steel horizontal mounts provided for the cab access steps.

- Two (2) for each driver's side cab access step.
- Two (2) for each driver's side crew cab access step.
- Two (2) for each passenger's side crew cab access step.
- Two (2) for each passenger's side cab access step.

The lights will be activated when the battery switch is on and the adjacent door is open.

FENDER CROWNS

Stainless steel fender crowns will be installed at the cab wheel openings.

ADDITIONAL HANDRAIL

There will be two (2) handrail(s) provided one each side of the back of the cab, 14" long. The handrail will be an anodized aluminum extrusion with a ribbed design to provide a positive gripping surface.

CREW CAB WINDOWS

One (1) fixed window with tinted glass will be provided on each side of the cab, to the rear of the front cab door. The windows will be sized to enhance light penetration into the cab interior. The windows will measure 18.70" wide x 23.75" high.

CAB ROOF COVERING

Horizontal cab roof surfaces will be covered with bright aluminum treadplate. The fastening screws and the perimeter between the roof and the bottom of the aluminum treadplate, no more than 1.00" in from the edge of the aluminum treadplate, will be properly caulked to prevent water from leaking under aluminum. Front and side warning lights will not be mounted on top of treadplate. The treadplate will extend and terminate next to the warning lights.

GLOVE BOX

A glove box with a drop-down door will be installed above the recessed area of the dash panel in front of the officer's position. The glove box will be 31.00" wide at the top and 24.75" at the bottom x 5.50" high x 6.25" deep. The clear door opening will be 14.25" wide x 3.95" high.

CAB DASH

The driver side dash, switch panel located to the right of the driver, and center console will be constructed of metal and painted to match the cab interior.

The officer side dash will be a flat top design with an upper beveled edge to provide easy maintenance and will be constructed out of aluminum and painted to match the cab interior.

The instrument gauge cluster will be surrounded with a high impact ABS plastic contoured to the same shape of the instrument gauge cluster.

MOUNTING PLATE ON ENGINE TUNNEL

Equipment installation provisions will be installed on the engine tunnel.

A 0.188" smooth aluminum plate will be bolted to the top surface of the engine tunnel. The plate will follow the contour of the engine tunnel and will run the entire length of the engine tunnel. The plate will be spaced off the engine tunnel .25" to allow for wire routing below the plate.

The mounting surface will be painted to match the cab interior.

CAB INTERIOR

The cab interior will be constructed of primarily metal (painted aluminum) to withstand the severe duty cycles of the fire service.

The engine tunnel will be padded and covered, on the top and sides, with black 36 ounce leather grain vinyl resistant to oil, grease, and mildew.

To provide a deluxe automotive interior the side walls and rear wall will be covered by a leather grain vinyl that is resistant to oil, grease, and mildew.

The headliner will be installed in both forward and rear cab sections. Headliner material will be vinyl. A sound barrier will be part of its composition. Material will be installed on aluminum sheet and securely fastened to interior cab ceiling.

Forward portion of cab headliner will permit easy access for service of electrical wiring or other maintenance needs.

All wiring will be placed in metal raceways.

CAB INTERIOR UPHOLSTERY

The cab interior upholstery will be 36 oz black vinyl.

CAB INTERIOR PAINT

The cab interior metal surfaces, excluding the rear heater panels, will be painted fire smoke gray, vinyl texture paint.

The rear heater panels will be painted black, vinyl textured paint.

CAB FLOOR

The cab and crew cab floor areas will be covered with Polydamp™ acoustical floor mat consisting of a black pyramid rubber facing and closed cell foam decoupler.

The top surface of the material has a series of raised pyramid shapes evenly spaced, which offer a superior grip surface. Additionally, the material has a 0.25" thick closed cell foam (no water absorption) which offers a sound dampening material for reducing sound levels.

The rubber floor material will have aluminum treadplate overlay. The aluminum treadplate floor will entirely cover the rubber floor material.

The vertical surface of the upper step wells in the crew cab will also be covered with floor mat overlaid with aluminum treadplate.

DEFROST/AIR CONDITIONING SYSTEM

A ceiling mounted combination heater, defroster and air conditioning system will be installed in the cab above the engine tunnel area.

Cab Defroster

A 54,000 BTU heater-defroster unit with 690 SCFM of air flow will be provided inside the cab. The heater-defrost will be installed in the forward portion of the cab ceiling. Air outlets will be strategically located in the cab header extrusion per the following:

- One (1) adjustable will be directed towards the left side cab window
- One (1) adjustable will be directed towards the right side cab window
- Six (6) fixed outlets will be directed at the windshield

The defroster will be capable of clearing 98 percent of the windshield and side glass when tested under conditions where the cab has been cold soaked at 0 degrees Fahrenheit for 10 hours, and a 2 ounce

per square inch layer of frost/ice has been able to build up on the exterior windshield. The defroster system will meet or exceed SAE J382 requirements.

Cab/Crew Auxiliary Heater

There will be one (1) 31,000 BTU auxiliary heater with 560 SCFM of air flow provided in each outboard rear facing seat riser with a dual scroll blower. An aluminum plenum incorporated into the cab structure to be used to transfer heat to the forward positions.

Air Conditioning

A 19.10 cubic inch compressor will be installed on the engine.

A roof-mounted condenser with a 78,000 BTU output at 2,400 SCFM that meets and exceeds the performance specification will be installed on the cab roof. Mounting the condenser below the cab or body would reduce the performance of the system and will not be acceptable. The condenser cover to be painted to match the cab roof.

The evaporator unit will be installed in the rear portion of the cab ceiling over the engine tunnel. The evaporator will include one (1) high performance heating core, one (1) high performance cooling core with (1) plenum directed to the front and one (1) plenum directed to the rear of the cab.

The evaporator unit will have a 80,000 BTU at 1,200 SCFM rating that meets and exceeds the performance specifications.

Adjustable air outlets will be strategically located on the forward plenum cover per the following:

- Four (4) will be directed towards the seating position on the left side of the cab
- Four (4) will be directed towards the seating position on the right side of the cab

Adjustable air outlets will be strategically located on the rear plenum cover per the following:

- 14 will be directed towards crew cab area

A high efficiency particulate air (HEPA) filter will be included for the system. Access to the filter cover will be hinged with two (2) thumb latches.

The air conditioner refrigerant will be R-134A and will be installed by a certified technician.

Climate Control

An automotive style controller will be provided to control the heat and air conditioning system within the cab. The controller will have three (3) functional knobs for fan speed, temperature, and air flow distribution (front to rear) control.

The system will control the temperature of the cab and crew cab automatically by pushing the center of the fan speed control knob. Rotate the center temperature control knob to set the cab and crew cab temperature.

The AC system will be manually activated by pushing the center of the temperature control knob. Pushing the center of the air flow distribution knob will engage the AC for max defrost, setting the fan speeds to 100 percent and directing all air flow to the overhead forward position.

The system controller will be located within panel position #12.

Gravity Drain Tubes

Two (2) condensate drain tubes will be provided for the air conditioning evaporator. The drip pan will have two (2) drain tubes plumbed separately to allow for the condensate to exit the drip pan. No pumps will be provided.

BRUSH GUARD

A protective enclosure will be provided around the roof mounted air conditioning unit. The enclosure will provide protection from tree limbs and debris.

The enclosure will be made of aluminum and painted to match the cab exterior.

120 VOLT AIR CONDITIONING

There will be one (1) black, Coleman®-Mach® 8, Roughneck™, 120 volt, low profile air conditioning unit installed on the crew cab roof. The air conditioner will have cooling capacity of 15,000 BTU and include a condensate pump and hose to prevent accumulation of condensate on the roof.

Ceiling unit controls will control the air conditioning unit.

The thermostat will be wired battery direct to operate when the battery switch is off.

This unit will be powered from the shoreline inlet.

INTERIOR CAB INSULATION

The walls and roof will be insulated to aid in cooling.

SUN VISORS

There will be two (2) vinyl covered sun visors provided. The sun visors will be located above the windshield with one (1) mounted on each side of the cab.

There will be a black plastic thumb latch provided to help secure each sun visor in the stowed position.

GRAB HANDLES

A black rubber covered grab handle will be mounted on the door post of the driver and officer's side cab door to assist in entering the cab. The grab handles will be securely mounted to the post area between the door and windshield.

ENGINE COMPARTMENT LIGHTS

There will be two (2) Whelen®, Model 3SC0CDCR, 12 volt DC, 3.00" white LED light(s) with Model 3FLANGEC, chrome flange kit(s) installed under the cab to be used as engine compartment illumination.

These light(s) will be activated automatically when the cab is raised or when the dip stick door is opened.

ACCESS TO ENGINE DIPSTICKS

For access to the engine oil and transmission fluid dipsticks, there will be a door on the engine tunnel, inside the crew cab. The door will be on the rear wall of the engine tunnel, on the vertical surface.

The engine oil dipstick will allow for checking only. The transmission dipstick will allow for both checking and filling.

The door will have a rubber seal for thermal and acoustic insulation. One (1) Southco C2 black powder coated flush latch will be provided on the access door.

MAP BOX WITH CUP HOLDERS

There will be a map box, open from top, provided. The map box will be installed on engine tunnel mounting plate 12" from the front of the plate. The rear of the map box will be supported on the slanted portion of the engine tunnel and the sides under the map box will be enclosed so nothing can slide underneath.

The map box will be divided into six (6) bins. Each bin will be 4.00" wide x 8.00" high x 12.00" long.

There will be two (2) cup holders slotted for handles, located at the front of the map box, one (1) on each side. Between the cup holders will be a 16.00" wide x 4.00" high x 9.00" long tray.

The map box will be constructed of 0.125" aluminum and painted to match the cab interior.

SEATING CAPACITY

The seating capacity of the vehicle (including tiller cab and belted seat positions in the rescue body) will be five (5).

DRIVER SEAT

A USSC Valor air suspension R-back seat will be provided in the cab for the driver. For increased convenience, the seat will include a manual control to adjust the horizontal position. To provide flexibility for multiple driver configurations, the seat will have a reclining back, adjustable from 15 degrees back to 45 degrees forward.

The seat will be furnished with a 3-point, shoulder type seat belt.

There will be no additional contaminant mitigation vinyl covers shipped loose with the seat.

OFFICER SEAT

A USSC, P1A, air suspension seat will be provided in the cab for the officer. For optimal comfort, the seat will be provided with a 20.00" wide x 18.00" deep cushion. For increased convenience, the seat will include a manual control to adjust the height (3.00" travel) and horizontal position (2.50" travel). The seat will have a reclining, R-back style seat back.

The seat will be furnished with a 3-point, shoulder type seat belt.

There will be no additional contaminant mitigation vinyl covers shipped loose with the seat.

FORWARD FACING DRIVER SIDE OUTBOARD SEAT

There will be one (1) forward facing, USSC Valor foldup high back seat provided at the driver side outboard position in the crew cab. For optimal comfort, the seat will be provided with 17.00" deep cushion and an adjustable recline back. To ensure safe operation, the seat will be equipped with a sensor in the seat cushion and belt receptacle that will activate an alarm indicating the seat is occupied but not buckled.

The seat will be furnished with a 3-point, shoulder type seat belt.

There will be no additional contaminant mitigation vinyl covers shipped loose with the seat.

FORWARD FACING CENTER SEAT

There will be one (1) forward facing, USSC Valor foldup seat provided at the center position in the crew cab. For optimal comfort, the seat will be provided with a 15.00" deep foam cushion.

The seat back will be an SCBA style with 90 degree back. The SCBA cavity will be adjustable from front to rear in 0.75" increments, to accommodate different sized SCBA cylinders. Moving the SCBA cavity will be accomplished by unbolting, relocating, and re-bolting it in the desired location.

The seat will be furnished with a 3-point, shoulder type seat belt.

FORWARD FACING PASSENGER SIDE OUTBOARD SEAT

There will be one (1) forward facing, USSC high back seat provided in the passenger side outboard position in the crew cab. The seat back will be a R-back style with an adjustable recline angle. For optimal comfort, the seat will be provided with 17.00" deep cushion. To ensure safe operation, the seat will be equipped with a sensor in the seat cushion and belt receptacle that will activate an alarm indicating the seat is occupied but not buckled.

Shipped loose with the seat will be no additional contaminant mitigation vinyl covers.

The seat will be furnished with a 3-point, shoulder type seat belt.

STORAGE CABINET

There will be two (2) storage cabinet(s) provided in the cab. The cabinet(s) will be located on either side of the forward facing center seat.

The cabinet will be 10.00" wide x 25.75" high x 20.00" deep with web netting. The netting will be made with 1.00" wide nylon material with 2.00" openings permanently fastened on the top with 1.00" cam buckle fasteners on the bottom to secure it. The clear door opening of the cabinet will be 7.50" wide x 22.75" high.

The cabinet will include one (1) permanent shelf located 16.00" above the floor with a 1.00" up-turned lip.

Each cabinet will be constructed of smooth aluminum and painted to match the cab interior.

SEAT UPHOLSTERY

All seat upholstery will be black, sewn with red stitching, ValorTechXD anti-microbial material.

AIR BOTTLE HOLDERS

All SCBA type seats in the cab will have a "Hands-Free" auto clamp style bracket in its backrest. For efficiency and convenience, the bracket will include an automatic spring clamp that allows the occupant to store the SCBA bottle by simply pushing it into the seat back. For protection of all occupants in the cab, in the event of an accident, the inertial components within the clamp will constrain the SCBA bottle in the seat and will exceed the NFPA standard of 9G.

There will be a quantity of one (1) SCBA brackets.

SEAT EMBROIDERY

The seats in the cab and crew cab, including flip up seat backs, will be provided with custom embroidery. The Fire Department will determine what the embroidery will be by providing pictures at the time of order.

The custom logo will be provided in place of the standard OEM logo. Flip up seat backs the logo will be provided on the center of the seat back.

The embroidery will be provided on five (5) seats.

FOOT REST ANGLE

A knurled handrail type will be provided for the officers position. The handrail will be mounted to the engine housing with a flat stanchion and a U shaped bracket. The handrail will extend the width of the officers seat area. The foot rest will be positioned approximately 3.50" from the forward wall.

SEAT BELTS

All cab and tiller cab (if applicable) seating positions will have red seat belts. To provide quick, easy use for occupants wearing bunker gear, the female buckle and seat belt webbing length will meet or exceed the current edition of applicable NFPA and CAN/ULC - S515 standards.

The 3-point shoulder type seat belts will include height adjustment. This adjustment will optimize the belts effectiveness and comfort for the seated firefighter. The 3-point shoulder type seat belts will be furnished with dual automatic retractors that will provide ease of operation in the normal seating position.

The 3-point shoulder type belts will also include the ReadyReach® D-loop assembly to the shoulder belt system. The ReadyReach feature adds an extender arm to the D-loop location placing the D-loop in a closer, easier to reach location.

Any flip up seats will include a 3-point shoulder type belts only.

To ensure safe operation, the seats will be equipped with seat belt sensors in the seat cushion and belt receptacle that will activate an alarm indicating a seat is occupied but not buckled.

HELMET STORAGE PROVIDED BY FIRE DEPARTMENT

NFPA 1900, 2024 edition, section 11.1.8.4.1 and CAN/ULC 515:2024 edition, section 5.2, requires a location for helmet storage be provided.

There is no helmet storage on the apparatus as manufactured. The fire department will provide a location for storage of helmets.

CAB DOME LIGHTS

There will be four (4) Whelen, Model 60C*EGCS, 6.00" round dual LED dome lights provided. Two (2) lights will be mounted above the inside shoulder of the driver and officer and two (2) lights will be installed and located, one (1) on each side of the crew cab.

The color of the LED's will be red and white.

The white LED's will be controlled by the lens switch.

The color LED's will be controlled by the door switches and the lens switch.

CAB SPOTLIGHT

There will be two (2) Golight® Stryker ST™, Model 30**4ST, black LED spotlights located on the cab roof, outside the front lightbar. The spotlights will be mounted to the surface of the cab roof.

These lights may be load managed when the parking brake is applied.

Spotlight Controller

There will be one (1) wired dash mounted remote provided for each spotlight.

Spotlight Controller Locations

The remotes to control the spotlights will be located one (1) within reach of the driver and one (1) within reach of the officer.

PORTABLE HAND LIGHTS PROVIDED BY DEALER

The hand lights are not on the apparatus as manufactured. The dealer will provide and mount these hand lights.

CAB INSTRUMENTATION

The cab instrument panel include gauges, an LCD display, telltale indicator lamps, control switches, alarms, and a diagnostic panel. The function of the instrument panel controls and switches will be identified by a label adjacent to each item. Actuation of the headlight switch will illuminate the labels in low light conditions. Telltale indicator lamps will not be illuminated unless necessary. The cab instruments and controls will be conveniently located within the forward cab section, forward of the driver. The gauge assembly and switch panels are designed to be removable for ease of service and low cost of ownership.

Gauges

The gauge panel will include the following ten (10) black faced gauges with black bezels to monitor vehicle performance:

- Voltmeter gauge (volts):

- Low volts (11.8 VDC)
 - Amber caution indicator on the information center with intermittent alarm
 - Amber caution light on gauge assembly
- High volts (15.5 VDC)
 - Amber caution indicator on the information center with intermittent alarm
 - Amber caution light on gauge assembly
- Very low volts (11.3 VDC)
 - Red warning indicator on the information center with a steady alarm
 - Amber caution light on gauge assembly
- Very high volts (16.0 VDC)
 - Red warning indicator on the information center with a steady alarm
 - Amber caution light on gauge assembly
- Engine Tachometer (RPM)
- Speedometer MPH (Major Scale), KM/H (Minor Scale)
- Fuel level gauge (Empty - Full in fractions):
 - Low fuel (1/8 full)
 - Amber caution indicator on the information center with intermittent alarm
 - Amber caution light on gauge assembly
 - Very low fuel (1/32 full)
 - Red caution indicator on the information center with steady alarm
 - Amber caution light on gauge assembly
- Engine Oil pressure Gauge (PSI):
 - Low oil pressure to activate engine warning lights and alarms
 - Red caution indicator on the information center with steady alarm
 - Amber caution light on gauge assembly
- Front Air Pressure Gauges (PSI):
 - Low air pressure to activate warning lights and alarm
 - Red warning indicator on the information center with a steady alarm
 - Amber caution light on gauge assembly
- Rear Air Pressure Gauges (PSI):
 - Low air pressure to activate warning lights and alarm
 - Red warning indicator on the information center with a steady alarm
 - Amber caution light on gauge assembly
- Transmission Oil Temperature Gauge (Fahrenheit):
 - High transmission oil temperature activates warning lights and alarm
 - Amber caution indicator on the information center with intermittent alarm
 - Amber caution light on gauge assembly
- Engine Coolant Temperature Gauge (Fahrenheit):
 - High engine temperature activates an engine warning light and alarms
 - Amber caution indicator on the information center with intermittent alarm
 - Amber caution light on gauge assembly
- Diesel Exhaust Fluid Level Gauge (Empty - Full in fractions):
 - Low fluid (1/8 full)
 - Amber indicator light in gauge dial

All gauges will perform prove out at initial power-up to ensure proper performance.

Indicator Lamps

To promote safety, the following telltale indicator lamps will be located on the instrument panel in clear view of the driver. The indicator lamps will be "dead-front" design that is only visible when active. The colored indicator lights will have descriptive text or symbols.

The following amber telltale lamps will be present:

- Low coolant
- Trac cntl (traction control) (where applicable)
- Check engine
- Check trans (check transmission)
- Aux brake overheat (Auxiliary brake overheat)
- Air rest (air restriction)
- Caution (triangle symbol)
- Water in fuel
- DPF (engine diesel particulate filter regeneration)
- Trailer ABS (where applicable)
- Wait to start (where applicable)
- HET (engine high exhaust temperature) (where applicable)
- ABS (antilock brake system)
- MIL (engine emissions system malfunction indicator lamp) (where applicable)
- Side roll fault (where applicable)
- Front air bag fault (where applicable)

The following red telltale lamps will be present:

- Warning (stop sign symbol)
- Seat belt
- Parking brake
- Stop engine
- Rack down

The following green telltale lamps will be provided:

- Left turn
- Right turn
- Battery on

The following blue telltale lamp will be provided:

- High beam

Alarms

Audible steady tone warning alarm: A steady audible tone alarm will be provided whenever a warning message is present.

Audible pulsing tone caution alarm: A pulsing audible tone alarm (chime/chirp) will be provided whenever a caution message is present without a warning message being present.

Alarm silence: Any active audible alarm will be able to be silenced by holding the ignition switch at the top position for three (3) to five (5) seconds. For improved safety, silenced audible alarms will intermittently chirp every 30 seconds until the alarm condition no longer exists. The intermittent chirp will act as a reminder to the operator that a caution or warning condition still exists. Any new warning or caution condition will enable the steady or pulsing tones respectively.

Indicator Lamp and Alarm Prove-Out

A system will be provided which automatically tests telltale indicator lights and alarms located on the cab instrument panel. Telltale indicators and alarms will perform prove-out at initial power-up to ensure proper performance.

Control Switches

For ease of use, the following controls will be provided immediately adjacent to the cab instrument panel within easy reach of the driver. All switches will have backlit labels for low light applications.

Headlight/Parking light switch: A three (3)-position maintained rocker switch will be provided. The first switch position will deactivate all parking and headlights. The second switch position will activate the parking lights. The third switch will activate the headlights.

Panel back lighting intensity control switch: A three (3)-position momentary rocker switch will be provided. Pressing the top half of the switch, "Panel Up" increases the panel back lighting intensity and pressing the bottom half of the switch, "Panel Down" decreases the panel back lighting intensity. Pressing the half or bottom half of the switch several times will allow back lighting intensity to be gradually varied from minimum to maximum intensity level for ease of use.

Ignition switch: A three (3)-position maintained/momentary rocker switch will be provided. The first switch position will turn off and deactivate vehicle ignition. The second switch position will activate vehicle ignition and will perform prove-out on the telltale indicators and alarms for 3 to 5 seconds after the switch is turned on. A green indicator lamp is activated with vehicle ignition. The third momentary position will temporarily silence all active cab alarms. An alarm "chirp" may continue as long as alarm condition exists. Switching ignition to off position will terminate the alarm silence feature and reset function of cab alarm system.

Engine start switch: A two (2)-position momentary rocker switch will be provided. The first switch position is the default switch position. The second switch position will activate the vehicle's engine. The switch actuator is designed to prevent accidental activation.

Hazard switch will be provided on the instrument panel or on the steering column.

Heater, defroster, and air conditioning control panel.

Turn signal arm: A self-canceling turn signal with high beam headlight controls will be provided.

Windshield wiper control will have high, low and intermittent modes.

Parking brake control: An air actuated push/pull park brake control valve will be provided.

Chassis horn control: Activation of the chassis horn control will be provided through the center of the steering wheel.

High idle engagement switch: A momentary rocker switch with integral indicator lamp will be provided. The switch will activate and deactivate the high idle function. The "OK To Engage High Idle" indicator lamp must be active for the high idle function to engage. A green indicator lamp integral to the high idle engagement switch will indicate when the high idle function is engaged.

"OK To Engage High Idle" indicator lamp: A green indicator light will be provided next to the high idle activation switch to indicate that the interlocks have been met to allow high idle engagement.

Emergency switching will be controlled by multiple individual warning light switches for various groups or areas of emergency warning lights. An Emergency Master switch provided on the instrument panel that enables or disables all individual warning light switches is included.

An additional "Emergency Master" button will be provided on the lower left hand corner of the gauge panel to allow convenient control of the "Emergency Master" system from inside the driver's door when standing on the ground.

Custom Switch Panels

The design of cab instrumentation will allow for emergency lighting and other switches to be placed within easy reach of the operator thus improving safety. There will be positions for up to four (4) switch panels in the lower instrument console and up to six (6) switch panels in the overhead visor console. All switches have backlit labels for low light conditions.

Diagnostic Panel

A diagnostic panel will be accessible while standing on the ground and located inside the driver's side door left of the steering column. The diagnostic panel will allow diagnostic tools such as computers to connect to various vehicle systems for improved troubleshooting providing a lower cost of ownership. Diagnostic switches will allow ABS systems to provide blink codes should a problem exist.

The diagnostic panel will include the following:

- Engine diagnostic port
- Transmission diagnostic port
- ABS diagnostic port
- Roll sensor diagnostic port
- Command Zone USB diagnostic port
- ABS diagnostic switch (blink codes flashed on ABS telltale indicator)
- Diesel particulate filter regeneration switch (where applicable)
- Diesel particulate filter regeneration inhibit switch (where applicable)

Cab LCD Display

A digital four (4)-row by 20-character dot matrix display will be integral to the gauge panel. The display will be capable of showing simple graphical images as well as text. The display will be split into three (3) sections. Each section will have a dedicated function. The upper left section will display the outside ambient temperature.

The upper right section will display the following, along with other configuration specific information:

- Odometer
- Trip mileage
- PTO hours
- Fuel consumption
- Engine hours

The bottom section will display INFO, CAUTION, and WARNING messages. Text messages will automatically activate to describe the cause of an audible caution or warning alarm. The LCD will be capable of displaying multiple text messages should more than one caution or warning condition exist.

AIR RESTRICTION INDICATOR

A high air restriction warning indicator light LCD message with amber warning indicator and audible alarm will be provided.

- Air pressure gauge will be provided on the cab instrument panel. The gauge will indicate pressure from the brake pedal primary circuit. The white needle will be for the rear brakes and the orange needle for the front brakes.

"DO NOT MOVE APPARATUS" INDICATOR

A flashing red indicator light, located in the driving compartment, will be illuminated automatically per the current NFPA requirements. The light will be labeled "Do Not Move Apparatus If Light Is On."

The same circuit that activates the Do Not Move Apparatus indicator will activate a pulsing alarm when the parking brake is released.

DO NOT MOVE TRUCK MESSAGES

Messages will be displayed on the Command Zone™, color display located within sight of the driver whenever the Do Not Move Truck light is active. The messages will designate the item or items not in the stowed for vehicle travel position (parking brake disengaged).

The following messages will be displayed (where applicable):

- Do Not Move Truck
- DS Cab Door Open (Driver Side Cab Door Open)
- PS Cab Door Open (Passenger's Side Cab Door Open)
- DS Crew Cab Door Open (Driver Side Crew Cab Door Open)
- PS Crew Cab Door Open (Passenger's Side Crew Cab Door Open)
- DS Body Door Open (Driver Side Body Door Open)
- PS Body Door Open (Passenger's Side Body Door Open)

- Rear Body Door Open
- DS Ladder Rack Down (Driver Side Ladder Rack Down)
- PS Ladder Rack Down (Passenger Side Ladder Rack Down)
- Deck Gun Not Stowed
- Lt Tower Not Stowed (Light Tower Not Stowed)
- Fold Tank Not Stowed (Fold-A-Tank Not Stowed)
- Aerial Not Stowed (Aerial Device Not Stowed)
- Stabilizer Not Stowed
- Steps Not Stowed
- Handrail Not Stowed

Any other device that is opened, extended, or deployed that creates a hazard or is likely to cause major damage to the apparatus if the apparatus is moved will be displayed as a caution message after the parking brake is disengaged.

SWITCH PANELS

The emergency light switch panel will have a master switch for ease of use plus individual switches for selective control. Each switch panel will contain eight (8) membrane-type switches each rated for one million (1,000,000) cycles. Panels containing less than eight (8) switch assignments will include non-functioning black appliqué. The built-in switch panels will be located in the lower console or overhead console of the cab.

Additional switch panel(s) will be located in the overhead position(s) above the windshield or in designated locations on the lower instrument panel layout.

The switches will be membrane-type and also act as an integral indicator light. For quick, visual indication the entire surface of the switch will be illuminated white whenever back lighting is activated and illuminated green whenever the switch is active. An active illuminated switch will flash when interlock requirements are not met or device is actively being load managed. For ease of use, a two (2)-ply, scratch resistant laser engraved Gravoply label indicating the use of each switch will be placed in the center of the switch. The label will allow light to pass through the letters for ease of use in low light conditions.

WIPER CONTROL

For simple operation and easy reach, the windshield wiper control will be an integral part of the directional light lever located on the steering column. The wiper control will include high and low wiper speed settings, an intermittent wiper control and windshield washer switch. The control will have a "return to park" provision, which allows the wipers to return to the stored position when not in use.

CAB USB

There will be four (4) USB terminations with a combination USB type A & C, wired to switched battery power, provided per the following:

- One (1) within reach of the driver
- One (1) within reach of the passenger
- Two (2) on the rear of the engine tunnel, one (1) each side.

This circuit may be load managed.

SPARE CIRCUIT

There will be [Qty,] pair of wires, including a positive and a negative, installed on the apparatus.

The wires will have the following features:

- The positive wire will be connected [12vdc power from].
- The negative wire will be connected to ground.
- Wires will be capable of carrying 15 amps.
- Power and ground will terminate [Location, Spare Wiring].
- Termination will be [Wire termination].
- Wires will be protected to meet the NFPA Automotive Fire Apparatus standard.

The circuit(s) may be load managed when the parking brake is set.

SPARE CIRCUIT

There will be one (1) pair of wires, including a positive and a negative, installed on the apparatus.

The wires will have the following features:

The positive wire will be connected directly to the battery switched power.

The negative wire will be connected to ground.

Wires will be capable of carrying 30 amps.

Power and ground will terminate behind the officer seat.

Termination will be to a Blue Sea System, Model 5025, 6 circuit with negative bus bar. The terminal block will include a cover with circuit labels.

Wires will be protected to meet the NFPA Automotive Fire Apparatus standard.

This circuit(s) may be load managed when the parking brake is set.

SPARE CIRCUIT

There will be one (1) pair of wires, including a positive and a negative, installed on the apparatus.

The wires will have the following features:

- The positive wire will be connected directly to the battery power
- The negative wire will be connected to ground
- Wires will be capable of carrying 15 amps
- Power and ground will terminate in the cab on the rear area of the engine tunnel
- Termination will be a Blue Sea part number 4365 panel with switch
- Wires will be protected to meet the NFPA Automotive Fire Apparatus standard

Battery direct loads cannot be load managed.

SPARE CIRCUIT

There will be seven (7) pair of wires, including a positive and a negative, installed on the apparatus.

The wires will have the following features:

The positive wire will be connected directly to the battery switched power.

The negative wire will be connected to ground.

Wires will be capable of carrying 30 amps.

Power and ground will terminate one in each body compartment, to be placed at preconstruction.

Termination will be to a Blue Sea System, Model 5025, 6 circuit with negative bus bar. The terminal block will include a cover with circuit labels.

Wires will be protected to meet the NFPA Automotive Fire Apparatus standard.

This circuit(s) may be load managed when the parking brake is set.

SPARE CIRCUIT

There will be one (1) pair of wires, including a positive and a negative, installed on the apparatus.

The wires will have the following features:

- The positive wire will be connected directly to the battery power
- The negative wire will be connected to ground
- Wires will be capable of carrying 15 amps
- Power and ground will terminate to be determined
- Termination will be a 15 amp power point plug with a rubber cover
- Wires will be protected to meet the NFPA Automotive Fire Apparatus standard

There will be a 2-Port USB-C charger adapter provided.

Battery direct loads cannot be Load Managed

STEREO RADIO

There will be one heavy duty AM/FM / Weatherband / Bluetooth stereo radio. The radio will be installed within reach of the officer. There will be 5.25" speakers installed one (1) pair of 5.25" speakers in the cab and one (1) pair of 5.25" speakers in the crew cab. The antenna will be a roof-mounted rubber antenna located in an open space, on the cab roof.

The following Jensen features will be included:

- 180 watts max power (45W x 4); 100 watts RMS (25W x 4)
- Bluetooth® streaming audio (A2DP/AVRCP)
- Weatherband
- AM/FM tuner with 30 presets

- Rear USB port for charging
- Stereo pre-amp line-level output (2V RMS)
- Amplifier remote trigger (12 VDC)
- PA microphone input
- Audio settings (volume/bass/treble/balance/fade)
- Toggle switch between day and night display
- Daylight-readable, segmented LCD
- Two-wire power with non-volatile memory and clock support
- Low battery alert

INFORMATION CENTER

An information center employing a 7.00" diagonal touch screen color LCD display will be encased in an ABS plastic housing.

The information center will have the following specifications:

- Operate in temperatures from -40 to 158 degrees Fahrenheit
- LCD optically bonded to hardened AR glass lens
- Five weather resistant user interface switches
- Grey with black accents
- Sunlight Readable
- Linux operating system
- Minimum of 1000nits rated display
- Display can be changed to an available foreign language
- A LCD display integral to the cab gauge panel will be included as outlined in the cab instrumentation area.
- Programmed to read US Customary

General Screen Design

Where possible, background colors will be used to provide "At a Glance" vehicle information. If information provided on a screen is within acceptable limits, a green background will be used.

If a caution or warning situation arises the following will occur:

- An amber background/text color will indicate a caution condition
- A red background/text color will indicate a warning condition
- The information center will utilize an "Alert Center" to display text messages for audible alarm tones. The text messages will be written to identify the item(s) causing the audible alarm to sound. If more than one (1) text message occurs, the messages will cycle every second until the problem(s) have been resolved. The background color for the "Alert Center" will change to

indicate the severity of the "warning" message. If a warning and a caution condition occur simultaneously, the red background color will be shown for all alert center messages.

- A label for each button will exist. The label will indicate the function for each active button for each screen. Buttons that are not utilized on specific screens will have a button label with no text or symbol.

Home/Transit Screen

This screen will display the following:

- Vehicle Mitigation (if equipped)
- Water Level (if the water level system includes compatible communications to the information center)
- Foam Level (if the foam level system includes compatible communications to the information center)
- Seat Belt Monitoring Screen
- Tire Pressure Monitoring (if equipped)
- Digital Speedometer
- Active Alarms

On Scene Screen

This screen will display the following and will be auto activated with pump engaged (if equipped):

- Battery Voltage
- Fuel
- Oil Pressure
- Coolant Temperature
- RPM
- Water Level (if equipped)
- Foam Level (if equipped)
- Foam Concentration (if equipped)
- Water Flow Rate (if equipped)
- Water Used (if equipped)
- Active Alarms

Virtual Buttons

There will be four (4) virtual switch panel screens that match the overhead and lower lighting and HVAC switch panels.

Page Screen

The page screen will display the following and allow the user to progress into other screens for further functionality:

- Diagnostics
 - Faults
 - Listed by order of occurrence

- Allows to sort by system
 - Interlock
 - Throttle Interlocks
 - Pump Interlocks (if equipped)
 - Aerial Interlocks (if equipped)
 - PTO Interlocks (if equipped)
 - Load Manager
 - A list of items to be load managed will be provided. The list will provide a description of the load.
 - The lower the priority numbers the earlier the device will be shed should a low voltage condition occur.
 - The screen will indicate if a load has been shed (disabled) or not shed.
 - "At a glance" color features are utilized on this screen.
 - Systems
 - Command Zone
 - Module type and ID number
 - Module Version
 - Input or output number
 - Circuit number connected to that input or output
 - Status of the input or output
 - Power and Constant Current module diagnostic information
 - Foam (if equipped)
 - Pressure Controller (if equipped)
 - Generator Frequency (if equipped)
 - Live Data
 - General Truck Data
- Maintenance
 - Engine oil and filter
 - Transmission oil and filter
 - Pump oil (if equipped)
 - Foam (if equipped)
 - Aerial (if equipped)
- Setup
 - Clock Setup
 - Date & Time
 - 12 or 24 hour format
 - Set time and date
 - Backlight
 - Daytime
 - Night time
 - Sensitivity
 - Unit Selection
 - Home Screen
 - Virtual Button Setup

- On Scene Screen Setup
- Configure Video Mode
 - Set Video Contrast
 - Set Video Color
 - Set Video Tint
- Do Not Move
 - The screen will indicate the approximate location and type of item that is open or is not stowed for travel. The actual status of the following devices will be indicated
 - Driver Side Cab Door
 - Passenger's Side Cab Door
 - Driver Side Crew Cab Door
 - Passenger's Side Crew Cab Door
 - Driver Side Body Doors
 - Passenger's Side Body Doors
 - Rear Body Door(s)
 - Ladder Rack (if applicable)
 - Deck Gun (if applicable)
 - Light Tower (if applicable)
 - Hatch Door (if applicable)
 - Stabilizers (if applicable)
 - Steps (if applicable)
- Notifications
 - View Active Alarms
 - Shows a list of all active alarms including date and time of the occurrence is shown with each alarm
 - Silence Alarms - All alarms are silenced
- Timer Screen
- HVAC (if equipped)
- Tire Information (if equipped)
- Ascendant Set Up Confirmation (if equipped)

Button functions and button labels may change with each screen.

VEHICLE DATA RECORDER

There will be a vehicle data recorder (VDR) capable of reading and storing vehicle information provided.

The information stored on the VDR can be downloaded through a USB port mounted in a convenient location determined by cab model. A USB cable can be used to connect the VDR to a laptop to retrieve required information. The program to download the information from the VDR will be available to download on-line.

The vehicle data recorder will be capable of recording the following data via hardwired and/or CAN inputs:

- Vehicle Speed - MPH
- Acceleration - MPH/sec
- Deceleration - MPH/sec
- Engine Speed - RPM
- Engine Throttle Position - % of Full Throttle
- ABS Event - On/Off
- Seat Occupied Status - Yes/No by Position
- Seat Belt Buckled Status - Yes/No by Position
- Master Optical Warning Device Switch - On/Off
- Internal clock syncs the time and date when a laptop is connected

Seat Belt Monitoring System

A seat belt monitoring system (SBMS) will be provided on the Command Zone™ color display and in the center overhead of the cab instrument panel. The SBMS will be capable of monitoring up to 10 seating positions indicating the status of each seat position per the following:

- Seat Occupied & Buckled = Green LED indicator illuminated
- Seat Occupied & Unbuckled = Red LED indicator with audible alarm
- No Occupant & Buckled = Red LED indicator with audible alarm
- No Occupant & Unbuckled = No indicator and no alarm
- FAULT = Blue LED indicator illuminated

The seat belt monitoring screen will become active on the Command Zone color display when:

- The home screen is active:
 - and there is any occupant seated but not buckled or any belt buckled with an occupant.
 - and there are no other Do Not Move Apparatus conditions present. As soon as all Do Not Move Apparatus conditions are cleared, the SBMS will be activated.

The SBMS will include an audible alarm that will warn that an unbuckled occupant condition exists and the parking brake is released, or the transmission is not in park.

Corona Radio Package per Johnson Equipment Quote 6608

VEHICLE CAMERA SYSTEM

There will be a FRC/Seon InView 360 HD™ degree surround view four (4) high definition camera system provided.

The system will have a built-in DVR with built in GPS and accelerometer to record all connected cameras. There will be an GPS antennas provided. There will be one (1) Secure Digital (SD) 32 GigaByte (GB) card provided.

There will be a WIFI antenna provided.

The camera images will be displayed on a 7" display in view of the driver located to be determined. The left side of the screen will always show the 360-degree view

The right side of the screen will show:

- The rear camera when the transmission is in reverse
- The right side camera when the right turn signal is active
- The left side camera when the left turn signal is active
- the forward camera with no triggers active.

A green view button and red event button will be installed in reach of the driver on the dash, the view button will activate the camera image on the display when no triggers are present.

System calibration will be provided by an FRC/Seon third party vendor.

The following components will be included:

- One (1) SNB100-C00-MS0 7" Cab monitor kit
- All Necessary Cables

Camera Switcher

A camera switcher is not required.

ELECTRICAL POWER CONTROL SYSTEM

The primary power distribution will be located forward of the officer's seating position and be easily accessible while standing on the ground for simplified maintenance and troubleshooting. Additional electrical distribution centers will be provided throughout the vehicle to house the vehicle's electrical power, circuit protection, and control components. The electrical distribution centers will be located strategically throughout the vehicle to minimize wire length. For ease of maintenance, all electrical distribution centers will be easily accessible. All distribution centers containing fuses, circuit breakers and/or relays will be easily accessible.

Distribution centers located throughout the vehicle will contain battery powered studs for supplying customer installed equipment thus providing a lower cost of ownership.

Circuit protection devices, which conform to SAE standards, will be utilized to protect electrical circuits. All circuit protection devices will be rated per NFPA requirements to prevent wire and component damage when subjected to extreme current overload. General protection circuit breakers will be Type-I automatic reset (continuously resetting). When required, automotive type fuses will be utilized to protect electronic equipment. Control relays and solenoid will have a direct current rating of 125 percent of the maximum current for which the circuit is protected per NFPA.

Solid-State Control System

A solid-state electronics based control system will be utilized to achieve advanced operation and control of the vehicle components. A fully computerized vehicle network will consist of electronic modules, electronic control modules to include a see through housing, a power indicator, a status indicator and circuit indicators located near their point of use to reduce harness lengths and improve reliability. The control system will comply with SAE J1939-11 recommended practices.

The control system will operate as a master-slave system whereas the main control module instructs all other system components. The system will contain patented Mission Critical software that maintains critical vehicle operations in the unlikely event of a main controller error. The system will utilize a Real Time Operating System (RTOS) fully compliant with OSEK/VDX™ specifications providing a lower cost of ownership.

For increased reliability and simplified use the control system modules will include the following attributes:

- Green LED indicator light for module power
- Red LED indicator light for network communication stability status
- Control system self test at activation and continually throughout vehicle operation
- No moving parts due to transistor logic
- Software logic control for NFPA mandated safety interlocks and indicators
- Integrated electrical system load management without additional components
- Integrated electrical load sequencing system without additional components
- Customized control software to the vehicle's configuration
- Factory and field programmable to accommodate changes to the vehicle's operating parameters

To assure long life and operation in a broad range of environmental conditions, the solid-state control system modules will meet the following specifications:

- Module circuit board will meet SAE J771 specifications
- Operating temperature from -40 degrees Celsius to +70 degrees Celsius
- Storage temperature from -40 degrees Celsius to +70 degrees Celsius
- Vibration to 50g
- IP67 rated enclosure (Totally protected against dust and also protected against the effect of temporary immersion between 15 centimeters and one (1) meter)
- Operating voltage from eight (8) volts to 32 volts DC

The main controller will activate status indicators and audible alarms designed to provide warning of problems before they become critical.

Circuit Protection and Control Diagram

Copies of all job-specific, computer network input and output (I/O) connections will be provided with each chassis. The sheets will indicate the function of each module connection point, circuit protection information (where applicable), wire numbers, wire colors and load management information.

On-Board Electrical System Diagnostics

The on-board information center will include the following diagnostic information:

- Text description of active warning or caution alarms
- Simplified warning indicators
- Amber caution indication with intermittent alarm
- Red warning indication with steady tone alarm

Advanced diagnostic feature will be provided in this control system. From the Command Zone display or connected wireless device, these features allow the user to monitor the real-time status of every input or output on the vehicle. It also allows users logged in as an administrator to force on inputs or outputs to assist the troubleshooting process.

TCU Module with WiFi

An in cab module will provide WiFi wireless interface and data logging capability. The WiFi interface will comply with IEEE 802.11 b/g/n capabilities while communicating at 2.4 Gigahertz. The module will communicate through a black WiFi antenna allowing a line of site communication range of up to 300 feet with a roof mounted antenna.

The module will transmit a password protected web page to a WiFi enabled device (i.e. most smart phones, tablets or laptops) allowing two levels of user interaction. The firefighter level will allow vehicle monitoring of the vehicle and firefighting systems on the apparatus. The technician level will allow diagnostic access to inputs and outputs installed on the Command Zone™, control and information system.

The TCU capability will record faults from the engine, transmission, ABS and Command Zone™, control and information systems as they occur. No other data will be recorded at the time the fault occurs. The data TCU will provide up to 2 Gigabytes of data storage.

The TCU will provide a means to download the TCU information and update software in the device.

Indicator Light and Alarm Prove-Out System

A system will be provided which automatically tests basic indicator lights and alarms located on the cab instrument panel.

Voltage Monitor System

A voltage monitoring system will be provided to indicate the status of the battery system connected to the vehicle's electrical load. The system will provide visual and audible warning when the system voltage is below or above optimum levels.

The alarm will activate if the system falls below 11.8 volts DC for more than two (2) minutes.

Dedicated Radio Equipment Connection Points

There will be three (3) studs provided in the primary power distribution center located in front of the officer for two-way radio equipment. The studs will consist of the following:

- 12-volt 40-amp battery switched power
- 12-volt 60-amp ignition switched power
- 12-volt 60-amp direct battery power

There will also be a 12-volt 100-amp ground stud located in or adjacent to the power distribution center.

EMI/RFI Protection

To prevent erroneous signals from crosstalk contamination and interference, the electrical system will meet, at a minimum, SAE J551/2, thus reducing undesired electromagnetic and radio frequency

emissions. An advanced electrical system will be used to ensure radiated and conducted electromagnetic interference (EMI) or radio frequency interference (RFI) emissions are suppressed at their source.

The apparatus will have the ability to operate in the electromagnetic environment typically found in fire ground operations to ensure clean operations. The electrical system will meet, without exceptions, electromagnetic susceptibility conforming to SAE J1113/25 Region 1, Class C EMR for 10KHz-1GHz to 100 Volts/Meter. The vehicle OEM, upon request, will provide EMC testing reports from testing conducted on an entire apparatus and will certify that the vehicle meets SAE J551/2 and SAE J1113/25 Region 1, Class C EMR for 10KHz-1GHz to 100 Volts/Meter requirements. Component and partial (incomplete) vehicle testing is not adequate as overall vehicle design can impact test results and thus is not acceptable by itself.

EMI/RFI susceptibility will be controlled by applying appropriate circuit designs and shielding. The electrical system will be designed for full compatibility with low-level control signals and high-powered two-way radio communication systems. Harness and cable routing will be given careful attention to minimize the potential for conducting and radiated EMI/RFI susceptibility.

ELECTRICAL SYSTEM PROGNOSTICS

There will be a software based vehicle tool provided to predict remaining life of the vehicles critical fluid and events.

The system will send automatic indications to the Command Zone™ information center and/or wireless enabled devices to proactively alert of upcoming service intervals.

Prognostics will include the following:

- Engine oil and filter
- Transmission oil and filter

ELECTRICAL

All 12-volt electrical equipment installed by the apparatus manufacturer will conform to modern automotive practices. All wiring will be high temperature crosslink type. Wiring will be run, in loom or conduit, where exposed and have grommets where wire passes through sheet metal. Automatic reset circuit breakers will be provided which conform to SAE Standards. Wiring will be color, function and number coded. Function and number codes will be continuously imprinted on all wiring harness conductors at 2.00" intervals. Exterior exposed wire connectors will be positive locking, and environmentally sealed to withstand elements such as temperature extremes, moisture and automotive fluids.

Electrical wiring and equipment will be installed utilizing the following guidelines:

1. All holes made in the roof will be caulked with silicon. Large fender washers, liberally caulked, will be used when fastening equipment to the underside of the cab roof.
2. Any electrical component that is installed in an exposed area will be mounted in a manner that will not allow moisture to accumulate in it. Exposed area will be defined as any location outside of the cab or body.

3. Electrical components designed to be removed for maintenance will not be fastened with nuts and bolts. Metal screws will be used in mounting these devices. Also a coil of wire will be provided behind the appliance to allow them to be pulled away from mounting area for inspection and service work.
4. Corrosion preventative compound will be applied to all terminal plugs located outside of the cab or body. All non-waterproof connections will require this compound in the plug to prevent corrosion and for easy separation (of the plug).
5. All lights that have their sockets in a weather exposed area will have corrosion preventative compound added to the socket terminal area.
6. All electrical terminals in exposed areas will have silicon applied completely over the metal portion of the terminal.

All lights and reflectors, required to comply with Federal Motor Vehicle Safety Standard #108, will be furnished. Rear identification lights will be recessed mounted for protection. Lights and wiring mounted in the rear bulkheads will be protected from damage by installing a false bulkhead inside the rear compartments.

An operational test will be conducted to ensure that any equipment that is permanently attached to the electrical system is properly connected and in working order.

The results of the tests will be recorded and provided to the purchaser at time of delivery.

BATTERY SYSTEM

Five-(5) Optima 1000M 12 volt, 800 CCA, 110 min reserve capacity, batteries with a system rating of 4000 CCA at 0 degrees Fahrenheit and 550 minutes of reserve capacity. The batteries will be provided with SAE posts.

ISOLATED BATTERY

One (1)-12 volt, Optima 1000M battery will be provided for voltage sensitive components. A battery isolator that is appropriately suited for the battery capacity will be supplied.

BATTERY SYSTEM

There will be a single starting system with an ignition switch and starter button provided and located on the cab instrument panel.

MASTER BATTERY SWITCH

There will be a master battery switch provided within the cab within easy reach of the driver to activate the battery system.

An indicator light will be provided on the instrument panel to notify the driver of the status of the battery system.

BATTERY COMPARTMENTS

Batteries will be placed on non-corrosive mats and be stored in well ventilated compartments located under the cab and bolted directly to the chassis frame. The battery boxes will have reinforced sides. The battery compartments will be constructed of 0.188" steel plate and be designed to accommodate a

maximum of three (3) group 31 batteries in each compartment. The battery hold-downs will be of a non-corrosive material. All bolts and nuts will be stainless steel.

Heavy-duty, 2/0 gauge, color coded battery cables will be provided. Battery terminal connections will be coated with anti-corrosion compound.

Battery solenoid terminal connections will be encapsulated with semi-permanent rubberized compound.

JUMPER STUDS

One (1) set of battery jumper studs with plastic color-coded covers will be included on the battery compartments.

INVERTER / BATTERY CHARGER

There will be a Xantrex part number 817-2080, 2000W inverter/charger with internal 30A transfer relay provided.

The inverter will be connected battery direct through proper fusing and also to AC shoreline power. A load management solenoid will be installed between the battery and the inverter. The inverter will be connected to power when the battery switch is on and system voltage is above the low voltage threshold or when the shoreline is connected.

When the shoreline is connected to the truck, the internal auto transfer switch will allow AC shoreline power to pass through the inverter to the AC loads connected to the inverter.

When the shoreline is connected to the truck, the battery charger function will be active.

There will be an on/off switch provided in the driver side cab switch panel.

Per NFPA1900, 2024 Edition 21.5.5.2*

The alternator and/or battery system will be adequate to provide power for continuous operation for a minimum of 2 hours at full output.

Per the fire department specifications, if all DC loads on the NFPA required electrical analysis report are active, the alternator cannot provide adequate power for continuous operation for 2 hours. The apparatus will be non-compliant to NFPA 1900 standards at time of contract execution.

Load management will be activated in low voltage situations, and the inverter will be de-energized until chassis electrical system voltage recovers.

The battery charger output will be a maximum of 18V DC at 80A (selectable).

The battery charger/inverter will be located in the left side forward body compartment located on the ceiling as far to the left side as practical.

BATTERY CHARGE DISPLAY

There will be one (1) Kussmaul™, Model 091-94-12, universal single battery bank bar graph display provided.

The display will read voltage direct from the battery system.

The battery charger/Inverter status indication/display(s) will be located above the cab left side wheel well.

AUTO EJECT FOR SHORELINE

There will be two (2) Kussmaul™, Model 091-55-20-120, 20 amp 120 volt AC shoreline inlet(s) provided to operate the dedicated 120 volt AC circuits on the apparatus.

The shoreline inlet(s) will include red weatherproof flip up cover(s).

There will be a release solenoid wired to the vehicle's starter to eject the AC connector when the engine is starting.

The shoreline(s) will be connected to Battery Charger and Aux AC unit..

There will be a mating connector body supplied with the loose equipment.

There will be a label installed near the inlet(s) that state the following:

- Line Voltage
- Current Rating (amps)
- Phase
- Frequency

The shoreline receptacle will be located on the driver side of cab, above wheel.

BATTERY SAVER

There will be one (1) Kussmaul, Model 091-295-12, 20 amp battery saver will be provided.

The battery saver will be located to be determined.

The items to be connected to this device are ..

This device will be connected to the 120 volt AC shoreline inlet.

This device will be connected to the chassis batteries to charge items when the shoreline is not plugged in.

ALTERNATOR

A Delco Remy®, Model 55SI, alternator will be provided. It will have a rated output current of 430 amps, as measured by SAE method J56. The alternator will feature an integral regulator and rectifier system that has been tested and qualified to an ambient temperature of 257 degrees Fahrenheit (125 degrees Celsius). The alternator will be connected to the power and ground distribution system with heavy-duty cables sized to carry the full rated alternator output.

ELECTRONIC LOAD MANAGER

An electronic load management (ELM) system will be provided that monitors the vehicles 12-volt electrical system, automatically reducing the electrical load in the event of a low voltage condition, and automatically restoring the shed electrical loads when a low voltage condition expires. This ensures the integrity of the electrical system.

For improved reliability and ease of use, the load manager system will be an integral part of the vehicle's solid state control system requiring no additional components to perform load management tasks. Load management systems which require additional components will not be allowed.

The system will include the following features:

- System voltage monitoring.
- A shed load will remain inactive for a minimum of five minutes to prevent the load from cycling on and off.
- Sixteen available electronic load shedding levels.
- Priority levels can be set for individual outputs.
- High Idle to activate before any electric loads are shed and deactivate with the service brake.
 - If enabled:
 - "Load Man Hi-Idle On" will display on the information center.
 - Hi-Idle will not activate until 30 seconds after engine start up.
- Individual switch "on" indicator to flash when the particular load has been shed.
- The information center indicates system voltage.

The information center, where applicable, includes a "Load Manager" screen indicating the following:

- Load managed items list, with priority levels and item condition.
- Individual load managed item condition:
 - ON = not shed
 - SHED = shed

SEQUENCER

A sequencer will be provided that automatically activates and deactivates vehicle loads in a preset sequence thereby protecting the alternator from power surges. This sequencer operation will allow a gradual increase or decrease in alternator output, rather than loading or dumping the entire 12 volt load to prolong the life of the alternator.

For improved reliability and ease of use, the load sequencing system will be an integral part of the vehicle's solid state control system requiring no additional components to perform load sequencing tasks. Load sequencing systems which require additional components will not be allowed.

Emergency light sequencing will operate in conjunction with the emergency master light switch. When the emergency master switch is activated, the emergency lights will be activated one by one at half-second intervals. Sequenced emergency light switch indicators will flash while waiting for activation.

When the emergency master switch is deactivated, the sequencer will deactivate the warning light loads in the reverse order.

Sequencing of the following items will also occur, in conjunction with the ignition switch, at half-second intervals:

- Cab Heater and Air Conditioning
- Crew Cab Heater (if applicable)

- Crew Cab Air Conditioning (if applicable)
- Exhaust Fans (if applicable)
- Third Evaporator (if applicable)

HEADLIGHTS

There will be a HiViz, P/N FT-4X6-4KIT, that includes four (4) 4.00" high x 6.00" long rectangular LED lights with parking lamp illumination around the outside of the lamps mounted in the front quad style, chrome housing on each side of the cab grille:

- The outside lamp on each side will contain P/N FT-4X6-HL with low beam LEDs.
- The inside lamp on each side will contain P/N FT-4X6-H with high beam LEDs.
- The lights will be controlled through the headlight switch.

FRONT DIRECTIONALS

The front directional's will be Whelen®, Model M62T, 4.31" high x 6.75" wide x 1.37" deep directional lights with amber LEDs. The lens color(s) to be the same as the LEDs. The directional's will be housed in the same common bezel as the front warning light and will be located above the headlights. The housing to be polished and the trim shall be chrome.

The flash pattern of the directional lights will be Steady On (Arrow).

INTERMEDIATE LIGHT

There will be two (2) Weldon, Model 9186-8580-29, amber LED turn signal marker lights furnished, one (1) each side, in the rear fender panel. The light will double as a turn signal and marker light.

CAB CLEARANCE LIGHTS

There will be two (2) amber LED lights provided to indicate the overall width of the vehicle, one (1) on each outboard side of the cab above the windshield.

FRONT CAB SIDE DIRECTIONAL/MARKER LIGHTS

There will be two (2) Weldon, Model 9186-8580-29, amber LED lights installed front of the cab door, one (1) on each side of the cab.

The lights will activate as marker lights with the headlight switch and directional lights with the corresponding directional circuit.

REAR CLEARANCE/MARKER/ID LIGHTING

There will be a three (3) LED light bar used as identification lights located at the rear of the apparatus per the following:

- As close as practical to the vertical centerline
- Centers spaced not less than 6.00" or more than 12.00" apart
- Red in color
- All at the same height

There will be two (2) LED lights installed at the rear of the apparatus used as clearance lights located at the rear of the apparatus per the following:

- To indicate the overall width of the vehicle
- One (1) each side of the vertical centerline
- As near the top as practical
- Red in color
- To be visible from the rear
- All at the same height

There will be two (2) LED lights installed on the side of the apparatus used as marker lights as close to the rear as practical per the following:

- To indicate the overall length of the vehicle
- One (1) each side of the vertical centerline
- As near the top as practical
- Red in color
- To be visible from the side
- All at the same height

There will be two (2) red reflectors located on the rear of the truck facing to the rear. One (1) each side, as far to the outside as practical, at a minimum of 15.00", but no more than 60.00", above the ground.

There will be two (2) red reflectors located on the side of the truck facing to the side. One (1) each side, as far to the rear as practical, at a minimum of 15.00", but no more than 60.00", above the ground.

Per FMVSS 108 and CMVSS 108 requirements.

REAR FMVSS LIGHTING

The rear stop/tail and directional lighting included in the rear tail light housing will include the following:

- Two (2) Whelen®, Model M62BTT, 4.30" high x 6.70" wide x 1.40" deep brake/tail lights with red LEDs
- Two (2) Whelen, Model M62T, 4.30" high x 6.70" wide x 1.40" deep directional lights with amber LEDs. The directional lights will be set to Steady On (Arrow) flash pattern.
- The lens color(s) to be the same as the LEDs.

There will be two (2) Whelen Model M62BU, LED backup lights provided in the tail light housing.

LICENSE PLATE BRACKET

One (1) license plate bracket constructed of stainless steel will be provided at the rear of the apparatus.

One (1) white LED light with chrome housing will be provided to illuminate the license plate. A stainless steel light shield will be provided over the light that will direct illumination downward, preventing white light to the rear.

LIGHTING BEZEL

There will be two (2) Whelen, Model M6FCV4P, four (4) place chromed ABS housings with Pierce logos provided for the rear M6 series stop/tail, directional, back up, scene lights or warning lights.

ADDITIONAL BRAKE/TAIL LIGHT

There will be one (1) Whelen, Model M62BTT, LED brake/tail light with chrome trim trim provided at the rear of the body, centered high below hosebed.

The lens color(s) to be the same as the LEDs.

BACK-UP ALARM

There will be an ECCO, Model SA917, electronic audible back-up alarm provided.

This alarm will be activated when the truck is shifted into reverse.

WARNING LIGHT FLASH PATTERN

The flash pattern of all the exterior warning lights will be set to meet the certified California, Title XIII flash pattern by either the light manufacturer's default flash pattern or by a conversion change to the certified flash pattern.

CAB PERIMETER SCENE LIGHTS

There will be four (4) TecNiq Model E10-WS00-1, 6.44" long x 1.38" high x 1.00" deep 12 volt DC weatherproof LED lights with a fabricated aluminum 45 degree brackets provided under the cab and crew cab access areas:

- One (1) for the driver's access.
- One (1) for the passenger's side front cab access door.
- One (1) for the passenger's side crew cab access door.
- One (1) for the driver's side crew cab access door.

These lights will be activated automatically when the battery switch is on and the adjacent doors are opened or by the same means as the body perimeter lights.

PUMP HOUSE PERIMETER LIGHTS

There will be two (2) TecNiq, Model E10-WS00-1, 1.39" high x 6.39" long 12 volt DC LED light with white LEDs provided under the pump panel running boards, one (1) each side.

The lights will be controlled by the same means as the body perimeter lights.

BODY PERIMETER SCENE LIGHTS

There will be two (2) TecNiq, Model E10-WS00-1, 1.39" high x 6.39" long 12 volt DC LED lights white LEDs provided at the rear step area of the body, one (1) each side shining to the rear.

The perimeter scene lights will be activated when a switch within reach of the driver is activated, the parking brake is applied and the rear scene lights are activated.

ADDITIONAL PERIMETER LIGHTS

There will be two (2) TecNiq, Model T10-LC00-1, 1.25" high x 15.00" long white LED light(s) provided under under the LS3 and RS3 compartment.

These additional lights will be controlled with the other body perimeter lights.

ENHANCED SOFTWARE FOR PERIMETER LIGHTS

All perimeter lights will be deactivated when the parking brake is released unless alternate control is selected.

The cab and crew cab perimeter lights will remain on for ten (10) seconds for improved visibility after the doors closed.

STEP LIGHTS

Four (4) white LED step lights will be provided. One (1) step light will be provided on each side, on the front compartment face and two (2) step lights at the rear to illuminate the tailboard.

These step lights will be actuated with the pump panel light switch.

All steps on the apparatus will be illuminated per the current edition of applicable NFPA standards.

SIDE SCENE LIGHTS

There will be two (2) HiViz, Model FT-GSM, 10,000 equivalent lumens 8.65" high x 10.61" wide x 2.75" deep light(s) with white LEDs installed on the side of the apparatus, one (1) high and forward on driver's side body and one (1) high and rearward on driver's side body.

The light(s) will be activated by a switch at the driver's side switch panel and by a switch at the left side pump panel.

The light(s) may be load managed when the parking brake is applied.

SCENE LIGHTS

There will be two (2) HiViz, Model FT-GSMJR, 3,125 effective lumens 5.04" high x 7.40" wide x 1.54" deep light(s) with white LEDs installed one each side centered over the forward axle.

The light(s) will be activated by a switch at the driver's side switch panel.

The light(s) may be load managed when the parking brake is applied.

SIDE SCENE LIGHTS

There will be two (2) HiViz, Model FT-GSM, 10,000 equivalent lumens 8.65" high x 10.61" wide x 2.75" deep light(s) with white LEDs installed on the side of the apparatus, one (1) high and forward on driver's side body and one (1) high and rearward on driver's side body.

The light(s) will be activated by a switch at the driver's side switch panel and by a switch at the left side pump panel.

The light(s) may be load managed when the parking brake is applied.

12 VOLT LIGHTING

There will be a HiViz Model FT-B-72-*-* , 2.56" high x 72.69" long x 3.31" deep 21,067 effective lumens 12 volt DC light with white LEDs configured with a combination of flood and spot optics provided on brackets in front of the cab roof.

The painted parts of the light housing and brackets to be black.

The light will be activated by a switch at the driver's side switch panel.

The light may be load managed when the parking brake is applied.

12 VOLT LIGHTING - BODY

There will be two (2) HiViz®, Model FT-GESM, surface mount, 20,500 equivalent lumens, 8.65" high x 10.61" wide x 2.78" deep with white LED's installed on the body high on each side of the rear body bulkhead. The light(s) to include chrome optic holders, chrome bezel and white fixture body paint and white circuit boards. The light(s) will be activated by a switch at the passenger's side switch panel and by a switch in a stainless steel cup located on the driver's side at the rear of the apparatus no more than 72.00" from the ground.

The light(s) may be load managed when the parking brake is applied.

HOSE BED LIGHTS

There will be white 12 volt DC LED light strips with stainless steel protective cover, provided to light the hose bed area. Hose Bed lights will meet the photometric levels listed in the current edition of applicable NFPA standards for Hose Bed lighting requirements.

- Light strip(s) will be installed along the upper edge of the left side of the hose bed.
- Light strip(s) will be installed along the upper edge of the right side of the hose bed.

The lights will be activated by a cup switch at the rear of the apparatus no more than 72.00" from the ground.

WALKING SURFACE LIGHT

There will be Model FRP, 4.00" round black 12 volt DC LED floodlight(s) with bolt mount provided to illuminate the entire designated walking surface on top of the body.

The light(s) will be activated when the body step lights are on.

MASTER SWITCH FOR BODY COMPARTMENT LIGHTS

A master on/off switch with indicator light will be provided in the cab on the instrument panel for the body compartment lights.

WATER TANK

Booster tank will have a capacity of 500 gallons and be constructed of polypropylene plastic by United Plastic Fabricating, Incorporated.

Tank joints and seams will be nitrogen welded inside and out.

Tank will be baffled in accordance with the current edition of applicable NFPA standards.

Baffles will have vent openings at both the top and bottom to permit movement of air and water between compartments.

Longitudinal partitions will be constructed of .38" polypropylene plastic and will extend from the bottom of the tank through the top cover to allow for positive welding.

Transverse partitions will extend from 4.00" off the bottom of the tank to the underside of the top cover.

All partitions will interlock and will be welded to the tank bottom and sides.

Tank top will be constructed of .50" polypropylene. It will be recessed .38" and will be welded to the tank sides and the longitudinal partitions.

Tank top will be sufficiently supported to keep it rigid during fast filling conditions.

Construction will include 2.00" polypropylene dowels spaced no more than 30.00" apart and welded to the transverse partitions. Two (2) of the dowels will be drilled and tapped (.50" diameter, 13.00" deep) to accommodate lifting eyes.

A sump that will be sized dependent on the tank to pump plumbing will be provided at the bottom of the water tank.

Sump will include a drain plug and the tank outlet.

Tank will be installed in a fabricated cradle assembly constructed of structural steel.

Sufficient crossmembers will be provided to properly support bottom of tank. Crossmembers will be constructed of steel bar channel or rectangular tubing.

Tank will "float" in cradle to avoid torsional stress caused by chassis frame flexing. Rubber cushions, .50" thick x 3.00" wide, will be placed on all horizontal surfaces that the tank rests on.

Stops or other provision will be provided to prevent an empty tank from bouncing excessively while moving vehicle.

Mounting system will be approved by the tank manufacturer.

Fill tower will be constructed of 0.50" polypropylene and will be a minimum of 8.00" wide x 14.00" long.

Fill tower will be furnished with a 0.25" thick polypropylene screen and a hinged cover.

An overflow pipe, constructed of 4.00" schedule 40 polypropylene, will be installed approximately halfway down the fill tower and extend through the water tank and exit to the rear of the rear axle.

SLEEVE PLUMBING THROUGH TANK

One (1) sleeve will be provided in the water tank for a 3.00" pipe to the rear.

HOSE BED

The hose bed will be fabricated of 0.125"-5052 aluminum with a nominal 38,000 psi tensile strength.

Upper and rear edges of side panels will have a double break for rigidity, a split tube finish will not be acceptable.

The upper area at the rear of the hose bed will be covered with brushed stainless steel to prevent damage to painted surface when hose is removed.

Flooring of the hose bed will be removable aluminum grating with the top surface corrugated to aid in hose aeration. The grating slats will be a minimum of 0.50" x 4.50" with spacing between slats for hose ventilation.

The hose bed interior walls will be painted to match the lower body color.

Hose bed will accommodate 200' of 1.5", 200' or 1.75", 600' of 2.5", 800' of 4".

HOSE BED DIVIDER

Three (3) hosebed dividers will be furnished for separating hose.

Each divider will be constructed of a .25" brushed aluminum sheet. Flat surfaces will be sanded for uniform appearance, or constructed of brushed aluminum.

An oval opening will be provided near the rear of the divider to be used as a hand hold and aid in accessing the hose bed.

Divider will be fully adjustable by sliding in tracks, located at the front and rear of the hose bed.

Divider will be held in place by tightening bolts, at each end.

Acorn nuts will be installed on all bolts in the hose bed which have exposed threads.

HOSE BED COVER

A roller shutter style hose bed cover will be supplied.

The cover will be the full length and width of the hose bed area.

The cover will be constructed of stainless steel with aluminum support channels bonded and mechanically fastened to the bottom. The cover will have a non-slip coating applied to the top surface.

A lift bar will be located at the rear of door and have latches on the outer extrusion of the door frame to hold the door in the closed position.

A cross divider will be provided at the front of the hose bed to section off the door roll area.

This cover will be included in the "Do Not Move Truck" circuit to provide an alert when open.

At the rear of the hose bed, a black vinyl flap will be provided with seat belt buckles at the top. The seat belt buckles will be provided with a metal bar, to connect each set of two buckles, and attached to

a web strap, to allow a single pull release per set of two buckles. At the bottom of the flap, hinged style seat belt buckle will be provided. The bottom of the flap will be lead shot weighted.

If a strap is provided, the color of the strap will be black.

A cross-divider will be provided just behind the fill tower. The divider will be bolted to the side sheet.

RUNNING BOARDS

Running boards will be fabricated of 0.125" bright aluminum treadplate.

Each running board will be supported by a welded 2.00" square tubing and channel assembly, which will be bolted to the pump compartment substructure.

Running boards will be 12.75" deep and spaced 0.50" away from the pump panel.

A splash guard will be provided above the running board treadplate.

TAILBOARD

The tailboard will also be constructed of .125" bright aluminum treadplate and spaced .50" from the body, as well as supported by a structural steel assembly.

The tailboard area will be 16.00" deep.

The exterior side will be flanged down and in for increased rigidity of tailboard structure.

REAR WALL, SMOOTH ALUMINUM/BODY MATERIAL

The rear facing surfaces of the center rear wall will be smooth aluminum.

The bulkheads, the surface to the rear of the side body compartments, will be smooth and the same material as the body.

The center rear wall will be inset 16" from the body bulkhead rear walls.

Any inboard facing surfaces below the height of the hosebed will be aluminum diamondplate.

REAR TOW EYES

Two (2) tow eyes, which are an integral part of the body mounting substructure, will be installed below the rear of the truck.

The tow eyes will be of adequate strength to allow the truck to be pulled from the eyes.

REAR TOW BAR

One (1) tow bar will be installed under the tailboard.

The tow bar assembly will be designed and positioned to allow up to a 30-degree upward angled pull of 17,000 lb, or a 20,000 lb straight horizontal pull in line with the centerline of the vehicle.

The tow bar design will have been tested and evaluated using finite element analysis techniques.

RUNNING BOARD HOSE RESTRAINT

A pair of 2.00" wide black nylon straps with stainless steel seat belt buckle style latches will be provided for each hose tray to secure the hose during travel. There will be Two (2) hose trays located one (1) in each side running board.

HOSE TRAY

Two (2) hose trays will be made free floating one (1) in each side running board.

The tray(s) will be flanged and drop in from the top. No fasteners will be used to secure the tray(s).

Capacity of the tray will be 25' of 4".

Rubber matting will be installed on the floor of the tray to provide proper ventilation. Drain holes will be provided.

COMPARTMENTATION

Body and compartments will be fabricated of 0.125", 5052-H32 aluminum.

Side compartments will be an integral assembly with the rear fenders.

Circular fender liners will be provided for prevention of rust pockets and ease of maintenance.

Side compartment flooring will be of the sweep out design with the floor higher than the compartment door lip.

The side compartment door opening will be framed by flanging the edges in 1.75" and bending out again 0.75" to form an angle.

Drip protection will be provided above the doors by means of bright aluminum extrusion, formed bright aluminum treadplate or polished stainless steel.

The top of the compartment will be covered with bright aluminum treadplate rolled over the edges on the front, rear and outward side. These covers will have the corners welded.

Side compartment covers will be separate from the compartment tops.

Front facing compartment walls will be covered with bright aluminum treadplate.

All screws and bolts which protrude into a compartment will have acorn nuts on the ends to prevent injury.

UNDERBODY SUPPORT SYSTEM

Due to the severe loading requirements of this pumper a method of body and compartment support suitable for the intended load will be provided.

The backbone of the support system will be the chassis frame rails which is the strongest component of the chassis and is designed for sustaining maximum loads.

Forward to the rear axle, the support system will include "L"-shaped support members bolted to the chassis frame rails. These welded support members will include vertical formed channels, horizontal structural channels, and support gussets. These parts extend from the chassis frame outward underneath the body.

Rearward to the rear axle, the body support system will include two rearward facing "L"-shaped support members bolted to the chassis frame rails. These support members will be connected to the two body supporting crossmembers forming a boxed foundation for the rear body support system.

Steel upper platform decks will be mounted on the top of these support members to create a floating substructure which will result in a 500 lb equipment support rating per lower compartment.

All structural components of this system will be made from high strength 50K steel plate material or structural steel componentry. The steel frames as well as the steel vertical angles will be treated with an epoxy E-coat or equivalent to provide resistance to corrosion and chemicals as standard.

The floating substructure will be separated from the horizontal members with neoprene elastomer isolators. These isolators will reduce the natural flex stress of the chassis from being transmitted to the body.

Isolators will have a broad load range, proven viability in vehicular applications, be of a fail-safe design and allow for all necessary movement in three (3) transitional and rotational modes.

The neoprene isolators will be installed in a pattern which assimilates a three (3)-point mounting pattern to reduce the natural flex of the chassis being transmitted to the body.

A design with body compartments hanging on the chassis in an unsupported fashion will not be acceptable.

AGGRESSIVE WALKING SURFACE

All exterior surfaces designated as stepping, standing, and walking areas will comply with the required average slip resistance of the current NFPA standards.

LOUVERS

Louvers will be stamped into compartment walls to provide the proper airflow inside the body compartments and to prevent water from dripping into the compartment. Where these louvers are provided, they will be formed into the metal and not added to the compartment as a separate plate.

TESTING OF BODY DESIGN

Body structural analysis will be fully tested. Proven engineering and test techniques such as finite element analysis, strain gauging, and model analysis will be performed with special attention given to fatigue, life and structural integrity of the body and substructure.

Body will be tested while loaded to its greatest in-service weight.

The criteria used during the testing procedure will include:

- Raising opposite corners of the vehicle tires 9.00" to simulate the twisting a truck may experience when driving over a curb.
- Making a 90 degree turn, while driving at 20 mph to simulate aggressive driving conditions.
- Driving the vehicle at 35 mph on a washboard road.
- Driving the vehicle at 55 mph on a smooth road.
- Accelerating the vehicle fully, until reaching the approximate speed of 45 mph on rough pavement.

Evidence of actual testing techniques will be made available upon request.

LEFT SIDE COMPARTMENTATION

The left side compartmentation will consist of three rollup door compartments.

A full height, rollup door compartment ahead of the rear wheels will be provided. The interior dimensions of this compartment will be 27.50" wide x 66.63" high x 25.88" deep in the lower 25.00" of the compartment and 12.00" deep in the remaining upper portion. The clear door opening will be a minimum of 21.75" wide x 56.88" high.

A rollup door compartment over the rear wheels will be provided. The interior dimensions of this compartment will be 66.50" wide x 32.88" high x 12.00" deep. The clear door opening will be a minimum of 58.25" wide x 23.13" high.

A full height, rollup door compartment behind the rear wheels will be provided. The interior dimensions of this compartment will be 47.75" wide x 67.63" high x 25.88" deep in the lower 26.00" of height and 12.00" deep in the remaining upper section of the compartment. The clear door opening will be a minimum of 44.75" wide x 57.88" high.

The interior height of the compartments will be measured from the compartment floor to the ceiling. The spool of the rollup door at the top of the compartment takes up some usable space. The depth of the compartments will be measured from the back wall to the inside of the door frame.

Closing of the doors will not require releasing, unlocking, or unlatching any mechanism and will easily be accomplished with one hand.

RIGHT SIDE COMPARTMENTATION

The right side compartmentation will consist of three rollup door compartments.

A full height, rollup door compartment ahead of the rear wheels will be provided. The interior dimensions of this compartment will be 27.50" wide x 65.13" high x 25.88" deep. The clear door opening will be a minimum of 21.75" wide x 56.88" high.

A rollup door compartment over the rear wheels will be provided. The interior dimensions of this compartment will be 66.50" wide x 31.38" high x 25.88" deep. The clear door opening will be a minimum of 58.25" wide x 23.13" high.

A full height, rollup door compartment behind the rear wheels will be provided. The interior dimensions of this compartment will be 47.75" wide x 66.13" high x 25.88" deep. The clear door opening will be a minimum of 44.75" wide x 57.88" high.

The interior height of the compartments will be measured from the compartment floor to the ceiling. The spool of the rollup door at the top of the compartment takes up some usable space. The depth of the compartments will be measured from the back wall to the inside of the door frame.

Closing of the doors will not require releasing, unlocking, or unlatching any mechanism and will easily be accomplished with one hand.

SIDE COMPARTMENT ROLLUP DOOR(S)

There will be six (6) compartment doors installed on the side compartments. The doors will be double faced, aluminum construction, painted one (1) color to match the lower portion of the body and manufactured by R-O-M Corporation.

The slats will be double wall box frame extrusion. The exterior surface will be flat and the interior surface will be concave to help loose equipment fall to the ground and prevent it from jamming the door.

Between each slat will be a PVC inner seal to prevent metal to metal contact and prevent dirt or moisture from entering the compartments.

A lift bar with locking key latches to be provided for each roll-up door. The keys to be Model 1250 for all compartment doors. The lift bar will be located at the bottom of the door and have latches on the outer extrusion of the door frame. A ledge will be supplied over the lift bar as additional area to aid in closing the door.

Each door will have a 4.00" counter balance to assist in lifting.

A heavy-duty magnetic switch will be used for the control of open compartment door warning lights.

REAR COMPARTMENTATION

A vertically hinged, double door compartment above the rear tailboard will be provided.

The interior dimensions of this compartment will be 40.00" wide x 40.63" high x 25.88" deep. The interior height of the compartments will be measured from the compartment floor to the ceiling. The depth of the compartments will be measured from the back wall to the inside of the door frame.

A louvered, removable access panel will be furnished on the back wall of the compartment.

The rear compartment will be open into the rear side compartments.

The clear door opening of this compartment will be 32.00" wide x 35.88" high.

Closing of the door will not require releasing, unlocking, or unlatching any mechanism and will easily be accomplished with one hand.

Each of the vertically hinged compartment doors will be provided with a positive door holder.

REAR COMPARTMENT DOORS

All hinged compartment doors will be lap style with double panel construction and will be a minimum of 1.50" thick. To provide additional door strength, a "C" section reinforcement will be installed between the outer and interior panels.

Doors will be provided with a closed cell rubber gasket around the surface that laps onto the body. A second heavy-duty automotive rubber molding with a hollow core will be installed on the door framing that seals onto the interior panel, to ensure a weather resisting compartment.

All compartment doors will have polished stainless steel continuous hinge with a pin diameter of 0.25", that is bolted or screwed on with stainless steel fasteners. (Hinges which are welded on will not be acceptable.) A strip of dielectric isolation tape will be provided between the hinge and door jamb.

All door lock mechanisms will be fully enclosed within the door panels to prevent fouling of the lock in the event equipment inside shifts into the lock area.

Doors will be latched with recessed, polished stainless steel "D" ring handles and FMVSS approved door latching mechanisms.

To prevent corrosion caused by dissimilar metals, compartment door handles will not be attached to outer door panel with screws. A rubber gasket will be provided between the "D" ring handle and the door.

DOOR GUARD

There will be six (6) compartment doors that will include a guard/drip pan designed to protect the rollup door from damage when in the retracted position and contain any water spray. The guard will be fabricated from stainless steel and installed left side rearward compartment, left side over the wheel compartment, left side forward compartment, right side rearward compartment, right side over the wheel compartment and right side forward compartment.

ELECTRIC DOOR LOCKS

There will be six (6) door(s) located in the crew cab equipped with electric locks. The switch for control will be located all side body compartments. In the event of loss of power, a manual override is available.

ELECTRIC DOOR LOCKS

There will be one (1) door(s) located inside the crew cab equipped with electric locks. The locks will be wired battery direct. The switch for control will be located on the rear compartment door. In the event of loss of power, a manual override is available.

COMPARTMENT LIGHTING

There will be seven (7) compartments with Amdor, Model AY-9220, white 12 volt DC LED compartment light strips. The lights will be mounted with mechanical fasteners.

There will be two (2) strip lights installed vertically in each compartment opening per the latest NFPA requirements.

The lights will be activated when the battery switch is on and the respective compartment door is opened.

HATCH COMPARTMENT

One (1) hatch compartment will be provided above the right side compartments.

Each hatch compartment will extend the full length of the side body compartmentation x 27.75" wide. The height of each hatch compartment will match the side sheet height.

Sides of the compartment will be constructed of the same material as the body and painted job color. A 2.00" tall formed aluminum painted to match the lower body color will be provided to cover the seam between the top of the body panel and the bottom of the hatch compartment. The vertical outboard seam at the center of the compartment will be smooth weld finished and painted. The top of the compartment will be constructed of bright aluminum treadplate.

Two (2) lift-up, bright aluminum treadplate doors will be provided on the top of the compartment. Doors will have lipped edges with a rubber seal for weather resistance. Each door will have a socket and plunger type latch and chrome grab handle. Doors will be hinged on the outboard side and will utilize a gas strut (or rubber covered chain on narrow width doors)

Compartment will drain to an area below the hose bed. Black rubber matting shall be provided to help prevent stored equipment in pooled water.

HATCH COMPARTMENT

One (1) hatch compartment will be provided above the left side compartments.

Each hatch compartment will extend the full length of the side body compartmentation x 13.75" wide. The height of each hatch compartment will match the side sheet height.

Sides of the compartment will be constructed of the same material as the body and painted job color. A 2.00" tall formed aluminum painted to match the lower body color will be provided to cover the seam between the top of the body panel and the bottom of the hatch compartment. The vertical outboard seam at the center of the compartment will be smooth weld finished and painted. The top of the compartment will be constructed of bright aluminum treadplate.

Two (2) lift-up, bright aluminum treadplate doors will be provided on the top of the compartment. Doors will have lipped edges with a rubber seal for weather resistance. Each door will have a socket and plunger type latch and chrome grab handle. Doors will be hinged on the outboard side and will utilize a gas strut (or rubber covered chain on narrow width doors)

Compartment will drain to an area below the hose bed. Black rubber matting shall be provided to help prevent stored equipment in pooled water.

COMPARTMENT LIGHTING

There will be a 42.00" 12 volt DC strip light with white LEDs mounted on the interior, hinged side of each door. The lights will be mounted with mechanical fasteners.

The lights will be activated when the battery switch is on and the door is opened.

CARGO/DUNNAGE AREA LIGHTING

There will be two (2) Amdor®, Model AY-LB-12HW020, 20.00" 12 volt DC strip light(s) with white LEDs and 45 degree aluminum housing to illuminate the cargo area. The light(s) will be located, one forward and one rear in the cargo compartment.

The light will be activated when the battery switch is on and the body step lights are activated and when a cargo compartment door is opened.

MOUNTING TRACKS

There will be seven (7) sets of tracks for mounting shelf(s) in LS1, LS2, LS3, RS1, RS2, RS3 and B1. These tracks will be installed vertically to support the adjustable shelf(s). The tracks will be painted to match the compartment interior.

ADJUSTABLE SHELVES

There will be 15 shelves with a capacity of 500 lb provided.

The shelf construction will consist of .188" aluminum with a dual action finish with 2.00" sides.

Each shelf will be infinitely adjustable by means of a threaded fastener, which slides in a track.

The shelves will be held in place by .12" thick stamped plated brackets and bolts.

The location(s) will be determined at a later date.

SLIDE-OUT FLOOR MOUNTED TRAY

There will be two (2) floor mounted slide-out tray(s) provided.

Each tray will have 2.00" high sides and a minimum capacity rating of 500 lb in the extended position.

Each tray will be constructed of aluminum with a dual action finish.

There will be two undermount-roller bearing type slides rated at 250 lb each provided. The pair of slides will have a safety factor rating of 2.

To ensure years of dependable service, the slides will be coated with a finish that is tested to withstand a minimum of 1,000 hours of salt spray per ASTM B117.

To ensure years of easy operation, the slides will require no more than a 50lb force for push-in or pull-out movement when fully loaded after having been subjected to a 40 hour vibration (shaker) test under full load. The vibration drive file will have been generated from accelerometer data collected from a heavy truck chassis driven over rough gravel roads in an unloaded condition. Proof of compliance will be provided upon request.

Automatic locks will be provided for both the "in" and "out" positions. The trip mechanism for the locks will be located at the front of the tray for ease of use with a gloved hand.

The location(s) will be RS1 and LS1.

DRAWER ASSEMBLY

A slide-out drawer assembly will be installed in the LS3 compartment.

The clear dimensions starting at the top of the cabinet with the first drawer will be 3.00" with a face plate that is 4.00" high x 21.00" deep.

The clear dimensions of the second drawer will be 4.75" with a face plate that is 5.00" high x 21.00" deep.

The clear dimensions of the third drawer will be 4.75" with a face plate that is 5.00" high x 21.00" deep.

The clear dimensions of the fourth drawer will be 6.75" with a face plate that is 7.00" high x 21.00" deep.

Each drawer will be the same width and not exceed 24.00".

The drawers will have a capacity of 250 lb.

The drawers will be mounted in a cabinet housing constructed of light gray powder coated aluminum with anodized aluminum frames. The housing will be 24.00" deep, and completely enclose the drawer.

A full-length aluminum extruded rail will be provided at the top edge of each drawer. This rail will act as the latching mechanism as well as the handle for each drawer.

There will be a total of one (1) provided.

PARTITION, TRANSVERSE REAR COMPARTMENT

Two (2) partitions will be bolted in place to separate the left and right side rear compartments from the rear tailboard compartment. The partition will be body material painted spatter gray.

Each partition will be permanently sealed with caulk to ensure no water will leak to or from the adjoining compartments.

COMPARTMENT DUST FILTERS

A total of seven (7) body compartment louvers will have a removable dust filter installed to restrict road dirt from easily entering the compartment and will be installed All body compartments.

RUB RAIL

Bottom edge of the side compartments will be trimmed with a bright aluminum extruded rub rail.

Trim will be 2.12" high with 1.38" flanges turned outward for rigidity.

The rub rails will not be an integral part of the body construction, which allows replacement in the event of damage.

BODY FENDER CROWNS

Polished stainless steel fender crowns will be provided around the rear wheel openings with a dielectric barrier will be provided between the fender crown and the fender sheet metal to prevent corrosion.

The fender crowns will be held in place with stainless steel screws that thread directly into a composite nut and not directly into the parent body sheet metal to eliminate dissimilar metals contact and greatly reduce the chance for corrosion. Rubber welting will be provided between the body and crown.

BODY FENDER LINER

A unpainted brushed stainless fender liner will be provided. The liners will be removable to aid in the maintenance of rear suspension components.

HARD SUCTION HOSE

Hard suction hose will not be required.

HANDRAILS

The handrails will be 1.25" diameter knurled aluminum to provide a positive gripping surface.

Chrome plated end stanchions will support the handrail. Plastic gaskets will be used between end stanchions and any painted surfaces.

Drain holes will be provided in the bottom of all vertically mounted handrails.

Handrails will be provided to meet current edition of applicable NFPA standards. The handrails will be installed as noted on the sales drawing.

HANDRAILS

One (1) vertical handrail will be located on each rear beavertail.

HANDRAIL

One (1) full width horizontal knurled aluminum handrail will be provided below the hose bed at the rear of the apparatus.

ADDITIONAL HANDRAIL

Two (2) handrails will be mounted one each side on top of the rear of the body. The handrail(s) will be constructed of knurled aluminum.

EXTINGUISHER/AIR BOTTLE/ STORAGE (TRIANGULAR)

A total of one (1) extinguisher/air bottle/storage compartments will be provided on the right side rearward of the rear wheels. The triangular shaped compartment will be sized to fit a 8.00" diameter extinguisher in the lower area and a 8.00" diameter extinguisher in the upper area. The compartment will be approximately 25.50" deep. A partition will be provided to separate the compartment. Also inside the compartment, black Dura-Surf friction reducing material will be provided. The compartment will be furnished with a drain hole. A painted stainless steel, triangular shaped door with a flush Southco C2 chrome latch will be provided to contain the air bottles. A dielectric barrier will be provided between the door hinge, hinge fasteners and the body sheet metal.

AIR BOTTLE COMPARTMENT STRAP

A strap will be provided in the air bottle compartment(s) to help contain the bottles when the vehicle is parked on an incline. The strap will wrap around the neck and attach to the wall of the compartment.

AIR BOTTLE STORAGE (TRIPLE)

A quantity of one (1) air bottle compartment designed to hold (3) air bottles up to 7.25" in diameter x 26.00" deep will be provided on the left side forward of the rear wheels. A painted stainless steel door with a Southco raised trigger C2 chrome lever latch will be provided to contain the air bottle. A dielectric barrier will be provided between the door hinge, hinge fasteners and the body sheet metal.

Inside the compartment, black Dura-Surf friction reducing material will be provided.

Air Bottle Compartment Strap

A strap will be provided in the air bottle compartment(s) to help contain the air bottles when the vehicle is parked on an incline. The strap will wrap around the neck and attach to the wall of the compartment.

EXTINGUISHER STORAGE

There will be one (1) extinguisher compartment(s) provided on the left side rearward of the rear wheels. The extinguisher compartment(s) will be in the form of a 9.00" square tube and of adequate depth to accommodate different size extinguishers. A triangular shaped painted stainless steel door with a flush Southco C2 chrome latch will be provided to contain the extinguisher and fuel fill. A dielectric barrier will be provided between the door hinge, hinge fasteners, and the body sheet metal.

Inside the compartment, black Dura-Surf friction reducing material will be provided. There will also be a drain hole for each compartment.

EXTENSION LADDER

There will be a 24' two-section aluminum Duo-Safety Series 900-A extension ladder provided.

ROOF LADDER

There will be a 14' aluminum Duo-Safety Series 775-A roof ladder provided.

LADDER STORAGE

The ladders will be stored inside the upper section of the right side compartments. This ladder rack will reduce the depth of the upper section in the side compartments.

A partition will be installed inside the compartment on the side of the rack to allow for equipment storage and to conceal the ladders.

The ladders will be banked in separate storage troughs.

The ladder storage assembly will be fabricated of stainless steel track angles to aid in loading and removal of ladders.

Rear of the ladder storage area will have a vertically hinged door with lift-and-turn latches to contain the ladders.

FOLDING LADDER

One (1) 10.00' aluminum, Series 585-A, Duo-Safety folding ladder will be installed.

FOLDING LADDER STORAGE

There will be storage designated right side for folding ladders stored through the full depth body panel in a stainless steel trough in the ladder storage compartment.

PIKE POLE 8 FT

There will be one (1) Fire Hooks Unlimited NHF-8, 8 foot pike pole(s) with fiberglass handles provided.

PIKE POLE STORAGE

There will be storage designated on the right side for One (1) pike pole 8' or longer pike poles with a 0.75" standard notch, stored in a tube between the side sheet and tank in the ground ladder storage compartment.

6' PIKE POLE

There will be one (1) Fire Hooks Unlimited NHF-6, 6' pike pole(s) with fiberglass handles provided.

PIKE POLE STORAGE

There will be storage designated on the right side for Two (2) pike poles stored in a tube between the side sheet and tank in the folding ladder storage compartment. The tube(s) will have a 0.75" standard notch.

TRASH HOOK STORAGE

There will be one (1) stainless steel U-shaped trough(s) provided for storage of D-handle style trash hook(s). The trough(s) will be installed in the ladder storage compartment.

PIKE POLE STORAGE

Aluminum tubing will be used for the storage of four (4) pike poles and will be located in the ladder storage compartment. If the head of a pike pole can come in contact with a painted surface, a stainless steel scuffplate will be provided.

One (1) bright aluminum treadplate full width step will be provided above the rear compartment. The remaining steps will be bright aluminum treadplate corner steps. All rear steps will provide adequate surface for stepping and will be located in accordance to the current edition of applicable NFPA standards.

I-ZONE BRACKETS

Two (2) flip-out I-Zone brackets will be provided and mounted at the rear of the apparatus, on the rear body bulkheads. The brackets will be designed with adequate reinforcement to eliminate flexing of the body (oil canning).

PUMP COMPARTMENT

The pump compartment will be separate from the hose body and compartments so that each may flex independently of the other. The pump compartment will be constructed of the same material as the body compartmentation.

The pump compartment substructure will be a fabricated assembly of steel tubing, angles and channels which supports both the fire pump and the side running boards.

The pump compartment will be mounted on the chassis frame rails with rubber biscuits in a four point pattern to allow for chassis frame twist.

Pump compartment, pump, plumbing and gauge panels will be removable from the chassis in a single assembly.

PUMP MOUNTING

Pump will be mounted to a substructure which will be mounted to the chassis frame rail using rubber isolators. The mounting will allow chassis frame rails to flex independently without damage to the fire pump.

LEFT SIDE PUMP CONTROL PANEL

All pump controls and gauges will be located at the left (driver's) side of the apparatus and properly identified.

Layout of the pump control panel will be ergonomically efficient and systematically organized.

The pump operator's control panel will be removable in two (2) main sections for ease of maintenance:

The upper section will contain sub panels for the mounting of the pump pressure control device, engine monitoring gauges, electrical switches, and foam controls (if applicable). Sub panels will be removable from the face of the pump panel for ease of maintenance. Below the sub panels will be located all valve controls and line pressure gauges.

The lower section of the panel will contain all inlets, outlets, and drains.

All push/pull valve controls will have 1/4 turn locking control rods with polished chrome plated zinc tee handles. Guides for the push/pull control rods will be chrome plated zinc castings securely mounted to the pump panel. Push/pull valve controls will be capable of locking in any position. The control rods will pull straight out of the panel and will be equipped with universal joints to eliminate binding.

IDENTIFICATION TAGS

The identification tag for each valve control will be recessed in the face of the tee handle.

All discharge outlets will have color coded identification tags, with each discharge having its own unique color. Color coding will include the labeling of the outlet and the drain for each corresponding discharge.

All line pressure gauges will be mounted directly above the corresponding discharge control tee handles and recessed within the same chrome plated casting as the rod guide for quick identification. The gauge and rod guide casting will be removable from the face of the pump panel for ease of maintenance. The casting will be color coded to correspond with the discharge identification tag.

All remaining identification tags will be mounted on the pump panel in chrome plated bezels.

The pump panel on the right (passenger's) side will be removable with lift and turn type fasteners.

Trim rings will be installed around all inlets and outlets.

MIDSHIP FIRE PUMP

Midship fire pump will be a Hale QMAX-150, 1500 gpm single (1) stage midship mounted centrifugal type.

Pump will be the class "A" type.

Pump will deliver the percentage of rated discharges at the pressures indicated below:

- 100% of rated capacity at 150 psi net pump pressure.
- 100% of rated capacity at 165 psi net pump pressure.
- 70% of rated capacity at 200 psi net pump pressure.
- 50% of rated capacity at 250 psi net pump pressure.

Entire pump and both suction and discharge passages will be hydrostatically tested to a pressure of 500 psi.

Pump will be fully tested at the pump manufacturer's factory to the performance requirements as outlined by the current edition of applicable NFPA standards and will be free from objectionable pulsation and vibration.

Pump body and related parts will be of fine grain, alloy cast iron with a minimum tensile strength of 30,000 psi (2041.2 bar).

All moving parts in contact with water will be of high quality bronze or stainless steel.

Pump body will be horizontally split, on a single plane in two (2) sections, for easy removal of entire impeller assembly, including wear rings and bearings from beneath the pump, without disturbing pump piping or the mounting of the pump in the chassis.

Pump will have one (1) double suction impeller. The pump body will have two (2) opposed discharge volute cutwaters to eliminate radial unbalance.

Pump impeller will be hard, fine grain bronze of the mixed flow design, accurately machined, hand-ground, and individually balanced. The vanes of the impeller intake eyes will be hand-ground and polished to a sharp edge. They will be of sufficient size and design to provide ample reserve capacity utilizing minimum horsepower.

Impeller clearance rings will be bronze and easily renewable without replacing impeller or pump volute body. They will be of the wrap-around double labyrinth design for maximum efficiency. Pump shaft will be electric furnace heat-treated, corrosion resistant stainless steel. It will be super-finished under packing with galvanic corrosion (zinc separators in packing) protection for longer shaft life. Pump shaft will be sealed with double oil seal to keep road dirt and water out of drive unit.

Pump shaft will be rigidly supported by three (3) bearings for minimum deflection. A high lead bronze sleeve bearing will be located immediately adjacent to the impeller (on the side opposite of the drive unit). The sleeve bearing will be automatically oil lubricated and pressure balanced to exclude foreign

material. The remaining bearings will be heavy-duty, deep groove ball bearings in the gearbox and will be splash lubricated.

MECHANICAL SEAL ON PUMP

Only one (1) mechanical seal will be used on the suction (inboard) side of the pump. The mechanical seal will be 2.00" in diameter and will be spring loaded, maintenance-free, and self-adjusting.

The mechanical seal construction will be a carbon sealing ring, stainless steel coil spring, Viton® rubber boot, and a tungsten carbide seat with a Teflon backup seal.

PUMP TRANSMISSION

The drive unit will be cast and completely manufactured and tested at the Hale Products, Inc. factory. The pump drive unit will be of sufficient size to withstand up to 16,000 foot/ pounds of torque from the engine in both the road and pump operating conditions. The drive unit is will be designed with ample lubrication reserve to maintain the proper operating temperature.

The gearbox drive shafts will be of heat treated chrome nickel steel and 2.75" in diameter on both the input and output drive shafts. They will be designed to withstand the full torque of the engine in both road and pump operating conditions.

All gears, both drive and pump, will be of the highest quality, electric furnace, chrome nickel steel. Bores will be ground to size and teeth integrated, crown-shaved and hardened, to give an extremely accurate gear for long life, smooth, quiet running and higher load carrying capability. An accurately cut spur design will be provided to eliminate all possible end thrust.

Pierce Manufacturing will select the pump ratio to provide the maximum performance with the engine and transmission selected. Three (3) green warning lights will be provided to indicate to the operator(s) when the pump has completed the shift from Road to Pump position. Two (2) lights will be located in the truck driving compartment and one (1) light on pump operator's panel adjacent to the throttle control.

PUMPING MODE

An interlock system will be provided to ensure that the pump drive system components are properly engaged so that the apparatus can be safely operated. The interlock system will be designed to allow stationary pumping only.

AIR PUMP SHIFT

Pump shift engagement will be made by a two (2) position sliding collar, actuated pneumatically (by air pressure), with a three (3) position air control switch located in the cab.

Two (2) indicator lights will be provided adjacent to the pump shift inside the cab. One (1) green light will indicate the pump shift has been completed and be labeled "pump engaged". The second green light will indicate when the pump has been engaged and the chassis transmission is in pump gear. This indicator light will be labeled "OK to pump".

The pump shift will be interlocked to prevent the pump from being shifted out of gear when the chassis transmission is in gear to meet NFPA requirements.

The pump shift control in the cab will be illuminated to meet NFPA requirements.

TRANSMISSION LOCK-UP

The direct gear transmission lock-up for the fire pump operation will engage automatically when the pump shift control in the cab is activated.

AUXILIARY COOLING SYSTEM

A supplementary heat exchange cooling system will be provided to allow the use of water from the discharge side of the pump for cooling the engine water. The heat exchanger will be a separate unit. It will be installed in the pump or engine compartment with the control located on the pump operator's control panel. The exchanger will be plumbed to the master drain valve.

INTAKE RELIEF VALVE - PUMP

One (1) Elkhart Style 40 relief valve(s) will be installed on the suction side of the pump preset at 200 psig.

The relief valve(s) will have a working range of 75 psi to 250 psi.

The outlet will terminate below the frame rails with a 2.50" National Standard hose thread adapter and will have a "do not cap" warning tag.

The relief valve pressure control will be located behind the right side pump panel with a stainless steel access door.

PRESSURE CONTROLLER

A FRC Pump Boss 500 electronic pressure controller with one (1) 600 PSI transducer on the pump discharge will be provided. All readouts will be standard PSI.

When a single 300 psi or single 600 psi pressure transducer is selected the transducer is installed in the discharge side of the water pump. The transducer continuously monitors pump pressure sending a signal to the electronic pressure controller.

When a dual 600 psi pressure transducer is selected the transducer are installed in the discharge side and intake side of the water pump. The discharge transducer continuously monitors pump pressure sending a signal to the electronic pressure controller. The intake transducer continuously monitors the pump intake sending a signal to the electronic pressure controller.

The pressure controller can be used in two (2) modes of operation, RPM mode and pressure modes. The controller will be programmed to turn on/default to RPM Setting mode.

In RPM mode, the controller can be activated after vehicle parking brake has been set. When in this mode, the controller will maintain the set engine speed, regardless of engine load (within engine operation capabilities).

In pressure mode, the controller can be activated after vehicle parking brake has been set. When in this mode, the controller will automatically maintain the discharge pressure set by the operator (within the discharge capabilities of the pump and water supply) regardless of flow.

A 2.00" diameter throttle control knob with no mechanical stops, a serrated grip, and a red idle push button in the center will be a integrated/part of the pressure controller. The throttle control knob will be programmed for Clockwise rotation to increase engine speed.

Individual LED indicators for ok to pump, throttle ready, pressure mode and rpm mode will be located on the pressure controller for easy viewing.

Safety features include recognition of low water and no water conditions with an automatic programmed response and a push button to return the engine to idle.

An additional audible alarm will NOT BE provided.

The pressure controller screen will be LCD. The LCD screen and LED intensity will be automatically adjust for day and nighttime operation. The LCD screen intensity can also be manually adjusted if needed.

The following information will be provided/displayed on the LCD screen:

- Engine RPM
- Check engine and stop engine warning indicators
- Engine oil pressure
- Engine coolant temperature
- Transmission Temp
- Battery voltage
- Operating mode (RPM or pressure)
- Pressure or RPM setting

On screen messaging show diagnostic and warning messages as they occur. It will show apparatus information, stored data, and program options when selected by the operator. It will monitor inputs outputs and support audible and visual warning alarms for the following conditions:

- High battery voltage
- Low battery voltage/engine off
- Low battery voltage/engine running
- High water pump temperature
- Low engine oil pressure
- High engine coolant temperature
- No engine response (visual alarm only)

The pressure controller will store the accumulated operating hours for the pump and engine. These items are to be displayed within the pressure controller menu.

The pressure controller will include a USB port on the back of the controller for easy software upgrades if needed.

PRIMING PUMP

The priming pump will be a Trident Emergency Products compressed air powered, high efficiency, multistage venturi based AirPrime System, conforming to standards outlined in the current edition of applicable NFPA standards.

All wetted metallic parts of the priming system are to be of brass and stainless steel construction.

One (1) priming control will open the priming valve and start the pump primer.

PUMP DRAIN

A Class 1 multi port pump drain will be used in place of the standard pump drain.

RECIRCULATING LINE WITH CHECK VALVE

A 0.375" diameter recirculating line, from the pump to the water tank, will be furnished with a control installed at the pump operator's control panel. A check valve will be provided in this line to prevent the back flow of water from the tank to the pump if the valve is left in the open position.

THERMAL RELIEF VALVE

A Hale TRV170-L thermal protection device will be included on the pump that monitors pump water temperature and opens to relieve water to cool the pump when the temperature of the pump water exceeds 170 Degrees F (77 C).

The thermal protection device will include a red warning light and audible alarm. The warning light with a test switch will be mounted on the pump operator panel.

The discharge line will be 3/8 inch diameter tubing plumbed to ground.

PUMP MANUALS

There will be a total of two (2) pump manuals provided by the pump manufacturer and furnished with the apparatus. The manuals will be provided by the pump manufacturer in the form of two (2) electronic copies. Each manual will cover pump operation, maintenance, and parts.

PLUMBING, STAINLESS STEEL AND HOSE

All inlet and outlet lines will be plumbed with either stainless steel pipe, flexible polypropylene tubing or synthetic rubber hose reinforced with hi-tensile polyester braid. All hose's will be equipped with brass or stainless steel couplings. All stainless steel hard plumbing will be a minimum of a schedule 10 wall thickness.

Where vibration or chassis flexing may damage or loosen piping or where a coupling is required for servicing, the piping will be equipped with victaulic or rubber couplings.

Plumbing manifold bodies will be ductile cast iron or stainless steel.

All piping lines are to be drained through a master drain valve or will be equipped with individual drain valves. All drain lines will be extended with a hose to drain below the chassis frame.

All water carrying gauge lines will be of flexible polypropylene tubing.

All piping, hose and fittings will have a minimum of a 500 PSI hydrodynamic pressure rating.

FOAM SYSTEM PLUMBING

All piping that is in contact with the foam concentrate or foam/water solution will be stainless steel. The fittings will be stainless steel or brass. Cast iron pump manifolds will be allowed.

MAIN PUMP INLETS

A 6.00" pump manifold inlet will be provided on each side of the vehicle. The suction inlets will include removable die cast zinc screens that are designed to provide cathodic protection for the pump, thus reducing corrosion in the pump.

SHORT SUCTION TUBE(S)

The suction tube(s) on the water pump will have short suction tube(s) installed to allow for installation of adapters, elbows or intake valves without excessive overhang.

MAIN PUMP INLET CAP PROVIDED BY FIRE DEPARTMENT

NFPA 1900, 2024 edition, section 13.6.8 and CAN/ULC S515:2024 edition, section 5.2, requires all intakes to be provided with caps or closures capable of withstanding a hydrostatic gauge pressure of 500 psi (3400 kPa).

The caps are not on the apparatus as manufactured. The fire department will provide both caps for the main pump inlets.

VALVES

All ball valves will be Akron® Brass. The Akron valves will be the 8000 series heavy-duty style with a stainless steel ball and a simple two-seat design. No lubrication or regular maintenance is required on the valve.

Valves will have a **ten (10) year** warranty.

The location of the valve for the one (1) inlet will be recessed behind the pump panel.

INLET CONTROL

The side auxiliary inlet(s) will incorporate a quarter-turn ball valve with the control located at the inlet valve. The valve operating mechanism will indicate the position of the valve.

LEFT SIDE INLET

There will be one (1) auxiliary inlet with a 2.50" valve at the left side pump panel, terminating with a 2.50" (F) National Standard hose thread adapter.

The auxiliary inlet will be provided with a strainer, chrome swivel and plug.

ANODE, INLET

A pair of sacrificial zinc anodes will be provided in the water pump inlets to protect the pump from corrosion.

INLET BLEEDER VALVE

A 0.75" bleeder valve will be provided for each side gated inlet.

The valves will be located behind the panel with a "T" swing style handle control extended to the outside of the panel.

The handles will be chrome plated and provide a visual indication of valve position. The swing handle will provide an ergonomic position for operating the valve without twisting the wrist and provides excellent leverage.

The water discharged by the bleeders will be routed below the chassis frame rails.

TANK TO PUMP

The booster tank will be connected to the intake side of the pump with 4.00" heavy duty piping and a quarter turn 3.00" full flow line valve with the control remotely located at the operator's panel. Tank to pump line will run straight (no elbows) from the pump into the front face of the water tank and angle down into the tank sump. A rubber coupling will be included in this line to prevent damage from vibration or chassis flexing.

The control on the pump panel will be "in" when the valve is open and "out" when the valve is closed.

A check valve will be provided in the tank to pump supply line to prevent the possibility of "back filling" the water tank.

TANK REFILL

A 2.00" combination tank refill and pump re-circulation line will be provided, using a quarter-turn full flow ball valve controlled from the pump operator's panel.

DISCHARGE OUTLET CONTROLS

The discharge outlets will incorporate a quarter-turn ball valve with the control located at the pump operator's panel. The valve operating mechanism will indicate the position of the valve.

If a handwheel control valve is used, the control will be a minimum of a 3.9" diameter stainless steel handwheel with a dial position indicator built into the center of the handwheel.

Any 3.00 inch or larger discharge valve will be a slow-operating valve in accordance with NFPA 1900 2024 Edition 13.7.5.3.

LEFT SIDE DISCHARGE OUTLETS

There will be Two (2) discharge outlets with a 2.50" valve on the left side of the apparatus, controlled by an Akron locking horizontal swing style control, terminating with a 2.50" (M) National Standard hose thread adapter. The controls will be Akron SZ handles

LEFT SIDE OUTLET ELBOWS

The 2.50" discharge outlets, located on the left side pump panel, will be furnished with a 2.50" (F) National Standard hose thread x 2.50" (M) National Standard hose thread, chrome plated, 30 degree elbow.

The elbow will be Pierce VLH, which incorporates an exclusive thread design to automatically relieve stored pressure in the line when disconnected.

RIGHT SIDE DISCHARGE OUTLETS

There will be One (1) discharge outlet with a 2.50" valve on the right side of the apparatus, terminating with a 2.50" (M) National Standard hose thread adapter. The valve will be controlled by a SZ swing handle control located at the pump operators panel.

RIGHT SIDE OUTLET ELBOWS

The 2.50" discharge outlets located on the right side pump panel will be furnished with a 2.50" (F) National Standard hose thread x 2.50" (M) National Standard hose thread, chrome plated, 45 degree elbow.

The elbow will be Pierce VLH, which incorporates an exclusive thread design to automatically relieve stored pressure in the line when disconnected.

LARGE DIAMETER DISCHARGE OUTLET

There will be an Akron 8800 4.00" flat ball valve with 4.00" plumbing terminating with a 4.00" MNST chrome adapter on the right side pump panel.

The valve will be controlled with a(n) Akron 9345 with pressure and flow located at the pump operator's panel.

LARGE DIAMETER OUTLET ELBOWS

The 4.00" outlet will be furnished with a 4.00" (F) National Standard hose thread x 4.00" (M) National Standard 30 degree chrome elbow adapter with a long handle cap.

FRONT DISCHARGE OUTLET

There will be one (1) 1.50" discharge outlet piped to the front of the apparatus and located in the center bumper tray.

Plumbing will consist of 2.00" piping and flexible hose with a 2.00" ball valve with control at the pump operator's panel. A fabricated weldment made of stainless steel pipe will be used in the plumbing where appropriate. The piping will terminate with a 1.50" NST with 90 degree stainless steel swivel.

There will be automatic drains provided at all low points of the piping.

REAR DISCHARGE OUTLET

There will be One (1) discharge outlet piped to the rear of the hose bed, left side, installed so proper clearance is provided for spanner wrenches or adapters. Plumbing will consist of 2.50" piping along with a 2.50" full flow ball valve with the control from the pump operator's panel.

REAR OUTLET ELBOWS

The 2.50" discharge outlets, located at the rear of the apparatus, will be furnished with a 2.50" (F) National Standard hose thread x 2.50" (M) National Standard hose thread, chrome plated, 30 degree elbow.

The elbow will be Pierce VLH, which incorporates an exclusive thread design to automatically relieve stored pressure in the line when disconnected.

DISCHARGE CAPS/ INLET PLUGS

Chrome plated, rocker lug, caps with S/S cables will be furnished for all discharge outlets 1.00" thru 3.00" in size, besides the pre-connected hose outlets.

Chrome plated, rocker lug, plugs with S/S cables will be furnished for all auxiliary inlets 1.00" thru 3.00" in size.

The caps and plugs will incorporate a thread design to automatically relieve stored pressure in the line when disconnected.

OUTLET BLEEDER VALVE

A 0.75" bleeder valve will be provided for each outlet 1.50" or larger. Automatic drain valves are acceptable with some outlets if deemed appropriate with the application.

The valves will be located behind the panel with a T swing style handle control extended to the outside of the side pump panel.

The handles will be chrome plated and provide a visual indication of valve position.

The T swing handle will provide an ergonomic position for operating the valve without twisting the wrist and provides excellent leverage.

Bleeders will be located at the bottom of the pump panel. They will be properly labeled identifying the discharge they are plumbed in to.

The water discharged by the bleeders will be routed below the chassis frame rails.

ADAPTER

There will be three (3) adapters with 2.50" Female NST x 2.50" Male NST thread.

There will be one (1) adapter with 4.00" FNST x 2.50" FNST rocker lug swivel installed on the large diameter outlet. The design will be an anodized aluminum with smooth tapered smooth reducer.

DELUGE RISER

A 3.00" deluge riser will be installed above the pump in such a manner that a monitor can be mounted and used effectively. Piping will be installed securely so no movement develops when the line is charged. The riser will be gated with an electrically actuated 3.00" valve and controlled from pump operators panel.

There will be an Akron 9333 electric valve controller provided on the pump operators panel. The electric control must be of a true position feedback design, requiring no clutches in the motor or current limiting. The unit must be completely sealed with momentary open, close as well and an optional one touch full open feature to operate the valve actuator. The controller will provide position indication on a full color, backlit LCD display. It will have manual adjustment of the brightness as well as an auto dimming option.

MONITOR

A customer/dealer supplied and installed make and model Akron 3431 monitor will be properly installed on the deluge riser.

The deluge riser will have male National Pipe Threads for mounting the monitor.

CROSSLAY HOSE BEDS, 1.50"

Two (2) crosslays with 1.50" outlets will be provided. Each bed to be capable of carrying Crosslay beds to be 7.5" wide and will be plumbed with 2.00" i.d. pipe and gated with a 2.00" quarter turn ball valve.

Outlets to be equipped with a 1.50" National Standard hose thread 90 degree swivel located in the hose bed so that hose may be removed from either side of apparatus.

The crosslay controls will be at the pump operator's panel.

The center crosslay dividers will be fabricated of .25" aluminum and will provide adjustment from side to side. The divider will be unpainted with a brushed finish.

Vertical scuffplates, constructed of polished stainless steel, will be provided at the front and rear ends of the bed on each side of vehicle.

Crosslay bed flooring will consist of removable perforated brushed aluminum.

DEADLAY HOSE BEDS

One (1) deadlay bed, without plumbing, will be provided above the pump compartment capable of carrying 300' of 1.75", bed to be 7.5" wide.

The center crosslay dividers will be fabricated of .25" aluminum and will provide adjustment from side to side. The divider will be unpainted with a DA finish. The remainder of the crosslay bed will be painted job color.

Polished stainless steel vertical scuffplates will be provided at hose bed ends (each side of vehicle). Bottom of hose bed ends (each side) will also be equipped with a polished stainless steel scuffplate.

Deadlay bed flooring will consist of removable perforated brushed aluminum.

CROSSLAY/DEADLAY HOSE RESTRAINT

A black vinyl cover restraint will be provided across the ends of crosslay(s)/deadlay(s) to secure the hose during travel. A webbing assembly is to be used to attached the vinyl cover at the bottom of the crosslay(s)/deadlay(s) with footman loops as a permanent attachment and is attached at the top outside corners with two (2) seat belt buckles. The female end is permanently attached above the crosslay(s)/deadlay(s) and the male end attached to the webbing.

There will be a metal bar, to connect the buckles, and an attached web strap, to allow a single pull release.

The color of the release strap will be black.

CROSSLAY COVER

A hinged .19" aluminum treadplate cover will be installed over the crosslay hose beds. It will include a latch at each end of the cover to hold it securely in place, a chrome grab handle at each end for opening and closing the cover and a foam rubber gasket where the cover comes into contact to a painted surface.

The cover will be provided with rubber latch hold open device.

The hinge will be to the front of the hose beds.

CROSSLAY 8.00" LOWER THAN STANDARD

The crosslays will be lowered 8.00" from standard.

BOOSTER HOSE REEL

A Hannay electric rewind booster hose reel will be installed over the pump in a recessed open compartment on the left side of the apparatus. Reel will be fabricated of aluminum and have highly polished end discs.

A polished stainless steel roller and guide assembly will be mounted on the reel side of the apparatus.

Discharge control will be provided at the pump operator's panel. Plumbing to the reel will consist of 1.50" Aeroquip hose and a 1.50" valve.

Reel motor will be protected from overload with a circuit breaker rated to match the motor.

Electric rewind controls will be a rubber covered button. Locate one adjacent to the reel, and one on each pump panel.

Booster hose, 1.00" diameter and 150 feet, with chrome plated Barway, or equal couplings will be provided.

Working pressure of the booster hose will be a minimum of 800 psi.

Capacity of the hose reel will be 150 feet of 1.00" booster hose.

PRESSURE GAUGE

There will be a pressure gauge provided for one (1) hose reel(s). The gauge will be located above the control handle. The gauge will match the discharge outlet gauges.

There will be one (1) additional polished stainless steel roller and guide assembly mounted over the passenger side dunnage area.

FOAM CONCENTRATE PROPORTIONING SYSTEM

A Hypro FoamPro®, Model 2001, foam system will be provided as the means for the proportioning of foam concentrate into the water stream. The FoamPro is an electronic, fully automatic, variable speed, direct injection, discharge side foam proportioning system.

This system will be capable of handling Class A foam concentrates, as well as most Class B foam concentrates.

The foam system will be plumbed to five (5) discharges. The discharges capable of dispensing foam will be both crosslays, rear discharge, hose reel and front discharge.

The foam proportioning system operation will be based on a direct measurement of water flows, and remain consistent within the specified flow and pressure. The system will be equipped with a digital electronic control display on the pump panel. Incorporated within the control display will be a microprocessor, which receives input from the system flow meter while also monitoring the foam concentrate pump output. The microprocessor will compare the values of the water flow versus the foam flow, to ensure the proportion rate is accurate.

One (1) paddle wheel will be installed to monitor all foam discharges.

Push button control for the foam proportioning rate will allow a ratio from .1 percent to 3 percent in .1 percent increments.

The rated capacity of this system will be 85 gpm at 3 percent and 500 gpm at .5 percent.

A 2.5 gpm @150 psi, positive displacement foam pump will be powered by a 1/2 hp 12 vdc electric motor.

One (1) check valve will be installed in the plumbing to prevent foam from contaminating the water pump. The check valve will be approved by the foam system manufacturer.

FOAM TANK

The foam tank will be an integral portion of the polypropylene water tank. The cell will have a capacity of 25 gallons of foam with the intended use of Class A foam. The foam cell will not reduce the capacity of the water tank. The foam cell will have a screen in the fill dome and a breather in the lid.

FOAM TANK DRAIN

The foam tank drain will be a 1.00" drain valve located inside the pump compartment accessible through a door on the right side pump panel.

PUMP PANEL CONFIGURATION

The pump panel configuration will be arranged and installed in an organized manner that will provide user-friendly operation.

PUMP AND GAUGE PANEL

The pump and gauge panels will be constructed of stainless steel with a brushed finish. A polished aluminum trim molding will be provided on both sides of the pump panel.

PUMP ACCESS

Right Side Panel

The right side pump panel will be hinged along the forward edge.

Panel Fastener

The right side hinged panel will be secured using a chrome flush trigger latch.

The right side lower (drain bank) and all left side panel will be secured using screws.

PUMP COMPARTMENT LIGHT

There will be one (1) Whelen®, Model 3SC0CDCR, 3.00" white 12 volt DC LED light(s) with Whelen, Model 3FLANGEC, flange(s) installed in the pump compartment.

PUMP PANEL GAUGES AND CONTROLS

The following will be provided on the pump panels in the FRC IN Control Pressure Governor system:

- Engine Oil Pressure Gauge: LED bar graph display
- Engine Water Temperature Gauge: LED bar graph display
- Tachometer: Over 0.50" high LED digits
- Master Pump Drain Control
- Voltmeter: LED bar graph display

THROTTLE READY GREEN INDICATOR LIGHT

There will be a green indicator light integrated with the pressure governor and/or engine throttle installed on the pump operators panel that is activated when the pump is in throttle ready mode.

OK TO PUMP INDICATOR LIGHT

There will be a green indicator light installed on the pump operators panel that is activated when the pump is in Ok To Pump mode.

FUEL GAUGE

A fuel gauge will be provided.

AIR HORN BUTTON

An air horn control button will be provided at the pump operator's control panel. This button will be red in color and properly labeled and put within easy reach of the operator.

PUMP HOUSE - FRONT PANEL

The front of the pump house will be covered with a 4-way aluminum treadplate panel. This panel will provide an enclosure that extends down the front edge of the pump house to the skirt level. This panel will assist in reducing road debris from entering into the pump house compartment.

VACUUM AND PRESSURE GAUGES

The pump vacuum and pressure gauges will be silicone filled and manufactured by Class 1 Incorporate ©.

The gauges will be a minimum of 4.50" in diameter and will have white faces with black markings.

The pump pressure gauge will have a pressure range of 0-40bar. The vacuum gauge will have a range of -1 -0-40 bar.

The pump pressure and vacuum gauges will be installed adjacent to each other at the pump operator's control panel.

Test port connections will be provided at the pump operator's panel. One (1) will be connected to the intake side of the pump, and the other to the discharge manifold of the pump. They will have 0.25 in. standard pipe thread connections and polished stainless steel plugs. They will be marked with a label.

PRESSURE GAUGES

The individual "line" pressure gauges for the discharges will be Class 1 interlube filled.

They will be a minimum of 2.00" in diameter and have white faces with black lettering.

Gauge construction will include a Zytel nylon case with adhesive mounting gasket and threaded retaining nut.

Gauges will have a pressure range of 30"-0-400#.

The individual pressure gauge will be installed as close to the outlet control as practical.

This gauge will include a 10 year warranty against leakage, pointer defect, and defective bourdon tube.

WATER LEVEL GAUGE

A Fire Research TankVision Pro model WLA300-A00 water tank indicator gauge will be installed on the pump operator's panel. The gauge kit will include an electronic indicator module, a pressure sensor, and a 10' sensor cable. The gauge will show the volume of water in the tank on nine (9) easy to see super bright RGB LEDs. A wide view lens over the LEDs will provide for a viewing angle of 180 degrees. The gauge case will be waterproof, manufactured of Polycarbonate/Nylon material, and have a distinctive blue label.

The program features will be accessed from the front of the indicator module. The program will support self-diagnostics capabilities, self-calibration, six (6) programmable colored light patterns to display tank volume, adjustable brightness control levels and a data link to connect remote indicators. Low water warnings will include flashing LEDs at 1/4 tank and down chasing LEDs when the tank is almost empty.

The gauge will receive an input signal from an electronic pressure sensor. The sensor will be mounted from the outside of the water tank near the bottom. No probe will be placed on the interior of the tank. Wiring will be weather resistant and have automotive type plug-in connectors.

ADDITIONAL WATER LEVEL GAUGE(S)

There will be one (1) Fire Research TankVision Pro model WLA300-B00 water tank remote indicator kit(s) installed at the rear of the apparatus. The kit(s) will include an electronic indicator module and a 10' remote cable. The indicator(s) will show the volume of water in the tank on nine (9) easy to see super bright RGB LEDs. A wide view lens over the LEDs will provide for a viewing angle of 180 degrees. The indicator case will be waterproof, manufactured of Polycarbonate/Nylon material, and have a distinctive blue label.

The remote indicator(s) will receive input information over a data link from the primary Fire Research TankVision indicator. A 10' cable will be provided to connect the data link. The remote indicator(s) will have the same program as the primary so that the two indicators are interchangeable.

The flash rate will be determined by the main water tank sensor.

CLASS "A" FOAM LEVEL GAUGE

A Fire Research TankVision Pro, Model WLA360-A00, cell/tank level indicator kit will be installed on the pump operator's panel. The kit will include an electronic indicator module, a pressure sensor, a 10'

sensor cable and a tank vent. The indicator will show the volume of Class "A" foam concentrate in the cell/tank on nine (9) easy to see super bright RGB LEDs. A wide view lens over the LEDs will provide for a viewing angle of 180 degrees. The indicator case will be waterproof, manufactured of Polycarbonate/Nylon material and have a distinctive green label.

The program features will be accessed from the front of the indicator module. The program will support self-diagnostics capabilities, self-calibration, six (6) programmable colored light patterns to display cell/tank volume, adjustable brightness control levels and a data link to connect remote indicators. Low foam level warnings will include flashing LEDs at 1/4 cell/tank and down chasing LEDs when the cell/tank is almost empty.

The indicator will receive an input signal from an electronic pressure sensor. The sensor will be mounted from the outside of the foam cell/tank near the bottom. No probe will be placed on the interior of the cell/tank. Wiring will be weather resistant and have automotive type plug-in connectors.

LIGHT SHIELD

There will be a polished, 16 gauge stainless steel light shield installed over the pump operators panel.

- There will be four (4) Fire Research, Firefly part number LED115-Q01, 12 volt DC white LED lights installed under the stainless steel light shield to illuminate the controls, switches, essential instructions, gauges, and instruments necessary for the operation of the apparatus. These lights will be activated by the pump panel light switch. Additional lights will be included every 18.00" depending on the size of the pump house.
- One (1) pump panel light will come on when the pump is in ok to pump mode. The remaining lights to be actuated from a switch located on the pump panel.

The switch panel will be lit when the parking brake is set. This is to afford the operator illumination when first approaching the control panel.

ADDITIONAL LIGHT SHIELD

An additional polished, 16 gauge stainless steel light shield will be provided above passenger's side pump panel.

- There will be four (4) Fire Research Firefly, Model 115-Q01, white LED lights installed under the light shield to illuminate the controls, switches, essential instructions, gauges, and instruments necessary for the operation of the apparatus. The lights will be operated from a switch on the pump panel. Additional lights will be included every 18.00" depending on the size of the pump house.

AIR HORN SYSTEM

One (1) Hadley round air horn with 6.00" bell will be recessed in the front bumper. The air horn system will be piped to the air brake system wet tank utilizing 0.38" tubing. A pressure protection valve will be installed to prevent the loss of air in the brake system.

Air Horn Location

The air horn will be located on the right side of the bumper, just outside of the frame rail.

Air Horn Control

The air horn(s) will be activated by the following:

- Right side foot switch
- Steering wheel horn ring with electric/air horn selector switch

ELECTRONIC SIREN

A Whelen, Model 295HFS2, electronic remote siren with noise canceling microphone will be provided.

This siren to be active when the battery switch is on and that emergency master switch is on.

Electronic siren head will be recessed in the driver side center switch panel.

The electronic siren will be controlled on the siren head only. No horn button or foot switches will be provided.

SPEAKER

There will be one (1) Whelen®, Model SA315P, black nylon composite, 100-watt, speaker with through bumper mounting brackets and polished stainless steel grille provided. The speaker will be connected to the siren amplifier.

The speaker will be recessed in the right side of the front bumper, towards the outside.

AUXILIARY MECHANICAL SIREN

There will be a Federal Signal Model Q2B mechanical siren furnished and installed in the front of the apparatus.

The Q2B will be chrome finish.

The siren will have a 2-gauge cable connected to a power solenoid that is connected by a 2-gauge cable ran battery direct to the primary chassis batteries and will be labeled Q2B+ at the battery. The power solenoid will only be enabled when the emergency master switch is on.

The siren will have a 2-gauge ground wire connected to the chassis battery stud. The cable will be labeled Q2B- at the battery.

The mechanical siren will be recessed in the front bumper on the left side. The siren will be properly supported using the bumper framework.

MECHANICAL SIREN CONTROL

The mechanical siren will be activated by the following:

Driver side cab switch will activate the mechanical siren for seven (7) seconds and then deactivate it for (10) seconds. This on/off cycling to remain until the driver side cab switch is engaged a second time.

- Left side foot switch.
- Right side foot switch

A momentary chrome push button switch will be included in the left side dash panel to activate the siren brake.

A momentary chrome push button switch will be included in the right side dash panel to activate the siren brake.

FRONT ZONE UPPER WARNING LIGHTS

There will be one (1) 81.00" Whelen Freedom IV LED lightbar mounted on the cab roof.

The lightbar will include the following:

- One (1) red flashing LED module in the driver's side end position.
- One (1) red flashing LED module in the driver's side front corner position.
- One (1) red flashing LED module in the driver's side first front position.
- One (1) red flashing LED module in the driver's side second front position.
- One (1) white flashing LED module in the driver's side third front position.
- One (1) red flashing LED module in the driver's side fourth front position.
- One (1) red flashing LED module in the driver's side fifth front position.
- One (1) red flashing LED module in the driver's side sixth front position.
- One (1) 795 LED traffic light controller set to national standard high priority in the center positions.
- One (1) red flashing LED module in the passenger's side sixth front position.
- One (1) red flashing LED module in the passenger's side fifth front position.
- One (1) red flashing LED module in the passenger's side fourth front position.
- One (1) white flashing LED module in the passenger's side third front position.
- One (1) red flashing LED module in the passenger's side second front position.
- One (1) red flashing LED module in the passenger's side first front position.
- One (1) red flashing LED module in the passenger's side front corner position.
- One (1) red flashing LED module in the passenger's side end position.

There will be clear lenses and colored filters included on the lightbar.

The following switches may be installed in the cab on the switch panel to control the lightbar:

- a switch to control the flashing LED modules.
- the traffic light controller with the emergency master switch only.
- no momentary switch to activate the traffic light controller.

The white flashing LED modules and the traffic light controller will be disabled when the parking brake is applied.

The ten (10) red flashing LED modules in the front positions may be load managed when the parking brake is applied.

LIGHTS, FRONT ZONE LOWER

There will be two (2) Whelen® Model M6**, 4.31" high x 6.75" wide x 1.37" deep flashing LED warning lights installed on the cab face above the headlights, in a common bezel with the directional lights per the following:

- The driver's side front warning light to be red.
- The passenger's side front warning light to be red.
- The warning light lens colors to be the same as the LEDs.

There will be a switch in the cab on the switch panel to control the lights.

DAYTIME RUNNING LIGHTS (HEADLIGHTS)

The low-beam headlights used as daytime running lights will be activated with the following measures:

- Ignition switch is turned on
- Parking brake is released

These lights will be deactivated with any one of the following measures:

- Headlight switch is turned on
- High-beam flash is turned on
- Parking brake is set

HEADLIGHT FLASHER

The high beam headlights will flash alternately between the left and right side.

There will be a switch installed in the cab on the switch panel to control the high beam flash. This switch will be live when the battery switch and the emergency master switches are on.

The flashing will automatically cancel when the hi-beam headlight switch is activated or when the parking brake is set.

SIDE ZONE LOWER LIGHTING

There will be six (6) Whelen®, Model M6**, 4.31" high x 6.75" long x 1.37" deep flashing LED warning lights with chrome trim installed per the following:

- Two (2) lights located, one (1) each side on the front custom cab corner. The driver's side, side front light to include red warning LEDs and the passenger's side, side front light to include red warning LEDs.
- Two (2) lights located, one (1) each side of cab rearward of crew cab doors. The driver's side, side middle light to include red warning LEDs and the passenger's side, side middle light to include red warning LEDs.
- Two (2) lights located, one (1) each side above rear wheels. The driver's side, side rear light to include red warning LEDs and the passenger's side, side rear light to include red warning LEDs.
- The warning light lens colors to be the same as the LEDs.

There will be a switch in the cab on the switch panel to control the lights.

REAR ZONE LOWER LIGHTING

There will be two (2) Whelen®, Model M6*, LED flashing warning lights will be located at the rear of the apparatus.

- The driver's side rear light to be red
- The passenger's side rear light to be red

Both lights will include a lens that is the same color as the LED's.

There will be a switch located in the cab on the switch panel to control the lights.

REAR WARNING LIGHTS

There will be two (2) Whelen®, Model M6**, 4.31" high x 6.75" wide x 1.37" deep flashing LED warning light(s) with chrome trim provided at the rear of the apparatus, one each side, forward, high on the body.

The light(s) to include red flashing LEDs. The warning light lens colors to be the same as the LEDs.

These light(s) will be controlled with the rear upper warning switch.

The light(s) may be load managed when the parking brake is applied.

WARNING LIGHTS (REAR AND SIDE UPPER ZONES)

Four (4) Whelen, model M6* LED flashing warning lights will be provided at the rear of the apparatus with Whelen, 6EFLANGE chrome flanges.

The side rear upper light(s) on the driver's side to be red.

The rear upper light(s) on the driver's side to be red.

The rear upper light(s) on the passenger's side to be red.

The side rear upper light(s) on the passenger's side to be red.

These lights will include a lens that is the same color as the LED's.

There will be a switch located in the cab on the switch panel to control the lights.

TRAFFIC DIRECTING LIGHT

There will be one (1) Whelen®, Model TAL65, 36.00" long x 2.87" high x 2.25" deep, amber LED traffic directing light installed at the rear of the apparatus.

The Whelen, Model TACTL5, control head will be included with this installation.

The controller will be energized when the battery switch is on.

The auxiliary flash to be activated when the parking brake is applied.

This traffic directing light will be recessed with a treadplate trim plate at the rear of the apparatus as high as practical.

The traffic directing light control head will be located in the driver side overhead switch panel in the right panel position.

LOOSE EQUIPMENT

The following equipment will be furnished with the completed unit:

- One (1) bag of chrome, stainless steel, or cadmium plated screws, nuts, bolts and washers, as used in the construction of the unit.

NFPA LOOSE EQUIPMENT

NFPA Required Loose Equipment Provided by Fire Department

The following loose equipment as outlined in NFPA 1900, 2024 edition, table 8.1 and CAN/ULC 515:2024 edition, section 5.2 will be provided by the fire department:

- One (1) traffic vest for each seating position, each vest to comply with ANSI/ISEA 207, *Standard for High Visibility Public Safety Vests*, and have a five-point breakaway feature that includes two (2) at the shoulders, two (2) at the sides, and one (1) at the front.
- Five (5) fluorescent orange traffic cones not less than 28.00" (711 mm) in height, each equipped with a 6.00" (152 mm) retro-reflective white band no more than 4.00" (152 mm) from the top of the cone, and an additional 4.00" (102 mm) retro-reflective white band 2.00" (51 mm) below the 6.00" (152 mm) band.
- Five (5) illuminated warning devices such as highway flares, unless the five (5) fluorescent orange traffic cones have illuminating capabilities.

NFPA Loose Equipment That Should be Considered

The following loose equipment as outlined in NFPA 1900, 2024 edition, appendix table A.8.4 (a) and CAN/ULC 515:2024 edition, section 5.2 should be considered:

- 800 ft (60 m) of 2.50" (65 mm) or larger fire hose.
- 400 ft (120 m) of 1.50" (38 mm), 1.75" (45 mm), or 2.00" (52 mm) fire hose.
- One (1) handline nozzle, 200 gpm (750 L/min) minimum.
- Two (2) handline nozzles, 95 gpm (360 L/min) minimum.
- One (1) smooth bore or combination nozzle with shutoff and with 2.50" (65 mm) inlet that flows a minimum of 250 gpm (950 L/min).
- Four (4) SCBA apparatus
- Four (4) SCBA spare cylinders
- One (1) first aid kit.
- Four (4) combination spanner wrenches.
- Two (2) hydrant wrenches.
- One (1) double female 2.50" (65 mm) adapter with national hose (NH) threads.
- One (1) double male 2.50" (65 mm) adapter with national hose (NH) threads.
- One (1) rubber mallet, for use on suction hose connections.

- Two (2) salvage covers each a minimum size of 12 ft × 18 ft (3.7 m × 5.5 m).
- One (1) automatic external defibrillator (AED).

SOFT SUCTION HOSE

There will be no soft suction hose provided.

DRY CHEMICAL EXTINGUISHER PROVIDED BY FIRE DEPARTMENT

The extinguisher is not on the apparatus as manufactured. The fire department will provide and mount the extinguisher.

WATER EXTINGUISHER PROVIDED BY FIRE DEPARTMENT

The extinguisher is not on the apparatus as manufactured. The fire department will provide and mount the extinguisher.

FLATHEAD AXE PROVIDED BY FIRE DEPARTMENT

The axe is not on the apparatus as manufactured. The fire department will provide and mount the axe.

PICKHEAD AXE PROVIDED BY FIRE DEPARTMENT

The axe is not on the apparatus as manufactured. The fire department will provide and mount the axe.

PAINT PROCESS

The exterior custom cab and body painting procedure will consist of a seven (7) step finishing process as follows:

1. Manual Surface Preparation - All exposed metal surfaces on the custom cab and body will be thoroughly cleaned and prepared for painting. Imperfections on the exterior surfaces will be removed and sanded to a smooth finish. Exterior seams will be sealed before painting. Exterior surfaces that will not be painted include; chrome plating, polished stainless steel, anodized aluminum and bright aluminum treadplate.
2. Chemical Cleaning and Pretreatment - All surfaces will be chemically cleaned to remove dirt, oil, grease, and metal oxides to ensure the subsequent coatings bond well. The aluminum surfaces will be properly cleaned and treated using a high pressure, high temperature 4 step Acid Etch process. The steel and stainless surfaces will be properly cleaned and treated using a high temperature 3 step process specifically designed for steel or stainless. The chemical treatment converts the metal surface to a passive condition to help prevent corrosion.
3. Surfacer Primer - The Surfacer Primer will be applied to a chemically treated metal surface to provide a strong corrosion protective basecoat. A minimum thickness of 2 mils of Surfacer Primer is applied to surfaces that require a Critical aesthetic finish. The Surfacer Primer is a two-component high solids urethane that has excellent sanding properties and an extra smooth finish when sanded.
4. Finish Sanding - The Surfacer Primer will be sanded with a fine grit abrasive to achieve an ultra-smooth finish. This sanding process is critical to produce the smooth mirror like finish in the topcoat.

5. Sealer Primer - The Sealer Primer is applied prior to the Basecoat in all areas that have not been previously primed with the Surfacer Primer. The Sealer Primer is a two-component high solids urethane that goes on smooth and provides excellent gloss hold out when topcoated.
6. Basecoat Paint - Two coats of a high performance, two component high solids polyurethane basecoat will be applied. The Basecoat will be applied to a thickness that will achieve the proper color match. The Basecoat will be used in conjunction with a urethane clear coat to provide protection from the environment.
7. Clear Coat - Two (2) coats of Clear Coat will be applied over the Basecoat color. The Clear Coat is a two-component high solids urethane that provides superior gloss and durability to the exterior surfaces. Lap style and roll-up doors will be Clear Coated to match the body. Paint warranty for the roll-up doors will be provided by the roll-up door manufacturer.

After the cab and body are painted, the color will be verified to make sure that it matches the color standard. Electronic color measuring equipment will be used to compare the color sample to the color standard entered into the computer. Color specifications will be used to determine the color match. A Delta E reading will be used to determine a good color match within each family color.

All removable items such as brackets, compartment doors, door hinges, and trim will be removed and painted separately if required, to ensure paint behind all mounted items. Body assemblies that cannot be finish painted after assembly will be finish painted before assembly.

The paint finish quality levels for critical areas of the apparatus (cab front and sides, body sides and doors, and boom lettering panels) are to meet or exceed Cadillac/General Motors GMW15777 global paint requirements. Orange peel levels are to meet or exceed the #6 A.C.T. standard in critical areas. The manufacture's written paint standards will be available upon request.

Environmental Impact

Contractor will meet or exceed all current state regulations concerning paint operations. Pollution control will include measures to protect the atmosphere, water and soil. Controls will include the following conditions:

- Topcoats and primers will be chrome and lead free.
- Metal treatment chemicals will be chrome free. The wastewater generated in the metal treatment process will be treated on-site to remove any other heavy metals.
- Particulate emission collection from sanding operations will have a 99.99 percent efficiency factor.
- Particulate emissions from painting operations will be collected by a dry filter or water wash process. If the dry filter is used, it will have an efficiency rating of 98 percent. Water wash systems will be 99.97 percent efficient.
- Water from water wash booths will be reused. Solids will be removed on a continual basis to keep the water clean.
- Paint wastes are disposed of in an environmentally safe manner.
- Empty metal paint containers will be recycled to recover the metal.
- Solvents used in clean-up operations will be recycled on-site or sent off-site for distillation and returned for reuse.

Additionally, the finished apparatus will not be manufactured with or contain products that have ozone depleting substances. Contractor will, upon demand, present evidence that the manufacturing facility meets the above conditions and that it is in compliance with his state EPA rules and regulations.

CAB PAINT

The cab will be painted #90 red.

BODY PAINT

The body will be painted to match the lower section of the cab.

PAINT CHASSIS FRAME ASSEMBLY

The chassis frame assembly will be finished with a single system black top coat before the installation of the cab and body, and before installation of the engine and transmission assembly, air brake lines, electrical wire harnesses, etc.

Components treated with epoxy E-coat protection prior to paint:

- Two (2) C-channel frame rails

Components that are included with the chassis frame assembly that will be painted not e-coated (unless otherwise stated in a secondary option) are:

- Cross members
- Axles
- Suspensions
- Steering gear
- Battery boxes
- Bumper extension weldment
- Frame extensions
- Body mounting angles
- Rear Body support substructure (front and rear)
- Pump house substructure
- Steel fuel tank
- Castings
- Individual piece parts used in chassis and body assembly

The E-coat process will meet the technical properties shown.

AXLE HUB PAINT

All axle hubs will be painted to match lower job color.

COMPARTMENT INTERIOR PAINT

The interior of all compartments will be painted with a gray spatter finish for ease of cleaning and to make it easier to touch up scratches and nicks.

REFLECTIVE BAND

A 4.00" white reflective band will be provided across the front of the vehicle and along the sides of the body.

The reflective band provided on the cab face will be at the headlight level.

REAR CHEVRON STRIPING

There will be alternating chevron striping located on the rear-facing vertical surface of the apparatus. The rear surface, excluding the rear compartment door, will be covered.

The colors will be Red V98-12 and Fluorescent Lime V98-112 oralite.

Each stripe will be 6.00" in width.

This will meet the requirements of the current edition of NFPA 1901, which states that 50% of the rear surface will be covered with chevron striping.

"Z" JOG IN REFLECTIVE STRIPE

There will be two (2) "Z"-shaped jog(s) provided in the reflective stripe design.

REFLECTIVE OUTLINE STRIPE

A .25" black reflective outline will be applied to the top and the bottom of the reflective band. There will be four (4) set of outline stripes required.

INVERTED "V" CHEVRON STRIPING ON CAB AND CREW CAB DOORS

There will be alternating chevron striping located on the inside of each cab and crew cab door.

The striping will consist of the following colors:

- The first color will be red diamond grade.
- The second color will be yellow diamond grade.

The size of the striping will be 4.00".

FIRE APPARATUS PARTS MANUAL

There will be one (1) custom parts manual(s) in USB flash drive format for the complete fire apparatus provided.

The manual(s) will contain the following:

- Job number
- Part numbers with full descriptions
- Table of contents
- Parts section sorted in functional groups reflecting a major system, component, or assembly
- Parts section sorted in alphabetical order
- Instructions on how to locate parts

Each manual will be specifically written for the chassis and body model being purchased. It will not be a generic manual for a multitude of different chassis and bodies.

Service Parts Internet Site

The service parts information included in these manuals are also available on the Pierce website. The website offers additional functions and features not contained in this manual, such as digital photographs and line drawings of select items. The website also features electronic search tools to assist in locating parts quickly.

CHASSIS SERVICE MANUALS

There will be one (1) chassis service manuals on USB flash drives containing parts and service information on major components provided with the completed unit.

The manual will contain the following sections:

- Job number
- Table of contents
- Troubleshooting
- Front Axle/Suspension
- Brakes
- Engine
- Tires
- Wheels
- Cab
- Electrical, DC
- Air Systems
- Plumbing
- Appendix

The manual will be specifically written for the chassis model being purchased. It will not be a generic manual for a multitude of different chassis and bodies.

CHASSIS OPERATION MANUAL

The chassis operation manual will be provided on one (1) USB flash drive. The manual will be in the English language.

ONE (1) YEAR MATERIAL AND WORKMANSHIP

A Pierce basic apparatus limited warranty certificate, WA0008, is included with this proposal.

ENGINE WARRANTY

A Cummins **five (5) year** limited engine warranty will be provided. A limited warranty certificate, WA0181, is included with this proposal.

STEERING GEAR WARRANTY

A TRW **one (1) year** limited steering gear warranty will be provided. A copy of the warranty certificate will be submitted with the bid package.

FIFTY (50) YEAR STRUCTURAL INTEGRITY

The Pierce custom chassis frame only (does not include crossmembers) limited warranty certificate, WA0013, is included with this proposal.

FRONT AXLE WARRANTY

A two (2) year/250,000 mile Hendrickson Steertek front axle warranty will be provided.

SINGLE REAR AXLE FIVE (5) YEAR MATERIAL AND WORKMANSHIP WARRANTY

A Meritor™ Axle 5 year limited warranty will be provided.

ABS BRAKE SYSTEM THREE (3) YEAR MATERIAL AND WORKMANSHIP WARRANTY

A Meritor Wabco™ ABS brake system limited warranty certificate, WA0232, is included with this proposal.

TEN (10) YEAR STRUCTURAL INTEGRITY

The Pierce custom cab limited warranty certificate, WA0012, is included with this proposal.

TEN (10) YEAR PRO-RATED PAINT AND CORROSION

A Pierce cab limited pro-rated paint warranty certificate, WA0055, is included with this proposal.

FIVE (5) YEAR MATERIAL AND WORKMANSHIP

The Pierce Command Zone electronics limited warranty certificate, WA0014, is included with this proposal.

CAMERA SYSTEM WARRANTY

Manufacturer's Guarantee will be (2) two years from the manufacture date code under normal use and service. Manufacturer will provide customer service, pre-sales applications assistance, and after-sales technical assistance. Manufacturer will provide technical assistance and support by means of a toll-free telephone number (1-800-645-0074) at no extra charge

COMPARTMENT LIGHT WARRANTY

The compartment lights will not offer an extended warranty.

TRANSMISSION WARRANTY

The transmission will have a **five (5) year/unlimited mileage** warranty covering 100 percent parts and labor. The warranty will be provided by Allison Transmission.

Note: The transmission cooler is not covered under any extended warranty you may be getting on your Allison Transmission. Please review your Allison Transmission warranty for coverage limitations.

TRANSMISSION COOLER WARRANTY

The transmission cooler will carry a five (5) year parts and labor warranty (exclusive to the transmission cooler). In addition, a collateral damage warranty will also be in effect for the first three (3) years of the warranty coverage and will not exceed \$10,000 per occurrence. A copy of the warranty certificate will be included with this proposal.

WATER TANK WARRANTY

A UPF poly water tank limited warranty certificate, WA0195, is included with this proposal.

TEN (10) YEAR STRUCTURAL INTEGRITY

The Pierce apparatus body limited warranty certificate, WA0009, is included with this proposal.

ROLLUP DOOR MATERIAL AND WORKMANSHIP WARRANTY

A R-O-M Corporation rollup door limited warranty will be provided. The mechanical components of the rollup door will be warranted against defects in material and workmanship for a period of seven (7) years. The door ajar switch will be warranted for a period of three (3) years and all other electrical components will be warranted for a period of one (1) year. A seven (7) year limited warranty will be provided on painted rollup doors.

The limited warranty certificate, WA0206, is included with this proposal.

PUMP WARRANTY

A Hale pump limited warranty certificate, WA0388, is included with this proposal.

TEN (10) YEAR PUMP PLUMBING WARRANTY

The Pierce apparatus plumbing limited warranty certificate, WA0035, is included with this proposal.

TEN (10) YEAR PRO-RATED PAINT AND CORROSION

A Pierce body limited pro-rated paint warranty certificate, WA0057, is included with this proposal.

VEHICLE STABILITY CERTIFICATION

The fire apparatus manufacturer will provide a certification stating the apparatus complies with NFPA 1900, current edition, section 7.14, Vehicle Stability. The certification is included with this proposal.

ENGINE INSTALLATION CERTIFICATION

The fire apparatus manufacturer will provide a certification, along with a letter from the engine manufacturer stating they approve of the engine installation in the bidder's chassis. The certification will be provided at the time of delivery.

POWER STEERING CERTIFICATION

The fire apparatus manufacturer will provide a certification stating the power steering system as installed meets the requirements of the component supplier. The certification is included with this proposal.

CAB INTEGRITY CERTIFICATION

The fire apparatus manufacturer will provide a cab crash test certification with this proposal. The certification will state that a specimen representing the substantial structural configuration of the cab has been tested and certified by an independent third party test facility. Testing events will be documented with photographs, real-time and high-speed video, vehicle accelerometers, cart accelerometers, and a laser speed trap. The fire apparatus manufacturer will provide a state licensed professional engineer to witness and certify all testing events. Testing will meet or exceed the requirements below:

- SAE J2422 Cab Roof Strength Evaluation - Quasi-Static Loading Heavy Trucks.
- European Occupant Protection Standard ECE Regulation No.29.
- SAE J2420 COE Frontal Strength Evaluation - Dynamic Loading Heavy Trucks.

Side Impact

The cab will be subjected to dynamic preload where a 14,320-lb moving barrier is slammed into the side of the cab at 5.50 mph, striking with an impact of 13,000 ft-lb of force. This test is part of the SAE J2422 test procedure and more closely represents the forces a cab will see in a rollover incident.

Frontal Impact

The same cab will withstand a frontal impact of 32,600 ft-lb of force using a moving barrier in accordance with SAE J2420.

Additional Frontal Impact

The same cab will withstand a frontal impact of 65,098 ft-lb of force using a moving barrier. (Twice the force required by SAE J2420)

Roof Crush

The cab will be subjected to a roof crush force of 22,500 lb. This value meets the ECE 29 criteria, and is equivalent to the front axle rating up to a maximum of ten (10) metric tons.

Additional Roof Crush

The same cab will be subjected to a roof crush force of 110,000 lbs. (Four and a half times the load criteria of ECE 29)

The same cab will withstand all tests without any measurable intrusion into the survival space of the occupant area.

CAB DOOR DURABILITY CERTIFICATION

Robust cab doors help protect occupants. Cab doors will survive a 200,000 cycle door slam test where the slamming force exceeds 20 G's of deceleration. The bidder will certify that the sample doors similar to those provided on the apparatus have been tested and have met these criteria without structural damage, latch malfunction, or significant component wear.

WINDSHIELD WIPER DURABILITY CERTIFICATION

Visibility during inclement weather is essential to safe apparatus performance. Windshield wipers will survive a 3 million cycle durability test in accordance with section 6.2 of SAE J198 *Windshield Wiper Systems - Trucks, Buses and Multipurpose Vehicles*. The bidder will certify that the wiper system design has been tested and that the wiper system has met these criteria.

ELECTRIC WINDOW DURABILITY CERTIFICATION

Cab window roll-up systems can cause maintenance problems if not designed for long service life. The window regulator design will complete 30,000 complete up-down cycles and still function normally when finished. The bidder will certify that sample doors and windows similar to those provided on the apparatus have been tested and have met these criteria without malfunction or significant component wear.

SEAT BELT ANCHOR STRENGTH

Seat belt attachment strength is regulated by Federal Motor Vehicle Safety Standards and should be validated through testing. Each seat belt anchor design will withstand 3000 lb of pull on both the lap

and shoulder belt in accordance with FMVSS 571.210 Seat Belt Assembly Anchorages. The bidder will certify that each anchor design was pull tested to the required force and met the appropriate criteria.

SEAT MOUNTING STRENGTH

Seat attachment strength is regulated by Federal Motor Vehicle Safety Standards and should be validated through testing. Each seat mounting design will be tested to withstand 20 G's of force in accordance with FMVSS 571.207 Seating Systems. The bidder will certify, at time of delivery, that each seat mount and cab structure design was pull tested to the required force and met the appropriate criteria.

PERFORMANCE CERTIFICATIONS

Cab Air Conditioning

Good cab air conditioning temperature and air flow performance keeps occupants comfortable, reduces humidity, and provides a climate for recuperation while at the scene. The cab air conditioning system will cool the cab from a heat-soaked condition at 100 degrees Fahrenheit to an average of 78 degrees Fahrenheit in 30 minutes. The bidder will certify that a substantially similar cab has been tested and has met these criteria.

Cab Defroster

Visibility during inclement weather is essential to safe apparatus performance. The defroster system will clear the required windshield zones in accordance with SAE J381 Windshield Defrosting Systems Test Procedure And Performance Requirements - Trucks, Buses, And Multipurpose Vehicles. The bidder will certify that the defrost system design has been tested in a cold chamber and passes the SAE J381 criteria.

Cab Auxiliary Heater

Good cab heat performance and regulation provides a more effective working environment for personnel, whether in-transit, or at a scene. An auxiliary cab heater will warm the cab 77 degrees Fahrenheit from a cold-soak, within 30 minutes when tested using the coolant supply methods found in SAE J381. The bidder will certify, at time of delivery, that a substantially similar cab has been tested and has met these criteria.

AMP DRAW REPORT

The bidder will provide, at the time of bid and delivery, an itemized print out of the expected amp draw of the entire vehicle's electrical system.

The manufacturer of the apparatus will provide the following:

- Documentation of the electrical system performance tests.
- A written load analysis, which will include the following:
 - The nameplate rating of the alternator.
 - The alternator rating under the conditions specified per:
 - Current edition of applicable NFPA standards.
 - The minimum continuous load of each component that is specified per:
 - Current edition of applicable NFPA standards.

- Additional loads that, when added to the minimum continuous load, determine the total connected load.
- Each individual intermittent load.

All of the above listed items will be provided by the bidder per the current edition of applicable NFPA standards.